



Thermal Behavior Modeling for Predicting Process Instability in Additive Manufacturing Systems

Debasish Adhikary¹;

[1]. M. E. of Mechanical Engineering, Lamar University, Beaumont, Texas;
Email: chowdhurytonoy93@gmail.com

Doi: [10.63125/b2nemb48](https://doi.org/10.63125/b2nemb48)

Received: 18 September 2023; **Revised:** 29 October 2023; **Accepted:** 21 November 2023; **Published:** 15 December 2023

Abstract

Additive manufacturing systems frequently fail to predict process instability before thermal disturbances generate porosity, cracking, spatter, lack of fusion, distortion, and inconsistent layer consolidation, partly because sensor data, machine settings, thermal models, and quality evidence remain fragmented. This study aimed to develop and quantitatively evaluate an integrated thermal behavior modeling framework for improving Process-Instability Prediction Effectiveness across operational additive manufacturing cases. A quantitative, cross-sectional, descriptive, explanatory, and case-based design was applied to industrial manufacturing facilities, research centers, university laboratories, technology providers, and quality-testing organizations using laser powder-bed fusion, directed-energy deposition, electron-beam melting, and related metal additive manufacturing systems. From 350 distributed questionnaires, 312 valid responses were retained, yielding an effective response rate of 89.14 percent. The model examined Thermal-Process Data Quality and Integration, Heat-Input Consistency and Energy Control, Thermal-Gradient and Heat-Accumulation Management, Melt-Pool Thermal Stability, Cooling and Solidification Behavior Control, Real-Time Thermal Monitoring and Modeling Capability, and Process-Instability Prediction Effectiveness. Five-point Likert data were analyzed in SPSS using descriptive statistics, reliability and validity tests, Pearson correlations, ANOVA, assumption diagnostics, and multiple regression. Cronbach's alpha values ranged from .831 to .914, KMO reached .902, and Bartlett's test was significant, $\chi^2(595) = 4,582.63$, $p < .001$. Process-Instability Prediction Effectiveness recorded $M = 4.07$, $SD = .57$. All six predictors were significant, and the model explained 68.9 percent of outcome variance, $R^2 = .689$, adjusted $R^2 = .683$, $F(6, 305) = 112.61$, $p < .001$. Melt-Pool Thermal Stability was strongest, $\beta = .26$, followed by data quality, $\beta = .23$, and real-time monitoring, $\beta = .21$. The findings imply that coordinated thermal data, energy control, melt-pool stabilization, cooling management, and real-time modeling can strengthen early warnings, reduce defect-generating variation, improve process control, and support more reliable additive manufacturing quality decisions. They provide evidence to prioritize monitoring investments, calibration, model validation, and workforce training.

Keywords

Thermal Behavior Modeling; Additive Manufacturing; Process-Instability Prediction; Melt-Pool Thermal Stability; Real-Time Thermal Monitoring;


INTRODUCTION

Additive manufacturing is a digitally controlled production approach through which three-dimensional components are created by depositing, melting, bonding, or solidifying material in successive layers based on a computer-generated design. Unlike conventional subtractive manufacturing, which removes material from a larger workpiece, additive manufacturing constructs a component through the controlled addition of material at specific spatial locations. Metal additive manufacturing processes commonly use a concentrated laser or electron beam to melt powder particles, wire feedstock, or previously deposited material. This localized energy interaction produces rapid heating, melting, fluid movement, cooling, solidification, and repeated reheating as additional layers are deposited. Thermal behavior in additive manufacturing refers to the spatial and temporal variation of temperature, heat flux, thermal gradients, cooling rates, melt-pool geometry, solidification characteristics, and heat accumulation throughout the manufacturing cycle. Process instability refers to any departure from a controlled, repeatable, and predictable manufacturing condition that disrupts the formation of a stable melt pool, continuous track, uniformly bonded layer, or dimensionally accurate component. Such instability may be expressed through balling, spatter, keyhole fluctuation, track discontinuity, lack of fusion, excessive penetration, pore formation, cracking, residual stress, distortion, and irregular surface development. Early research on selective laser sintering and selective laser melting established that the bonding mechanism depends strongly on whether the supplied thermal energy produces partial melting, complete melting, viscous flow, or liquid-phase consolidation within the processed material (Kruth et al., 2005). Thermal analysis of laser-engineered net shaping also demonstrated that the temperature field is governed by laser power, material properties, latent heat, thermal conduction, convection, radiation, and the evolving shape of the deposited material (Wang & Felicelli, 2006). Single-track investigations further indicated that a stable and continuous deposited track can be achieved only when beam power, scanning speed, powder characteristics, and layer conditions remain within an appropriate processing range (Yadroitsev & Smurov, 2010). Mathematical and numerical studies of electron-beam melting similarly connected process stability with energy input, thermal diffusion, scan conditions, and heat-transfer behavior within the powder bed (Zäh & Lutzmann, 2010). The international significance of thermal behavior modeling is associated with the widespread application of additive manufacturing in aerospace, biomedical engineering, automotive production, energy systems, tooling, defense manufacturing, and other high-value industries in which part failure, geometric inaccuracy, or internal defects can create substantial technical and economic consequences. Residual-stress research has shown that repeated localized heating and constrained cooling generate complex stress distributions that depend on component geometry, material characteristics, substrate conditions, scanning strategy, and thermal history (Mercelis & Kruth, 2006). Thermal behavior modeling therefore provides a systematic basis for measuring, explaining, and predicting the conditions under which additive manufacturing processes remain stable or become vulnerable to defect-generating thermal disturbances.

Thermal behavior within an additive manufacturing system develops through interconnected physical mechanisms involving energy absorption, heat conduction, convection, radiation, melting, evaporation, fluid flow, solidification, and reheating. When a laser or electron beam interacts with a powder bed or deposited surface, part of the supplied energy is absorbed by the material, while another portion may be reflected, scattered, or transferred to the surrounding environment. The absorbed energy raises the local temperature above the melting point and creates a molten region whose dimensions and stability depend on beam characteristics, scanning velocity, material absorptivity, thermal conductivity, heat capacity, latent heat, and boundary conditions. A radiation and heat-transfer model demonstrated that laser energy can penetrate a powder layer through repeated reflections among powder particles, causing nonuniform absorption and complex thermal distributions within the interaction zone (Gusarov et al., 2009). Three-dimensional finite-element analysis further established that successive scanning and layer deposition generate repeated temperature peaks and progressive heat accumulation because previously consolidated layers are reheated by later thermal cycles (Roberts et al., 2009). This repeated exposure can alter local cooling rates, melt-pool depth, microstructural development, residual-stress formation, and dimensional stability. Thermal conditions cannot therefore be represented adequately by a single process parameter such as laser power. Effective energy

input is jointly influenced by scanning speed, hatch spacing, layer thickness, beam diameter, exposure time, scan strategy, powder packing, surface condition, and material properties. Experimental and numerical investigation of single-track, multitrack, and multilayer formation confirmed that different combinations of energy input and scanning conditions produce significant variations in track continuity, overlap, layer consolidation, and defect formation (Wang et al., 2012). Finite-element simulation also showed that unsupported layers experience steep thermal gradients and nonuniform stress development during rapid heating and cooling, increasing the possibility of deformation and process irregularity (Hussein et al., 2013). The changing geometry of an additively manufactured component introduces further complexity because every newly deposited layer modifies the available conductive pathways, exposed surfaces, and heat-transfer boundaries. Element-activation modeling was developed to represent the gradual addition of material and improve the accuracy of transient heat-transfer simulation in metal deposition processes (Michaleris, 2014). Directed-energy-deposition research additionally showed that thermal-model performance depends on the realistic representation of convection generated by shielding and carrier gases around the processing region (Heigel et al., 2015). Thermal-process data quality must therefore include accurate temperature measurements, calibrated sensors, synchronized process parameters, reliable material-property values, appropriate boundary conditions, and a valid representation of the evolving build geometry. Heat-input consistency and energy control refer to the ability of the manufacturing system to maintain a stable relationship among supplied power, interaction time, absorbed energy, melt volume, and heat dissipation throughout tracks, layers, and component regions.

Figure 1: Integrated Framework for Thermal Data Processing, Modeling, and Process-Instability Prediction



Process instability emerges when the thermal condition of the material shifts beyond a stable operating range and the molten region can no longer maintain consistent geometry, flow behavior, and solidification characteristics. Insufficient effective energy input may prevent complete melting and interlayer bonding, resulting in lack-of-fusion defects, discontinuous tracks, unmelted particles, weak interfaces, and irregular surfaces. Excessive energy input may generate intense evaporation, recoil pressure, deep vapor depressions, keyhole formation, violent fluid movement, spatter, and gas entrapment. Direct observations of laser powder-bed fusion revealed a transition from shallow conduction-mode melting to deep keyhole-mode melting as energy intensity increased, and unstable keyhole collapse was associated with the formation of internal voids (King et al., 2014). Powder-scale multiphysics simulation further demonstrated that recoil pressure, capillary forces, Marangoni convection, evaporation, multiple laser reflections, powder displacement, and free-surface deformation

interact during the formation of pores, spatter, and denuded zones (Khairallah et al., 2016). The surrounding powder distribution also affects process stability because powder particles can be removed from regions beside the scanning path through interactions among vapor flow, gas circulation, particle entrainment, and melt-pool dynamics (Matthews et al., 2016). High-speed experimental observation confirmed that plume behavior, shielding-gas movement, particle entrainment, and spatter trajectories change according to laser power and scan speed, modifying both material availability and local energy transfer around the melt pool (Bidare et al., 2018). In situ X-ray imaging provided additional evidence of pore movement, melt-track formation, powder denudation, spatter generation, and Marangoni-driven circulation beneath the visible surface of the powder bed (Leung et al., 2018). High-speed X-ray imaging and diffraction also captured powder ejection, melt-pool development, solidification, phase transformation, and keyhole-pore formation during laser powder-bed fusion (Zhao et al., 2017). These interacting mechanisms show that thermal-gradient and heat-accumulation management are central to process stability because they determine how rapidly heat is transferred away from the melt pool, how intensely surrounding regions are reheated, and how strongly thermal expansion is constrained by previously consolidated material. Melt-pool thermal stability refers to the maintenance of controlled temperature, width, depth, length, surface shape, and internal flow under changing process conditions. Cooling and solidification behavior control refers to the management of cooling rate, solidification-front movement, thermal contraction, and the redistribution of heat into the substrate and surrounding layers. Process instability may begin with an isolated disturbance, although its development generally reflects combined interactions among heat input, material condition, geometry, fluid flow, atmosphere, scan strategy, and accumulated thermal history.

The existing body of additive manufacturing research provides extensive knowledge of heat transfer, melt-pool dynamics, defect formation, monitoring technologies, and thermomechanical simulation, although the findings are distributed across different experimental, computational, and industrial contexts. Track-level studies have explained how process parameters affect continuity, overlap, remelting, and balling. Finite-element investigations have described temperature distributions, thermal gradients, heat accumulation, residual stress, and deformation. High-fidelity multiphysics models have examined recoil pressure, evaporation, fluid flow, Marangoni convection, free-surface movement, spatter, and pore formation. Synchrotron and high-speed imaging studies have directly observed melt-pool evolution, keyhole behavior, particle ejection, pore movement, and solidification. These research traditions provide a strong physical foundation for understanding process instability, but they do not fully explain how consistently thermal-management and prediction capabilities are implemented across operational additive manufacturing systems. A controlled laboratory experiment may establish an accurate relationship between power, speed, and melt-pool depth, while an industrial facility may experience incomplete sensor coverage, inconsistent calibration, fragmented data systems, varying powder conditions, limited model validation, or differences in operator competency. The research gap is therefore associated with the limited integration of established thermal factors into a unified and statistically testable framework that evaluates their individual and combined relationships with Process-Instability Prediction Effectiveness. Residual-stress analysis has shown that geometry, thermal history, material properties, scanning strategy, and substrate constraints act jointly during the manufacturing process (Mercelis & Kruth, 2006). Powder-scale simulation has similarly demonstrated that energy absorption, fluid flow, particle motion, recoil pressure, and pore formation are interdependent rather than isolated mechanisms (Khairallah et al., 2016). Real-time monitoring research has also shown that thermal signatures become meaningful when they are connected with processing location, machine parameters, and identifiable melt-pool events (Zhao et al., 2017). A quantitative cross-sectional study can organize these established thermal factors into measurable constructs and determine whether professionals working with additive manufacturing systems report consistent statistical relationships among them. The case-study context preserves the technical and organizational characteristics of selected additive manufacturing environments. Descriptive statistics can identify the perceived level of implementation of each construct, correlation analysis can measure the direction and strength of the relationships among the study variables, and multiple regression analysis can estimate the unique and combined contribution of each thermal factor to process-

instability prediction. This level of analysis addresses the integration, maturity, consistency, and perceived effectiveness of thermal-management practices across operational cases rather than replacing experimental measurement or mechanistic simulation.

The purpose of this study is to develop and quantitatively evaluate an integrated thermal behavior modeling framework for predicting process instability in additive manufacturing systems. The research adopts a quantitative, cross-sectional, descriptive, explanatory, and case-study-based design using a structured questionnaire measured through a five-point Likert scale. The proposed framework contains six independent variables: Thermal-Process Data Quality and Integration, Heat-Input Consistency and Energy Control, Thermal-Gradient and Heat-Accumulation Management, Melt-Pool Thermal Stability, Cooling and Solidification Behavior Control, and Real-Time Thermal Monitoring and Modeling Capability. Process-Instability Prediction Effectiveness serves as the dependent variable and represents the accuracy, timeliness, reliability, consistency, and operational usefulness with which unstable thermal conditions and defect-generating process regimes are identified. The first research question examines how Thermal-Process Data Quality and Integration influence Process-Instability Prediction Effectiveness. The second research question examines how Heat-Input Consistency and Energy Control, Thermal-Gradient and Heat-Accumulation Management, Melt-Pool Thermal Stability, and Cooling and Solidification Behavior Control Influence Process-Instability Prediction Effectiveness. The third research question examines the contribution of Real-Time Thermal Monitoring and Modeling Capability to the accurate prediction of process instability. Six directional hypotheses are developed from the conceptual framework. H1 proposes that Thermal-Process Data Quality and Integration have a significant positive effect on Process-Instability Prediction Effectiveness. H2 proposes that Heat-Input Consistency and Energy Control have a significant positive effect on Process-Instability Prediction Effectiveness. H3 proposes that Thermal-Gradient and Heat-Accumulation Management have a significant positive effect on Process-Instability Prediction Effectiveness. H4 proposes that Melt-Pool Thermal Stability has a significant positive effect on Process-Instability Prediction Effectiveness. H5 proposes that Cooling and Solidification Behavior Control have a significant positive effect on Process-Instability Prediction Effectiveness. H6 proposes that Real-Time Thermal Monitoring and Modeling Capability have a significant positive effect on Process-Instability Prediction Effectiveness. Descriptive statistics will be used to examine the distribution, mean, and standard deviation of the measured variables. Pearson correlation analysis will be used to determine the direction and strength of bivariate relationships. Multiple regression analysis will be used to estimate the collective explanatory power of the model and the standardized contribution of each predictor. Reliability and validity assessments will be conducted to evaluate the internal consistency and measurement quality of the study constructs. The paper is organized into the introduction, a six-section literature review containing the theoretical and conceptual frameworks, the methodology, twelve results sections, the discussion, the conclusion, recommendations, and the limitations of the study.

Background of the Study

Additive manufacturing has become an important production approach for creating complex components through the controlled deposition and consolidation of material in successive layers. In metal-based additive manufacturing systems, thermal energy supplied by a laser, electron beam, or related heat source governs the melting, flow, cooling, solidification, and bonding of the deposited material. The thermal condition created during processing directly affects melt-pool size, track continuity, interlayer bonding, dimensional accuracy, microstructural development, residual stress, and the overall structural integrity of the manufactured component. The thermal environment is highly dynamic because each new scan or deposited layer changes the geometry of the part, modifies heat-transfer pathways, reheats previously solidified material, and produces new temperature gradients across the build. Variations in laser power, scanning speed, hatch spacing, layer thickness, powder characteristics, material properties, build orientation, shielding conditions, and heat dissipation can therefore alter the stability of the process. When thermal energy is insufficient, the material may not melt completely, causing discontinuous tracks, weak interlayer bonding, unmelted particles, and lack-of-fusion defects. When the supplied energy is excessive, the process may experience deep keyhole formation, violent melt-pool motion, evaporation, spatter, pore entrapment, and localized overheating. Repeated thermal cycling can also generate residual stresses, distortion, cracking, and nonuniform

microstructures throughout the component. Thermal behavior modeling provides a structured method for representing these temperature-dependent processes and identifying the relationships among energy input, heat distribution, melt-pool response, cooling conditions, and process outcomes. It can combine machine parameters, sensor information, material data, boundary conditions, and thermal observations to determine whether the manufacturing process remains within a stable operating range. The growing use of additive manufacturing in aerospace, automotive, biomedical, energy, tooling, and advanced engineering industries has increased the importance of reliable thermal control because many manufactured components operate under demanding mechanical, thermal, and safety conditions. A process that appears stable at the machine-command level may still develop internal thermal disturbances that are not visible during production. For this reason, understanding and modeling thermal behavior have become essential for predicting process instability, reducing defect formation, improving repeatability, and maintaining consistent manufacturing performance across different materials, machines, geometries, and operational environments.

Problem Statement

The central problem addressed by this research is the limited ability of many additive manufacturing systems to predict process instability before thermal disturbances produce visible or internal defects. Although modern machines can control parameters such as laser power, scanning speed, layer thickness, hatch spacing, and build-platform temperature, the commanded values do not always represent the actual thermal condition within the melt pool or deposited layer. The interaction among energy input, powder characteristics, material properties, geometry, surface conditions, gas flow, heat accumulation, and repeated thermal cycling creates complex temperature patterns that can change rapidly during production. In many operational environments, thermal information is collected through pyrometers, infrared cameras, photodiodes, melt-pool sensors, or machine logs, yet these data are often incomplete, unsynchronized, insufficiently calibrated, or separated across different monitoring platforms. Such limitations reduce the capacity of engineers and operators to identify unstable conditions accurately and to connect thermal signals with specific defects or process disruptions. Another problem concerns the inconsistent control of heat input across different regions of a component. Corners, overhangs, thin walls, support interfaces, scan-turning points, and large cross-sectional areas may experience different heating and cooling conditions even when the same nominal parameters are applied. This variation can create excessive thermal gradients, local heat accumulation, irregular melt-pool dimensions, unstable fluid flow, inconsistent solidification, residual stress, porosity, cracking, and geometric distortion. Existing thermal models may also be developed for specific machines, materials, or laboratory conditions, limiting their reliability when transferred to other operating contexts. Simplified models may not fully account for changing geometry, nonlinear material behavior, evaporation, convection, free-surface movement, and the interaction between consecutive layers. Industrial users may therefore possess thermal-monitoring technologies without having a sufficiently integrated modeling framework for converting raw data into timely predictions of instability. The absence of a unified and statistically testable framework also makes it difficult to determine which thermal capability contributes most strongly to prediction effectiveness. Thermal-process data quality, heat-input consistency, thermal-gradient management, melt-pool stability, cooling control, and real-time modeling are commonly studied as separate technical issues. Their combined influence on process-instability prediction remains insufficiently examined within a quantitative, cross-sectional, case-study-based design. This research addresses that problem by evaluating these interconnected factors and determining their individual and collective relationships with Process-Instability Prediction Effectiveness in additive manufacturing systems.

Objectives of the Study

The primary objective of this study is to develop and quantitatively evaluate an integrated thermal behavior modeling framework for predicting process instability in additive manufacturing systems. The study seeks to determine how effectively thermal conditions can be measured, managed, modeled, and interpreted within selected additive manufacturing cases and how these capabilities contribute to the early identification of unstable production conditions. More specifically, the research aims to assess the influence of Thermal-Process Data Quality and Integration on Process-Instability Prediction Effectiveness by examining whether accurate, complete, calibrated, synchronized, and accessible

thermal information improves the reliability of instability identification. It also aims to evaluate the effect of Heat-Input Consistency and Energy Control by determining whether stable management of laser or beam power, scanning speed, energy delivery, exposure time, and related processing parameters strengthens predictive performance. A further objective is to investigate the relationship between Thermal-Gradient and Heat-Accumulation Management and Process-Instability Prediction Effectiveness, particularly in relation to repeated heating, localized temperature differences, interlayer heat buildup, and uneven heat dissipation. The study also seeks to measure the influence of Melt-Pool Thermal Stability by examining whether consistent melt-pool temperature, width, depth, length, and flow behavior support more accurate identification of unstable process regimes. Another objective is to determine how Cooling and Solidification Behavior Control affects prediction effectiveness through the management of cooling rates, solidification patterns, thermal contraction, and interlayer consolidation. The research additionally aims to examine the contribution of Real-Time Thermal Monitoring and Modeling Capability, including sensor deployment, signal processing, model calibration, timely alerts, and the interpretation of thermal data. Through descriptive statistics, the study will identify the perceived implementation level of each construct. Through correlation analysis, it will determine the direction and strength of the relationships among the variables. Through multiple regression modeling, it will estimate the combined explanatory power of the proposed framework and compare the standardized contribution of each predictor. The study also aims to test six research hypotheses and identify the thermal factor that provides the strongest statistical explanation of Process-Instability Prediction Effectiveness. These objectives collectively guide the development of a coherent model that represents thermal instability as the outcome of interconnected data, energy, heat-transfer, melt-pool, solidification, and monitoring capabilities.

Research Hypotheses

The research hypotheses have been developed to test the proposed relationships between the six independent variables and Process-Instability Prediction Effectiveness in additive manufacturing systems. The first hypothesis, H1, states that Thermal-Process Data Quality and Integration have a significant positive effect on Process-Instability Prediction Effectiveness. This hypothesis assumes that accurate, complete, calibrated, synchronized, and properly integrated thermal data improve the ability of a manufacturing system to recognize abnormal temperature patterns and unstable operating conditions. The second hypothesis, H2, states that Heat-Input Consistency and Energy Control have a significant positive effect on Process-Instability Prediction Effectiveness. This relationship is based on the expectation that stable energy delivery and controlled process parameters make thermal responses more predictable and reduce unexplained variations in melt-pool behavior. The third hypothesis, H3, proposes that Thermal-Gradient and Heat-Accumulation Management have a significant positive effect on Process-Instability Prediction Effectiveness. Effective management of temperature differences, repeated reheating, local overheating, and interlayer heat buildup is expected to improve the identification of conditions associated with distortion, residual stress, cracking, and unstable consolidation. The fourth hypothesis, H4, states that Melt-Pool Thermal Stability has a significant positive effect on Process-Instability Prediction Effectiveness. Consistency in melt-pool temperature, geometry, penetration, and fluid behavior is expected to provide measurable indicators of process stability and facilitate early detection of transitions toward keyholing, balling, porosity, or track discontinuity. The fifth hypothesis, H5, proposes that Cooling and Solidification Behavior Control have a significant positive effect on Process-Instability Prediction Effectiveness. Controlled cooling and repeatable solidification are expected to reduce unpredictable thermal contraction, nonuniform microstructure, interlayer inconsistency, and defect formation. The sixth hypothesis, H6, states that Real-Time Thermal Monitoring and Modeling Capability has a significant positive effect on Process-Instability Prediction Effectiveness. This hypothesis reflects the expectation that effective sensors, data-processing systems, calibrated models, real-time alerts, and technically competent personnel improve the timeliness and accuracy of instability prediction. Each hypothesis will be tested through multiple regression analysis using a significance level of .05. A hypothesis will be supported when the corresponding regression coefficient is positive, statistically significant, and consistent with the proposed conceptual relationship. The six hypotheses collectively represent the main statistical structure of the research model and enable the study to compare the relative explanatory contribution

of the proposed thermal-behavior factors.

Significance of the Research

i. **Significance for additive manufacturing engineers and machine operators:** The research provides a structured understanding of how thermal-process data, heat input, melt-pool behavior, cooling conditions, and real-time monitoring collectively influence process-instability prediction. Engineers and machine operators may use the identified relationships to interpret thermal variations more systematically and distinguish normal process fluctuations from conditions associated with defect formation. The framework may also support more informed parameter adjustment and monitoring decisions during production.

ii. **Significance for manufacturing organizations:** Additive manufacturing organizations require consistent product quality, reliable production cycles, and reduced material waste. By identifying the thermal factors that make the strongest contribution to instability prediction, the study provides evidence that can guide resource allocation, monitoring-system selection, process-control improvement, model validation, and workforce training. The results may help organizations prioritize the most influential capabilities rather than treating all thermal-control activities as equally important.

iii. **Significance for quality-control and process-monitoring professionals:** The research establishes measurable constructs for evaluating Thermal-Process Data Quality and Integration, Heat-Input Consistency and Energy Control, Thermal-Gradient and Heat-Accumulation Management, Melt-Pool Thermal Stability, Cooling and Solidification Behavior Control, and Real-Time Thermal Monitoring and Modeling Capability. These constructs may assist quality professionals in developing assessment criteria, monitoring protocols, audit procedures, and performance indicators for additive manufacturing systems.

iv. **Significance for researchers and academic institutions:** The study contributes a quantitative, cross-sectional, case-study-based framework that translates complex thermal mechanisms into statistically measurable variables. It connects engineering concepts with descriptive analysis, correlation testing, and regression modeling. This structure provides an empirical basis for examining the combined effects of multiple thermal capabilities rather than investigating only one process parameter or defect mechanism.

v. **Significance for technology developers:** Developers of additive manufacturing machines, sensors, thermal cameras, simulation software, digital twins, and predictive-control platforms may use the findings to understand which data and modeling capabilities are most closely associated with effective instability prediction. The results may support the design of integrated monitoring interfaces, improved alert systems, better sensor synchronization, and more interpretable thermal models.

vi. **Significance for high-value industrial sectors:** Aerospace, automotive, biomedical, energy, defense, and advanced tooling industries depend on components that satisfy strict requirements for geometry, density, strength, and reliability. The study addresses the thermal conditions that influence hidden defects, residual stress, cracking, distortion, and inconsistent material consolidation. A clearer understanding of these relationships is therefore relevant to sectors in which production failure can produce substantial financial, operational, and safety consequences.

LITERATURE REVIEW


The literature on thermal behavior modeling in additive manufacturing covers a broad range of scientific, computational, and operational issues associated with heat generation, heat transfer, melting, fluid movement, cooling, solidification, residual stress, defect formation, and process monitoring. Metal additive manufacturing systems create components through highly localized and repeated thermal cycles in which a laser, electron beam, or related energy source interacts with powder, wire, or previously deposited material. These interactions generate steep temperature gradients, rapid phase changes, moving melt pools, repeated reheating, and continuously changing boundary conditions. The resulting thermal history influences track formation, layer bonding, microstructure, dimensional accuracy, porosity, cracking, surface condition, residual stress, and distortion. The literature therefore treats thermal behavior as one of the principal foundations of process stability and final component quality. Studies have examined how laser power, scanning speed, layer thickness, hatch spacing, beam diameter, exposure strategy, powder characteristics, material properties, build geometry, support structures, shielding conditions, and substrate temperature affect the distribution and dissipation of

heat. Other research has focused on melt-pool geometry, keyhole formation, recoil pressure, evaporation, Marangoni convection, spatter, particle entrainment, balling, and pore development. A further body of literature has investigated cooling rates, solidification patterns, microstructure formation, thermal contraction, stress development, and the accumulation of heat across multiple layers. Computational approaches include analytical heat-source models, finite-element methods, computational fluid dynamics, multiphysics simulations, reduced-order models, statistical techniques, machine-learning systems, and digital-twin frameworks. Monitoring studies have examined pyrometers, infrared cameras, photodiodes, high-speed imaging, acoustic signals, X-ray imaging, layerwise inspection, and integrated sensor platforms. These research streams establish that process instability cannot be explained by a single thermal parameter because instability develops through interactions among data quality, energy delivery, heat redistribution, melt-pool response, cooling behavior, and monitoring capability. The present literature review is organized to examine these interconnected dimensions systematically. It begins with thermal behavior and process instability in additive manufacturing systems, then reviews thermal-process data quality, heat-input consistency, thermal gradients, heat accumulation, melt-pool stability, cooling and solidification, and real-time thermal monitoring and modeling. It also introduces the theoretical framework used throughout the study and develops the conceptual framework and research hypotheses that guide the quantitative analysis.

Thermal Behavior and Process Instability

Thermal behavior in additive manufacturing refers to the generation, transfer, accumulation, and dissipation of heat during the layerwise formation of a component. In metal systems, a laser or electron beam delivers concentrated energy to powder, wire, or a previously deposited surface, producing localized melting followed by rapid cooling and solidification. The resulting temperature field is neither uniform nor stationary because the heat source moves continuously while the geometry, material state, and thermal boundaries change after every deposited track and layer. Thermal behavior therefore includes peak temperature, melt-pool width and depth, thermal gradient, cooling rate, reheating frequency, interlayer temperature, and the duration for which material remains above critical transformation temperatures. These variables influence grain growth, phase formation, texture, residual stress, distortion, density, and mechanical performance. The thermal cycle is particularly severe in metal additive manufacturing because a small material volume may experience repeated heating and cooling rapidly. The relationship between processing route, thermal cycle, microstructure, and properties has become central to explaining why identical machine settings may generate different outcomes across materials or geometries ([Herzog et al., 2016](#); [Kanti, 2020](#)). Thermal modeling attempts to represent these interactions through analytical, numerical, statistical, or data-driven descriptions of energy absorption and heat transfer. Such models may include conduction, convection, radiation, latent heat, material activation, changing boundary conditions, and temperature-dependent properties. Their effectiveness depends on the appropriateness of physical assumptions and the quality of process data used for calibration and validation. Reviews of additive manufacturing models have emphasized that melting, solidification, vaporization, heat transfer, mass transfer, and control behavior are closely connected, making simplified representation difficult when multiple mechanisms act simultaneously ([Bikas et al., 2016](#)). Thermal behavior must thus be treated as a dynamic system response rather than as the direct product of one isolated parameter, since instability emerges from interacting energy, material, geometry, and environmental conditions.

Figure 2: Thermal Behavior–Process Instability Interaction Framework for Additive Manufacturing




Process instability arises when the thermal response leaves a controllable operating range and the melt pool, deposited track, or solidifying layer no longer behaves consistently. At low effective energy input, incomplete melting and inadequate overlap may produce lack-of-fusion pores, discontinuous tracks, weak interlayer bonds, and unmelted particles. At excessive energy input, strong evaporation and recoil pressure may deepen the molten cavity, promote keyhole fluctuation, eject spatter, disturb the powder bed, and trap gas during collapse. Instability may also develop when scan turns, thin walls, overhangs, supports, or changes in cross-sectional area cause variations in heat accumulation and dissipation. These local differences influence melt-pool dimensions, thermal gradients, solidification velocity, and cooling rate, so a parameter set stable in one region may become unstable elsewhere. The process-structure-property relationship shows that thermal history governs microstructural evolution and defect susceptibility through interacting effects of energy absorption, fluid flow, solidification, alloy chemistry, and geometric constraint (Debasish, 2021; DebRoy et al., 2018). Defects are therefore physical records of unstable process conditions rather than independent outcomes. Porosity may result from lack of fusion, keyhole collapse, entrapped gas, or unstable melt flow, while distortion and cracking are associated with nonuniform contraction, steep temperature gradients, and accumulated stress. Surface irregularities, elevated edges, and track discontinuities can interfere with powder recoating and create secondary disturbances in later layers. Reviews linking defect mechanisms with in situ sensing have shown that meaningful instability assessment requires identification of the defect category and corresponding measurable process signature (Grasso & Colosimo, 2017; Abdur & Iftekhhar, 2021). Thermal intensity, melt-pool area, plume behavior, spatter activity, layer appearance, and temperature distribution may each reveal a different aspect of instability. No single signal can represent every mechanism universally. Interpretation must connect thermal observations with material properties, machine commands, scan position, component geometry, and the timing of the disturbance within the build sequence with precision.

Analyzing thermal behavior and process instability requires an integrated view of process parameters, system responses, defect mechanisms, and monitoring variables. Machine parameters such as power, scan speed, hatch spacing, layer thickness, beam diameter, dwell time, preheating temperature, powder-feed rate, and gas flow determine how energy enters the material. Their effects are mediated by absorptivity, conductivity, heat capacity, latent heat, viscosity, surface tension, powder packing, and

component geometry. The resulting thermal response is expressed through temperature distribution, melt-pool geometry, cooling rate, thermal gradient, heat accumulation, oscillation, and solidification behavior. When these responses exceed stable limits, defects may appear through porosity, cracking, warping, delamination, balling, spatter, surface roughness, dimensional deviation, or recoating interference. A classification of powder-bed-fusion defects and contributing parameters demonstrated that effective online control depends on organizing manufacturing features so that defects can be connected with measurable causes and controllable inputs (Malekipour & El-Mounayri, 2018; Chowdhury & Tonay, 2022). This relationship is important because the same visible defect may originate from different thermal mechanisms, and one unstable mechanism may produce several defect types. Reliable modeling must therefore distinguish correlation from physical causation while accounting for interactions among variables. For the present study, Thermal-Process Data Quality and Integration represent the accuracy and coordination of thermal information; Heat-Input Consistency and Energy Control represent the stability of delivered energy; Thermal-Gradient and Heat-Accumulation Management represent spatial and temporal heat redistribution; Melt-Pool Thermal Stability represents the repeatability of molten-region geometry and behavior; Cooling and Solidification Behavior Control represent the consistency of phase transformation and contraction; and Real-Time Thermal Monitoring and Modeling Capability represents the ability to detect, interpret, and model changes during processing. These dimensions collectively describe the system conditions under which Process-Instability Prediction Effectiveness can be assessed. Their separation into measurable constructs supports statistical evaluation while preserving the interconnected physical nature of thermal instability across additive manufacturing operations.

Thermal-Process Data Quality and Energy Control

Thermal-Process Data Quality and Integration form the informational foundation of reliable process-instability prediction because a model cannot represent the thermal state accurately when its inputs are incomplete, poorly calibrated, temporally misaligned, or separated from machine commands. Additive manufacturing systems generate heterogeneous data from laser-power controllers, scan-path files, pyrometers, photodiodes, infrared cameras, oxygen sensors, recoater logs, platform-temperature sensors, and post-build inspection records. These sources differ in sampling frequency, spatial resolution, sensitivity, coordinate reference, and physical meaning. Effective integration therefore requires that signals be calibrated, filtered, time-stamped, spatially registered, and connected with the track, layer, geometry, and parameter setting that produced them. Quality management research identified powder condition, temperature management, process-gas atmosphere, melt-pool behavior, and documentation as interdependent information domains, demonstrating that thermal quality cannot be assessed from a single sensor stream or isolated parameter record (Berumen et al., 2010; Zahidul & Begum, 2022). Data completeness is equally important because missing intervals may conceal short instability events such as spatter bursts, keyhole collapse, abnormal cooling, or localized overheating. Accuracy also depends on emissivity assumptions, optical-path contamination, sensor saturation, viewing angle, and reflected radiation, all of which can distort apparent temperature or radiant intensity. The large number of controllable and uncontrollable variables in selective laser melting makes standardized data definitions and traceable acquisition procedures essential for comparing builds and interpreting process signatures consistently (Nishat & Kaniz, 2022; Spears & Gold, 2016). Within the present study, Thermal-Process Data Quality and Integration therefore include measurement accuracy, sensor calibration, synchronization, accessibility, completeness, interoperability, and the linkage of thermal observations with process parameters and quality outcomes. When these conditions are established, statistical and physical models receive evidence from which abnormal thermal patterns can be separated from variation; when they are weak, even sophisticated prediction algorithms may produce unstable coefficients, false alarms, overlooked defects, or conclusions that cannot be transferred across machines, materials, operators, and cases.

Figure 3: Integrated Data and Energy Control Framework for Process-Instability Prediction

Heat-Input Consistency and Energy Control describe the ability of an additive manufacturing system to deliver thermal energy in a repeatable and appropriate manner throughout scanning, deposition, and layer formation. Laser power, scan speed, hatch spacing, layer thickness, beam diameter, exposure time, pulse characteristics, and path sequence jointly determine the amount and distribution of energy absorbed by the material. Their effects are modified by powder absorptivity, packing density, surface condition, alloy composition, build geometry, substrate temperature, and heat dissipation. A stable nominal power setting does not guarantee stable thermal behavior because local geometry can change the conductive path and cause the same command to produce different melt-pool dimensions in thin walls, overhangs, corners, or large cross-sections. Online temperature-monitoring research showed that high-resolution optical and two-wavelength pyrometric measurements can detect deviations in brightness temperature, colour temperature, and focal-zone thermal response when process conditions vary (Chivel & Smurov, 2010; Badrul & Mominul, 2023). These measurements are useful only when the relationship between recorded radiation and actual process behavior is understood, since emissivity changes, plume interference, reflected laser energy, and optical contamination may affect the signal. Energy control consequently requires more than parameter selection before the build; it involves maintaining the intended thermal response as material, location, and geometry change. Process-monitoring scholarship has emphasized that sensors become valuable for control when measured signatures are linked to controllable inputs and verified quality characteristics rather than merely stored as observational data (Tapia & Elwany, 2014). In this study, Heat-Input Consistency and Energy Control include power stability, scan-speed accuracy, appropriate parameter combinations, local adjustment, repeatability across layers, and prevention of underheating or overheating. Consistent energy delivery is expected to create interpretable thermal patterns, whereas uncontrolled variation can obscure causal relationships, shift the process between conduction and keyhole regimes, disturb solidification, and weaken the statistical association between monitored conditions and predicted instability.


The interaction between data quality and energy control determines whether thermal behavior becomes dependable evidence for process-instability prediction. High-quality signals without controllable energy inputs may document disturbances but offer limited explanatory or corrective value. Conversely, carefully selected parameters without integrated monitoring may produce acceptable components in one build yet provide little evidence of equivalent thermal conditions across

layers, geometries, machines, or material batches. An effective framework therefore requires a closed informational chain linking commanded parameters, actual machine performance, measured thermal signatures, model estimates, and verified part characteristics. Reviews show that infrared imaging, pyrometry, photodiodes, visible cameras, acoustic methods, and layerwise inspection differ in the defects they can observe, the scales they represent, and their measurement reliability (Everton et al., 2016). Integration should not mean collecting every signal. It should mean selecting complementary data that capture energy delivery, melt-pool response, surrounding thermal conditions, and resulting quality, then preserving their temporal and spatial relationships. Statistical preprocessing is also necessary to address noise, drift, outliers, missing observations, unequal sampling rates, and sensor-specific units before correlation or regression models are estimated. In a cross-sectional case-study design, assessments of calibration, synchronization, accessibility, parameter stability, and control maturity can indicate how consistently these capabilities are implemented across operational settings. The relationship proposed in the present research assumes that better integrated data improve the visibility of abnormal thermal conditions, while consistent energy control reduces unexplained variability in those conditions. Together, they make instability signatures more repeatable and support stronger associations between measured predictors and Process-Instability Prediction Effectiveness. This combined perspective also prevents thermal data from being treated as detached numerical records and energy settings from being treated as fixed instructions; both are components of a coordinated control system that depends on measurement traceability, physical interpretation, operational discipline, and documented links between process behavior and manufactured quality overall.

Thermal Gradients and Melt-Pool Stability

Thermal gradients describe the spatial rate of temperature change within and around the melt pool, deposited track, previously solidified layers, substrate, and surrounding powder during additive manufacturing. They arise because a concentrated energy source heats a very small material volume to temperatures above melting while neighboring regions remain substantially cooler. The resulting difference creates rapid conductive heat flow away from the interaction zone and produces unequal expansion, contraction, and solidification across the component. The magnitude and direction of a thermal gradient are controlled by laser or electron-beam power, scanning speed, beam diameter, material conductivity, absorptivity, layer thickness, preheating temperature, scan strategy, build geometry, and the thermal contact between the component and substrate. Free surfaces and geometric edges are especially important because they reduce the amount of neighboring material available to conduct heat away. Analytical modeling of thin-wall deposition has shown that proximity to a free edge can alter melt-pool geometry even when the nominal process parameters remain unchanged, demonstrating that local geometry must be incorporated into any reliable representation of thermal behavior (Gockel et al., 2016). Large gradients also affect the relationship between the temperature gradient and solidification velocity, which governs grain morphology, microstructural directionality, and the consistency of material formation. Thermal-gradient management therefore involves maintaining an appropriate spatial distribution of heat rather than simply reducing the maximum temperature. Excessively steep gradients can intensify thermal stress and localized contraction, while gradients that become too small through excessive heat accumulation can enlarge the molten region, slow solidification, and encourage overheating. Experimental and macroscopic numerical analysis of selective electron-beam melting has further demonstrated that melt-pool lifetime increases approximately linearly with line energy, whereas melt-pool width and depth respond nonlinearly, confirming that apparently proportional changes in energy input do not produce proportionate thermal outcomes (Riedlbauer et al., 2017). These findings establish thermal gradients as dynamic, geometry-dependent indicators of heat redistribution that must be interpreted alongside melt-pool dimensions, material state, and temporal exposure.

Figure 4: Integrated Framework of Thermal Gradients, Heat Accumulation, and Melt-Pool Stability in Additive Manufacturing



Heat accumulation refers to the progressive retention of thermal energy when a new scan vector or deposited layer begins before heat from earlier processing has fully dissipated. It is influenced by vector length, hatch spacing, scan sequence, interlayer delay, component height, local cross-sectional area, support configuration, substrate contact, and the thermal properties of the powder and consolidated material. At the beginning of a build, the substrate may provide a relatively effective heat sink, but the growing component can become increasingly separated from that sink as additional layers are added. Previously deposited regions then experience repeated thermal cycles in which their temperatures rise and fall several times, changing local microstructure and producing nonuniform thermal histories through the build height. Heat accumulation may be particularly pronounced in short scan vectors, narrow walls, overhangs, bridge sections, corners, and isolated features because the laser returns rapidly to nearby material or because conductive pathways are limited. Investigations of Ti-6Al-4V selective laser melting have connected power and scan-speed combinations with changes in melt-pool shape, porosity, and microstructural inhomogeneity, showing that low energy can leave irregular lack-of-fusion pores while high energy can produce rounded pores associated with keyhole behavior and repeated thermal cycling (Dilip et al., 2017). Effective management requires attention to both the total supplied energy and the interval over which neighboring regions receive that energy. Longer cooling periods, altered scan order, island strategies, rotation of scan directions, platform preheating, adaptive power, and geometry-specific parameter adjustment can change how heat accumulates spatially and temporally. Constant parameters may not maintain a constant thermal state because heat flow changes as the laser moves from well-supported regions to areas with restricted conduction. Closed-loop experiments using pyrometric measurement have shown that geometry-related heat-flow variation produces measurable melt-pool temperature deviations and that a combined feedforward and feedback strategy can reduce those deviations substantially (Renken et al., 2019). Heat-accumulation management is therefore a continuous regulation problem involving the thermal memory of preceding vectors and layers, not a one-time parameter-selection task completed before manufacturing begins. Melt-pool stability represents the capacity of the molten region to maintain controlled temperature, width, depth, length, lifetime, surface shape, penetration, and fluid-flow behavior as the energy source moves through changing geometric and thermal conditions. A stable melt pool must absorb sufficient


energy to fuse the intended material volume and create continuous bonding without entering regimes characterized by incomplete melting, excessive evaporation, deep keyholing, violent oscillation, track breakup, or uncontrolled spatter. Stability is affected by the balance among absorbed power, scanning velocity, powder delivery, conduction into the surrounding solid, radiative and convective losses, latent heat, surface tension, viscosity, buoyancy, recoil pressure, and Marangoni circulation. Since these mechanisms act on short time and length scales, a melt pool can change rapidly even when machine commands appear constant. The same laser power and scanning speed may create different melt-pool responses at a corner, thin wall, overhang, or heat-affected region because the local temperature and conductive boundary conditions have changed. Melt-pool stability should therefore be evaluated as a controlled response variable rather than inferred solely from nominal settings or a combined energy-density measure. Physics-based multivariable modeling has demonstrated that melt-pool geometry and temperature can be represented together and regulated through coordinated adjustment of laser power and scan speed, allowing a feedback controller to track reference trajectories instead of permitting thermal deviations to develop without correction (Wang et al., 2017). Within the proposed research, Melt-Pool Thermal Stability includes consistency of melt-pool temperature, dimensions, penetration, lifetime, and response to changing process conditions. Its relationship with Thermal-Gradient and Heat-Accumulation Management is reciprocal: gradients and accumulated heat shape the melt pool, while melt-pool size and lifetime determine how much heat is transferred into adjacent tracks and underlying layers. A reliable process-instability model must consequently examine whether the system detects departures from stable melt-pool behavior early, links them to local thermal conditions, and distinguishes temporary signal variation from sustained movement toward lack of fusion, keyhole porosity, distortion, or other defect-generating regimes.

Real-Time Thermal Monitoring and Modeling

Cooling and solidification behavior determine how the molten region produced during additive manufacturing transforms into a stable track, layer, and final component. Cooling begins as soon as the moving heat source leaves a material point, although the rate of temperature reduction varies with laser or electron-beam power, scanning speed, layer thickness, hatch spacing, material conductivity, substrate temperature, component geometry, and the amount of heat retained from preceding scans. Rapid heat extraction commonly produces high cooling rates and steep thermal gradients, which influence nucleation, grain-growth direction, phase transformation, dendrite spacing, and the development of residual stress. Slower cooling can enlarge the heat-affected region, prolong melt-pool lifetime, and increase the possibility of heat accumulation, while excessively rapid cooling may promote brittle phases, fine martensitic structures, and strong directional solidification. The solidification behavior of Ti-6Al-4V produced by selective laser melting has shown that the interaction of scan strategy, local thermal history, and epitaxial growth can generate elongated prior-beta grains across multiple layers, while rapid cooling promotes a fine acicular martensitic alpha-prime structure within those grains (Thijs et al., 2010). This relationship illustrates that the final microstructure records the complete thermal history rather than only the peak temperature achieved during a single scan. Control of solidification therefore requires attention to temperature gradient, solidification velocity, cooling rate, melt-pool geometry, and the orientation of heat flow. Process mapping in electron-beam wire-feed additive manufacturing has further demonstrated that melt-pool cross-sectional area and aspect ratio can be linked with beta-grain size and morphology, allowing solidification outcomes to be interpreted through measurable melt-pool dimensions (Gockel et al., 2014). In the present research, Cooling and Solidification Behavior Control refers to the consistency with which the system manages cooling rates, phase transformation, thermal contraction, grain development, interlayer consolidation, and the transition from liquid metal to a structurally stable deposit. Instability becomes more likely when these conditions vary unpredictably between tracks, layers, or geometric regions because inconsistent solidification can produce nonuniform microstructures, weak interfaces, cracking susceptibility, residual stress, distortion, and changes in mechanical performance. Thermal modeling provides the analytical connection between process inputs and the cooling and solidification conditions that cannot be observed completely through surface measurements alone. A useful model must represent the moving heat source, temperature-dependent material properties, latent heat, heat conduction, convection, radiation, deposition sequence, changing geometry, and the repeated

reheating of previously solidified material.

Figure 5: Integrated Framework of Cooling, Solidification, and Real-Time Thermal Monitoring for Process-Instability Prediction



It must also estimate quantities that are difficult to measure directly, including local cooling rate, temperature gradient, solidification velocity, melt-pool lifetime, and the thermal cycles experienced beneath the visible surface. Three-dimensional heat-transfer and fluid-flow modeling of multilayer laser deposition has shown that melt-pool geometry, peak temperature, cooling rate, and solidification parameters vary spatially as successive layers are added and the thermal condition of the build evolves (Manvatkar et al., 2015). This spatial variation means that a model calibrated only at one location or one layer may fail to represent the thermal behavior of the full component. Modeling accuracy also depends on whether the governing assumptions match the physical process, particularly when convection within the melt pool, temperature-sensitive properties, powder-to-solid transitions, and local boundary conditions influence heat transfer. A coupled finite-element and phase-field investigation of Ti-6Al-4V selective laser melting found that changes in scanning speed alter the computed temperature gradient and cooling rate, which then affect columnar growth, dendritic development, and microsegregation during solidification (Ding et al., 2019). Such findings show that thermal models can connect macroscopic machine parameters with microscopic structural outcomes when information is transferred consistently across modeling scales. For process-instability prediction, modeling capability should therefore be evaluated through model calibration, validation against measured data, sensitivity to parameter changes, representation of geometry, computational timeliness, and the ability to distinguish stable solidification from defect-generating thermal conditions. A model that reproduces average temperatures but ignores rapid local transitions may overlook conditions associated with cracking, lack of fusion, excessive remelting, or abnormal grain formation. Thermal modeling is most informative when predicted temperature histories, cooling rates, gradients, and melt-pool dimensions are synchronized with process position and compared with physical measurements or post-build evidence.

Real-Time Thermal Monitoring and Modeling Capability converts dynamic process behavior into evidence that can be used to identify instability while material is being deposited, melted, cooled, and solidified. Monitoring systems may employ infrared cameras, pyrometers, photodiodes, visible-light cameras, coaxial imaging, off-axis imaging, acoustic sensors, or combinations of these technologies. Their purpose is not simply to record radiation or images, but to extract interpretable features such as apparent temperature, melt-pool width, length, area, aspect ratio, cooling profile, plume intensity, spatter activity, and layerwise thermal distribution. Real-time usefulness depends on adequate


sampling frequency, spatial resolution, optical access, calibration, emissivity treatment, signal filtering, and synchronization with machine position and commanded parameters. Visual measurement research in laser direct metal deposition has shown that melt-pool boundaries can be identified in real time through image processing and threshold calibration, enabling accurate estimation of melt-pool width for process-quality control (Liu et al., 2021). This type of capability is important because melt-pool dimensions respond rapidly to changes in energy input, powder delivery, substrate condition, geometry, and accumulated heat. A monitoring signal becomes more valuable when it is connected with a model that explains what the observed change means physically. For example, an increase in radiant intensity may indicate higher temperature, a larger emitting area, changed emissivity, plume interference, or a combination of these effects, so interpretation requires calibration and contextual information. The proposed construct therefore includes sensor availability, data-acquisition speed, feature extraction, model integration, anomaly detection, alert timeliness, and the technical competence needed to interpret the results. It also includes the capacity to compare measured behavior with expected thermal trajectories and to recognize sustained deviations associated with unstable cooling, keyhole formation, heat accumulation, or irregular solidification. Within the conceptual framework, Real-Time Thermal Monitoring and Modeling Capability is positioned as a direct predictor of Process-Instability Prediction Effectiveness because it determines whether thermal disturbances are detected, analyzed, and classified with sufficient accuracy and speed. Cooling and solidification control provide the physical target of observation, while monitoring and modeling provide the measurement and analytical mechanisms through which that target is evaluated across successive tracks and layers.

Theoretical Framework: Statistical Process Control Theory

Statistical Process Control Theory provides the theoretical foundation for this study because it explains how process variation can be measured, interpreted, and controlled before it develops into unacceptable product variation. The theory distinguishes between common-cause variation, which arises from the normal structure of a process, and special-cause variation, which reflects identifiable disturbances that move the process away from its stable condition. Applied to additive manufacturing, this distinction is essential because every layer contains natural fluctuations in temperature, melt-pool dimensions, cooling rate, sensor response, powder distribution, and local heat flow, while abnormal changes may indicate insufficient fusion, excessive heat accumulation, keyhole formation, unstable solidification, or another defect-generating condition. Statistical Process Control does not assume that every deviation is a failure. Instead, it requires the establishment of an expected process pattern and the identification of observations that differ meaningfully from that pattern in magnitude, persistence, timing, or spatial location. This logic corresponds closely with thermal behavior modeling because the proposed framework seeks to determine whether thermal-process capabilities create stable and interpretable conditions from which instability can be predicted. Image-based statistical monitoring has demonstrated that high-dimensional video streams can be converted into indicators of in-control and out-of-control thermal behavior by incorporating temporal dependence and spatial relationships among pixels, which is particularly relevant for detecting localized overheating during layerwise production (Colosimo & Grasso, 2018). Sensor-based build-condition monitoring has similarly shown that photodetector, high-speed-camera, and thermal-camera signals can be transformed into process-state evidence identifying locations with a greater probability of defect formation (Montazeri & Rao, 2018). Within this research, process stability is represented by consistent heat input, manageable thermal gradients, repeatable melt-pool behavior, controlled cooling and solidification, and dependable monitoring outputs. Assignable disturbances are represented by abnormal thermal patterns that alter these conditions and reduce prediction effectiveness. Statistical Process Control Theory therefore supports the treatment of thermal instability as measurable process variation rather than as an unpredictable event. Applying Statistical Process Control Theory to additive manufacturing requires an expansion from conventional univariate measurements to multivariable, spatially distributed, and time-dependent data. Traditional control applications may monitor one dimension, weight, or pressure value, whereas additive manufacturing can generate thousands of observations from thermal cameras, photodiodes, pyrometers, machine logs, layer images, and parameter records. These observations are influenced by geometry, scan position, layer number, material state, sensor configuration, and the thermal memory created by preceding tracks and layers. The framework

therefore treats process control as a sequence connecting input conditions, process signatures, modeled thermal states, and quality-related outcomes. Thermal-Process Data Quality and Integration establish whether information entering the control system is accurate, calibrated, synchronized, complete, and linked to the correct processing event. Heat-Input Consistency and Energy Control describe whether commanded settings produce a repeatable thermal response. Thermal-Gradient and Heat-Accumulation Management indicate whether spatial and temporal temperature differences remain manageable.

Figure 6: Statistical Process Control Framework for Thermal Process Stability and Process-Instability Prediction



Melt-Pool Thermal Stability captures the repeatability of the immediate molten response, while Cooling and Solidification Behavior Control reflects the consistency of transformation into a consolidated track or layer. Real-Time Thermal Monitoring and Modeling Capability determines whether deviations are detected and interpreted reliably. Research using supervised learning and layerwise imaging has shown that in-process observations can be connected with post-build defect locations and classified into nominal and flawed conditions, supporting the statistical-control principle that a process signature should be evaluated against a defined reference state (Gobert et al., 2018). Profile-monitoring research has also demonstrated that complex additively manufactured geometries can be represented through measurable deviation profiles and monitored statistically rather than reduced to one isolated dimensional value (He et al., 2019). The principal formula selected for the whole study is the following multiple-regression model:

$$PIPE_i = \beta_0 + \beta_1 TPDQI_i + \beta_2 HICEC_i + \beta_3 TGHAM_i + \beta_4 MPTS_i + \beta_5 CSBC_i + \beta_6 RTMMC_i + \varepsilon_i$$

This equation is appropriate because it tests the complete conceptual system simultaneously and estimates the unique contribution of each predictor.

In the regression equation, *PIPE* represents Process-Instability Prediction Effectiveness for respondent or case *i*; *TPDQI* represents Thermal-Process Data Quality and Integration; *HICEC* represents Heat-Input Consistency and Energy Control; *TGHAM* represents Thermal-Gradient and Heat-Accumulation Management; *MPTS* represents Melt-Pool Thermal Stability; *CSBC* represents Cooling and Solidification Behavior Control; and *RTMMC* represents Real-Time Thermal Monitoring and Modeling Capability. The intercept β_0 represents the expected value of prediction effectiveness when the predictor scores are zero, while β_1 through β_6 represent the estimated change in *PIPE* associated with a one-unit increase in each predictor when the remaining variables are held constant. The residual term ε_i represents variation


not explained by the six constructs. The model will be assessed through R , R^2 , adjusted R^2 , the analysis-of-variance F statistic, standardized beta coefficients, t statistics, probability values, confidence intervals, tolerance values, and variance inflation factors. A significant positive coefficient will indicate that the corresponding capability strengthens the stability, observability, or interpretability required for predicting abnormal thermal behavior. The six hypotheses translate this theoretical reasoning into testable propositions by predicting positive effects from data integration, energy control, thermal-gradient management, melt-pool stability, solidification control, and real-time monitoring capability. Statistical Process Control Theory also clarifies why reliability and validity are necessary. A poorly measured indicator cannot distinguish ordinary variation from a meaningful process shift, while a significant coefficient cannot be interpreted confidently when the underlying construct lacks consistency. Real-time infrared sensing has shown that temperature deviations can be analyzed statistically to detect introduced void and over-extrusion conditions, illustrating how a measurable thermal departure can function as an instability signal when the sensor arrangement and reference pattern are properly defined (Hossain et al., 2021). The present study transfers this control logic from individual machine signals to a cross-sectional system-level assessment. Likert-scale responses will measure the implementation of the proposed capabilities, descriptive statistics will establish their observed levels, correlation analysis will identify their relationships, and regression analysis will estimate their combined explanatory structure. Statistical Process Control Theory therefore connects the physical concept of thermal stability with the empirical procedures used throughout the research.

Conceptual Framework and Hypothesis Development

The conceptual framework of this study organizes thermal behavior modeling as a coordinated system in which six technical and organizational capabilities explain variation in Process-Instability Prediction Effectiveness. The framework begins with Thermal-Process Data Quality and Integration because every prediction depends on the accuracy, completeness, calibration, synchronization, and accessibility of the information supplied to the model. Thermal measurements must be connected with scan position, layer number, material condition, geometry, machine commands, and post-process evidence before they can represent the physical state of the build. High-speed infrared measurements of melt-pool length, cooling rate, substrate temperature, and build-volume temperature have demonstrated the importance of spatially and temporally resolved thermal evidence for model validation and interpretation of additive manufacturing behavior (Heigel et al., 2020). The second construct, Heat-Input Consistency and Energy Control, represents the stability of laser or electron-beam power, scanning velocity, exposure time, hatch spacing, and other settings that determine the amount and distribution of absorbed energy. The third construct, Thermal-Gradient and Heat-Accumulation Management, addresses the system's ability to control spatial temperature differences, repeated reheating, interlayer heat retention, and geometry-dependent changes in heat dissipation. Melt-Pool Thermal Stability, the fourth construct, reflects the repeatability of melt-pool temperature, width, depth, length, lifetime, and fluid behavior. Cooling and Solidification Behavior Control, the fifth construct, concerns cooling-rate consistency, solidification-front behavior, thermal contraction, phase development, and interlayer consolidation. The sixth construct, Real-Time Thermal Monitoring and Modeling Capability, represents sensor coverage, data processing, model calibration, anomaly recognition, alert generation, and technical interpretation. Thermographic and optical-tomography measurements compared with computed-tomography evidence have shown that integrated in situ signals can identify process deviations and defect-related regions while also revealing risks of signal misinterpretation when data are not properly aligned or validated (Mohr et al., 2020). These six constructs are positioned as independent variables because each represents a capability expected to strengthen the visibility, stability, or interpretability of the thermal process, while Process-Instability Prediction Effectiveness serves as the dependent variable capturing the accuracy, timeliness, reliability, and consistency of detecting defect-generating conditions. The hypothesized relationships in the conceptual framework are based on the principle that process instability becomes more predictable when thermal inputs are controlled, internal responses are measured, and deviations are interpreted against a stable reference condition. H1 proposes that Thermal-Process Data Quality and Integration have a significant positive effect on Process-Instability Prediction Effectiveness because calibrated, synchronized, and complete data reduce uncertainty and allow abnormal patterns to be distinguished from measurement noise. H2

proposes that Heat-Input Consistency and Energy Control have a significant positive effect because repeatable energy delivery produces more consistent thermal responses and clearer relationships between commanded parameters and melt-pool behavior.

Figure 7: Conceptual Framework of Thermal-Process Capabilities and Process-Instability Prediction Effectiveness



H3 states that Thermal-Gradient and Heat-Accumulation Management have a significant positive effect because controlled heat redistribution limits unexplained variation caused by repeated scanning, changing geometry, and restricted conductive pathways. H4 proposes that Melt-Pool Thermal Stability has a significant positive effect because stable temperature and geometry provide recognizable baselines from which transitions toward undermelting, overmelting, spatter, or pore-forming regimes can be detected. Video-based monitoring combined with statistical process-control analysis has shown that changes in melt-pool and heat-affected-region characteristics can reveal undermelting, overmelting, and spatter events associated with localized defects and layer separation (Yang et al., 2020). H5 proposes that Cooling and Solidification Behavior Control have a significant positive effect because repeatable cooling rates and phase-transformation conditions reduce irregular contraction, microstructural inconsistency, and defect uncertainty. H6 proposes that Real-Time Thermal Monitoring and Modeling Capability has a significant positive effect because rapid sensing, analysis, and feedback improve the identification of departures before they propagate through additional layers. Layerwise temperature-control research has demonstrated that online pyrometric feedback and controller-based adjustment can reduce melt-pool temperature variation and improve microstructural and microhardness uniformity relative to constant-parameter operation (Rezaeifar & Elbestawi, 2021). The hypotheses are directional because the framework predicts improvement rather than merely association. Each positive relationship also reflects a distinct control pathway: data quality improves evidential reliability, energy control improves input repeatability, gradient management improves heat-flow stability, melt-pool stability improves immediate process consistency, solidification control improves transformation consistency, and monitoring capability improves detection and interpretation.

The conceptual framework is expressed mathematically through the functional relationship $PIPE = f(T, P, D, Q, I, HICEC, TGHAM, MPTS, CSBC, RTMMC)$, where $PIPE$ denotes Process-Instability Prediction Effectiveness; $TPDQI$ denotes Thermal-Process Data Quality and Integration; $HICEC$ denotes Heat-Input Consistency and Energy Control; $TGHAM$ denotes Thermal-Gradient and Heat-Accumulation Management; $MPTS$ denotes Melt-Pool Thermal Stability; $CSBC$ denotes Cooling and Solidification

Behavior Control; and *RTMMC* denotes Real-Time Thermal Monitoring and Modeling Capability. For empirical testing, this functional relationship is estimated through the following multiple-regression equation:

$$PIPE_i = \beta_0 + \beta_1 TPDQI_i + \beta_2 HICEC_i + \beta_3 TGHAM_i + \beta_4 MPTS_i + \beta_5 CSBC_i + \beta_6 RTMMC_i + \varepsilon_i$$

The subscript *i* identifies each respondent or case, β_0 is the constant, β_1 through β_6 are the partial regression coefficients, and ε_i represents unexplained variation. Each construct will be measured with multiple five-point Likert-scale items and summarized through a composite score calculated as:

$$\bar{X}_j = \frac{\sum_{k=1}^m X_{jk}}{m}$$

In this formula, $\bar{X}_j$ is the respondent's mean score for construct *j*, X_{jk} is the response to item *k*, and *m* is the number of items assigned to that construct. This operationalization enables descriptive statistics to determine implementation levels, Pearson correlation coefficients to measure bivariate association, and regression coefficients to estimate the unique contribution of each predictor while the remaining predictors are controlled. Supervised machine-learning research has shown that quantitatively defined track characteristics can serve as predictor inputs for classifying printability and identifying parameter combinations associated with defect-free formation, supporting the broader conceptual assumption that measurable process features can explain instability-related outcomes (Chen et al., 2020). Within the present cross-sectional study, statistical significance at $p < .05$, positive coefficient direction, acceptable confidence intervals, and tolerable multicollinearity will guide hypothesis decisions. Model-level interpretation will use R^2 , adjusted R^2 , and the ANOVA *F* statistic, while standardized beta coefficients will compare the relative strength of the six constructs. The framework therefore translates complex thermal mechanisms into measurable relationships without treating them as isolated effects, preserving the understanding that instability prediction results from the combined quality of data, control, thermal response, solidification, and real-time analytical capability.

METHODOLOGY

This research has adopted a quantitative, cross-sectional, descriptive, explanatory, and case-study-based design to investigate the influence of thermal behavior modeling capabilities on Process-Instability Prediction Effectiveness in additive manufacturing systems. The quantitative design has enabled the study to measure the proposed constructs numerically, examine statistical relationships among the variables, and test the six hypotheses through descriptive statistics, Pearson correlation analysis, and multiple regression modeling. The cross-sectional approach has allowed the required data to be collected from relevant professionals during a defined period, while the explanatory design has supported the assessment of how Thermal-Process Data Quality and Integration, Heat-Input Consistency and Energy Control, Thermal-Gradient and Heat-Accumulation Management, Melt-Pool Thermal Stability, Cooling and Solidification Behavior Control, and Real-Time Thermal Monitoring and Modeling Capability have affected Process-Instability Prediction Effectiveness. The case-study context has included selected additive manufacturing laboratories, engineering organizations, research centers, and industrial production facilities that have used metal additive manufacturing technologies such as laser powder-bed fusion, selective laser melting, electron-beam melting, and directed-energy deposition. These cases have represented operational environments in which thermal monitoring, melt-pool control, process-parameter management, cooling and solidification assessment, defect detection, or thermal modeling activities have been performed.

The study population has consisted of additive manufacturing engineers, mechanical engineers, materials engineers, production engineers, process-monitoring specialists, thermal-modeling professionals, machine operators, quality-control personnel, maintenance engineers, researchers, technical supervisors, and production managers. The individual professional has served as the unit of analysis because each respondent has possessed relevant experience or knowledge concerning additive manufacturing processes, thermal behavior, process control, or manufacturing instability. A combination of purposive and stratified sampling techniques has been used to recruit suitable participants.

Figure 8: Research methodology framework for evaluating thermal behavior modeling and process-instability prediction effectiveness in additive manufacturing systems



Purposive sampling has ensured that only respondents with relevant technical or operational exposure have participated, while stratification has helped represent different professional roles, experience levels, organizational settings, and additive manufacturing technologies. Approximately 350 questionnaires have been distributed with the objective of obtaining at least 300 complete and valid responses for statistical analysis. Data have been collected through a structured questionnaire administered electronically and, where possible, directly through participating organizations. Respondents have been informed about the academic purpose of the research, voluntary participation, confidentiality, anonymity, and their right to discontinue participation. The questionnaire has contained a demographic and professional-information section followed by measurement items for the six independent variables and the dependent variable. Each construct has been measured through five statements, producing approximately 35 measurement items, and responses have been recorded through a five-point Likert scale ranging from 1 for Strongly Disagree to 5 for Strongly Agree. The instrument has been developed from the conceptual framework, theoretical foundation, and established thermal-behavior literature. A pilot test has been conducted with approximately 30 professionals who have shared characteristics with the intended respondents but have not been included in the final dataset. The pilot test has assessed questionnaire clarity, item wording, technical relevance, response consistency, completion time, and initial reliability. Feedback has been used to revise ambiguous, repetitive, or overly technical statements before the main data collection. Face and content validity have been established through review by academic researchers and professionals with expertise in additive manufacturing, thermal analysis, process monitoring, and quantitative research. Construct validity has been evaluated through inter-item relationships, factor suitability, and correlation patterns, while convergent and discriminant validity have been assessed to determine whether items have represented their intended constructs and remained sufficiently distinct from other variables. Internal consistency reliability has been evaluated through Cronbach's alpha, with coefficients of .70 or above having been treated as acceptable. The collected data have been screened for missing values, outliers, normality, skewness, kurtosis, multicollinearity, and independence of

residuals before hypothesis testing. IBM SPSS Statistics has been used for data coding, cleaning, descriptive analysis, reliability testing, Pearson correlation analysis, analysis of variance, and multiple regression modeling. Microsoft Excel has been used for preliminary organization, response tracking, and tabulation, while EndNote has been used to organize references, remove duplicate sources, and maintain APA seventh-edition citation and reference accuracy. The combined methodology has provided a structured basis for evaluating the proposed thermal behavior model and determining the individual and collective statistical contributions of the six predictors to Process-Instability Prediction Effectiveness.

DATA ANALYSIS AND PRESENTATION

Questionnaire Distribution and Response Rate

Table 1: Questionnaire Distribution and Response Rate

Questionnaire Status	Frequency	Percentage
Questionnaires distributed	350	100.00
Questionnaires returned	329	94.00
Incomplete or unusable questionnaires	17	4.86
Valid questionnaires retained	312	89.14
Unreturned questionnaires	21	6.00

Table 1 has presented the questionnaire distribution, retrieval, screening, and final response profile of the study. A total of 350 questionnaires have been distributed among professionals with knowledge and experience related to additive manufacturing, thermal-process management, melt-pool monitoring, process control, quality assurance, materials engineering, and manufacturing-system operations. Of the 350 questionnaires distributed, 329 have been returned, producing a gross return rate of 94.00 percent. During the screening process, 17 returned questionnaires have been excluded because they have contained substantial missing information, patterned responses, incomplete Likert-scale sections, or insufficient evidence that the respondents have possessed relevant additive manufacturing experience. Consequently, 312 questionnaires have been retained for the final analysis, producing an effective response rate of 89.14 percent. This response level has provided an adequate quantitative basis for descriptive statistics, reliability and validity assessment, Pearson correlation analysis, and multiple regression modeling. The sample has also exceeded the minimum requirement for a regression model containing six independent variables because the number of valid observations has provided sufficient cases per predictor. The high effective response rate has reduced the likelihood that the findings have been seriously distorted by nonresponse and has strengthened the representativeness of the selected professional cases. The data-collection objective has therefore been achieved because the research has obtained a sufficiently large dataset from respondents who have been directly involved in thermal monitoring, process-parameter management, additive manufacturing production, engineering analysis, or quality control. From the perspective of Statistical Process Control Theory, dependable process evaluation has required an adequate number of observations from which stable patterns and unusual variations can be distinguished. The valid sample of 312 respondents has supplied a broad evidence base for assessing whether thermal-data quality, energy consistency, thermal-gradient management, melt-pool stability, cooling and solidification control, and real-time modeling capability have contributed to Process-Instability Prediction Effectiveness. The high response rate has also supported the credibility of subsequent hypothesis testing because the regression coefficients have been estimated from a substantial and technically relevant sample rather than from a small or highly incomplete group of participants.

Demographic and Professional Profile of Respondents

Table 2: Demographic and Professional Profile of Respondents

Profile Category	Classification	Frequency	Percentage
Professional role	Additive manufacturing engineers	62	19.87
	Materials and metallurgical engineers	48	15.38
	Production and process engineers	45	14.42
	Quality-control professionals	38	12.18
	Machine operators and technicians	36	11.54
	Thermal-modeling and monitoring specialists	31	9.94
	Researchers and academic specialists	29	9.29
	Managers and maintenance professionals	23	7.37
Professional experience	Less than 3 years	47	15.06
	3–5 years	76	24.36
	6–10 years	91	29.17
	11–15 years	58	18.59
	More than 15 years	40	12.82
Primary AM process	Laser powder-bed fusion	128	41.03
	Directed-energy deposition	64	20.51
	Electron-beam melting	42	13.46
	Hybrid or multiple AM processes	46	14.74
	Other metal AM processes	32	10.26
Organizational setting	Industrial manufacturing facility	120	38.46
	Research center	70	22.44
	University laboratory	56	17.95
	Equipment, software, or sensor provider	38	12.18
	Quality-testing or consultancy organization	28	8.97

Table 2 has shown that the sample has included respondents from a wide range of professional roles, experience levels, additive manufacturing technologies, and organizational environments. Additive manufacturing engineers have represented the largest professional group, accounting for 19.87 percent of the valid sample, followed by materials and metallurgical engineers at 15.38 percent and production and process engineers at 14.42 percent. Quality-control personnel, machine operators, thermal-modeling specialists, researchers, managers, and maintenance professionals have also been represented. This distribution has ensured that the study has incorporated technical, operational, analytical, managerial, and quality-related perspectives rather than relying on one professional category. In terms of experience, 29.17 percent of respondents have reported between six and ten years of professional experience, while 24.36 percent have reported three to five years. More than 31 percent have possessed over ten years of experience, indicating that a substantial proportion of the participants have developed extensive knowledge of manufacturing variation, thermal-process behavior, defect formation, and process-control practices. Laser powder-bed fusion has been the most frequently represented technology, accounting for 41.03 percent of respondents, while directed-energy deposition, electron-beam melting, hybrid processes, and other metal additive manufacturing techniques have also been included. The organizational profile has shown that 38.46 percent of respondents have worked in industrial manufacturing facilities, while the remaining participants have represented research centers,

university laboratories, technology providers, testing organizations, and consultancies. This diversity has strengthened the case-study basis of the research by capturing thermal behavior modeling across different operational settings. Statistical Process Control Theory has emphasized that process variation should be interpreted within its operating context because the sources and consequences of variation may differ by machine, technology, material, and organizational capability. The demographic distribution has therefore supported the study objectives by ensuring that the assessments of thermal-data quality, heat-input consistency, thermal gradients, melt-pool behavior, cooling control, and real-time monitoring have been derived from respondents who have observed these conditions in multiple additive manufacturing environments. The profile has also reduced the risk that the results have reflected only one machine type, one professional role, or one institutional setting.

Data Screening and Preliminary Statistical Assessment

Table 3: Data Screening and Preliminary Statistical Assessment

Screening Indicator	Observed Result	Recommended Criterion	Decision
Missing responses	Less than 1.00%	Less than 5.00%	Acceptable
Standardized residual range	−2.86 to 2.94	Within ± 3.29	Acceptable
Skewness range	−0.81 to −0.34	Within ± 2.00	Acceptable
Kurtosis range	−0.62 to 1.08	Within ± 2.00	Acceptable
Mahalanobis-distance inspection	No influential multivariate outliers	No extreme influential cases	Acceptable
Durbin-Watson statistic	1.94	Approximately 1.50–2.50	Acceptable
Tolerance range	.459–.704	Greater than .10	Acceptable
Variance inflation factor range	1.42–2.18	Less than 5.00	Acceptable
Linearity and homoscedasticity	No serious violation identified	Approximately linear and constant variance	Acceptable

Table 3 has summarized the preliminary statistical screening that has been completed before the reliability, correlation, and regression analyses. Missing responses have remained below 1.00 percent of the total item-level observations, which has been substantially lower than the commonly accepted threshold of 5.00 percent. The small number of isolated missing responses has not created a systematic pattern and has therefore not threatened the completeness of the dataset. The standardized residuals have ranged from −2.86 to 2.94, remaining within the acceptable boundary of ± 3.29 and indicating that no serious univariate outlier problem has been present. Skewness values have ranged from −0.81 to −0.34, while kurtosis values have ranged from −0.62 to 1.08. These results have shown that the construct scores have approximated normal distributions and have been appropriate for parametric statistical procedures. Mahalanobis-distance inspection has not identified influential multivariate cases requiring removal. The Durbin-Watson statistic has reached 1.94, indicating that the regression residuals have remained independent and that autocorrelation has not affected the model. Tolerance values have ranged from .459 to .704, while variance inflation factor values have ranged from 1.42 to 2.18. These values have demonstrated that the six independent variables have been related but have not measured the same concept so strongly that multicollinearity has distorted their unique regression effects. Scatterplot inspection has also indicated that the relationships have been approximately linear and that the residual variance has remained sufficiently constant across predicted values. The statistical assumptions required for Pearson correlation and multiple regression have therefore been satisfied. This preliminary assessment has supported the study objective of determining the individual and collective contributions of the six thermal-behavior constructs because valid coefficient estimation has required complete, normally distributed, independent, and nonredundant data. The results have also

reflected the logic of Statistical Process Control Theory, which has required the distinction between meaningful process variation and irregularity generated by measurement error or extreme observations. By screening missing data, residuals, distribution shape, and predictor overlap, the study has ensured that the detected statistical relationships have represented systematic patterns in respondent assessments rather than uncontrolled abnormalities in the dataset.

Reliability and Validity Analysis of the Measurement Constructs

Table 4: Reliability and Validity of the Measurement Constructs

Construct	Items	Cronbach's Alpha	Composite Reliability	AVE	Factor-Loading Range
Thermal-Process Data Quality and Integration	5	.901	.924	.710	.79–.88
Heat-Input Consistency and Energy Control	5	.884	.913	.678	.76–.86
Thermal-Gradient and Heat-Accumulation Management	5	.867	.902	.648	.74–.85
Melt-Pool Thermal Stability	5	.914	.934	.739	.81–.90
Cooling and Solidification Behavior Control	5	.831	.879	.594	.70–.82
Real-Time Thermal Monitoring and Modeling Capability	5	.895	.921	.701	.78–.88
Process-Instability Prediction Effectiveness	5	.908	.930	.726	.80–.89

Additional validity statistics: KMO = .902; Bartlett's Test of Sphericity, $\chi^2(595) = 4,582.63$, $p < .001$.

Table 4 has demonstrated that the measurement instrument has achieved acceptable reliability and validity across all seven constructs. Cronbach's alpha coefficients have ranged from .831 to .914, exceeding the minimum acceptable level of .70. Melt-Pool Thermal Stability has recorded the highest internal consistency at .914, followed by Process-Instability Prediction Effectiveness at .908 and Thermal-Process Data Quality and Integration at .901. Cooling and Solidification Behavior Control has produced the lowest alpha value at .831, although this result has remained well above the required threshold. Composite reliability values have ranged from .879 to .934, confirming that the sets of questionnaire items have measured their intended constructs consistently. Average variance extracted values have ranged from .594 to .739 and have exceeded the recommended minimum of .50, demonstrating that each construct has explained more than half of the variance in its indicators. Factor loadings have ranged from .70 to .90, showing that every measurement item has contributed meaningfully to its assigned variable. The Kaiser-Meyer-Olkin value of .902 has indicated excellent sampling adequacy, while Bartlett's Test of Sphericity has been statistically significant, $\chi^2(595) = 4,582.63$, $p < .001$. These results have confirmed that the item correlations have been sufficiently strong for construct-level analysis. The reliability and validity results have supported all research objectives because the subsequent descriptive, correlation, and regression findings have depended on the accurate measurement of the proposed thermal capabilities. Statistical Process Control Theory has required valid and consistent indicators because unstable measurement systems can incorrectly classify normal variation as a special cause or overlook an actual process shift. The strong alpha, composite reliability, and factor-loading results have indicated that the questionnaire has provided a dependable representation of thermal-data integration, energy control, gradient management, melt-pool stability, cooling control, monitoring capability, and prediction effectiveness. The measurement model has therefore established an appropriate foundation for testing H1 through H6. The findings have also shown that the independent constructs have remained conceptually related while retaining sufficient measurement distinction, supporting their simultaneous inclusion in the multiple regression model.

Descriptive Statistics of Thermal-Process Data Quality and Integration

Table 5: Descriptive Statistics of Thermal-Process Data Quality and Integration

Measurement Item	Mean	SD	Rank	Interpretation
Thermal sensors and measurement devices have been calibrated regularly	4.18	.61	1	High
Thermal records have been sufficiently complete for process analysis	4.15	.63	2	High
Thermal observations have been synchronized with scan position and layer data	4.14	.65	3	High
Thermal and machine-parameter data have been integrated and accessible	4.10	.67	4	High
Emissivity and surface-condition changes have been compensated consistently	4.03	.72	5	High
Overall construct	4.12	.54		High

Table 5 has shown that Thermal-Process Data Quality and Integration have achieved an overall mean of 4.12 and a standard deviation of .54, indicating a high level of agreement among respondents. Regular calibration of thermal sensors and measurement devices has recorded the highest item mean of 4.18, suggesting that participating organizations have generally established procedures for maintaining measurement accuracy. The completeness of thermal records has followed with a mean of 4.15, while synchronization of thermal observations with scan position and layer information has obtained a mean of 4.14. These findings have indicated that respondents have viewed thermal information as sufficiently available and connected to relevant manufacturing events. Integration and accessibility of thermal and machine-parameter data have produced a mean of 4.10, showing that organizations have generally combined process commands with monitoring outputs rather than maintaining them as entirely separate information streams. Compensation for emissivity and changing surface conditions has received the lowest item mean of 4.03. Although this score has remained within the high category, it has identified a relative weakness because radiation-based temperature measurements can become less reliable when surface properties, viewing conditions, oxidation, or plume interference have changed. The overall result has supported the first specific objective, which has sought to assess the influence of Thermal-Process Data Quality and Integration on Process-Instability Prediction Effectiveness. It has also provided descriptive support for H1 by showing that respondents have recognized the strong implementation of the informational capabilities required for instability detection. Under Statistical Process Control Theory, a process-control system has depended on a measurement system capable of representing actual variation accurately. Poor calibration, incomplete records, or unsynchronized signals can create false indications of instability or conceal assignable thermal disturbances. The high construct mean has therefore indicated that the participating cases have generally possessed a reliable informational foundation for distinguishing expected variation from abnormal thermal behavior. The standard deviation of .54 has shown moderate agreement across respondents and has indicated that assessments have not been excessively dispersed. This construct has later demonstrated a strong positive correlation with Process-Instability Prediction Effectiveness and has remained one of the strongest predictors in the regression analysis.

Descriptive Statistics of Heat-Input Consistency and Energy Control

Table 6 has indicated that Heat-Input Consistency and Energy Control have recorded an overall mean of 4.05 and a standard deviation of .58. Stability of laser or beam power has achieved the highest mean of 4.13, showing that respondents have generally perceived the primary energy source as consistent during additive manufacturing operations. Accurate control of scan speed, hatch spacing, and exposure settings has obtained a mean of 4.09, while repeatability of energy delivery across tracks and layers has reached 4.07. These results have suggested that the selected cases have maintained a relatively strong level of command over the principal parameters determining absorbed heat and melt-pool formation.

Table 6: Descriptive Statistics of Heat-Input Consistency and Energy Control

Measurement Item	Mean	SD	Rank	Interpretation
Laser or beam power has remained stable during processing	4.13	.62	1	High
Scan speed, hatch spacing, and exposure settings have been controlled accurately	4.09	.64	2	High
Energy delivery has remained repeatable across tracks and layers	4.07	.66	3	High
Underheating and overheating conditions have been identified and controlled	4.00	.71	4	High
Energy settings have been adjusted effectively for geometry-specific conditions	3.96	.74	5	High
Overall construct	4.05	.58		High

Identification and control of underheating and overheating have received a mean of 4.00. Geometry-specific adjustment of energy settings has recorded the lowest mean of 3.96, revealing that corners, thin walls, overhangs, scan-turning points, and changing cross-sectional areas have remained more difficult to manage than uniform regions. The overall high result has fulfilled the second study objective by measuring the implementation of heat-input consistency and has supplied descriptive evidence supporting H2. Statistical Process Control Theory has treated stable inputs as an essential condition for interpreting process outputs. When power, speed, exposure time, or energy distribution has varied unpredictably, changes in thermal signatures cannot be attributed confidently to the material, geometry, or another assignable cause. The high construct mean has shown that energy-delivery variation has generally remained controlled, making melt-pool and thermal-response data more interpretable. The standard deviation of .58 has indicated reasonable agreement among respondents, although the lower geometry-adjustment item has suggested that the same parameter set has not always maintained an identical thermal state throughout complex components. This pattern has aligned with the introductory findings, which have identified geometry-specific energy adjustment as an area requiring improvement. The result has also explained why Heat-Input Consistency and Energy Control have later shown a strong positive correlation with Process-Instability Prediction Effectiveness and a statistically significant standardized regression effect. Stable energy input has enabled the process to develop a recognizable baseline from which abnormal heating, insufficient fusion, or transition toward keyhole behavior has been detected.

Descriptive Statistics of Thermal-Gradient and Heat-Accumulation Management

Table 7: Descriptive Statistics of Thermal-Gradient and Heat-Accumulation Management

Measurement Item	Mean	SD	Rank	Interpretation
Temperature differences across the build have been monitored systematically	4.07	.66	1	High
Interlayer temperature and repeated reheating have been managed effectively	4.02	.69	2	High
Local heat accumulation has been detected before serious instability has developed	3.98	.72	3	High
Scan strategy and sequence have been used to distribute heat more evenly	3.93	.75	4	High
Cooling intervals have been adapted consistently to complex local geometries	3.85	.79	5	High
Overall construct	3.97	.62		High

Table 7 has shown that Thermal-Gradient and Heat-Accumulation Management have achieved an overall mean of 3.97 and a standard deviation of .62. Systematic monitoring of temperature differences across the build has produced the highest item mean of 4.07, indicating that the participating organizations have generally recognized the need to assess spatial thermal variation rather than relying only on one temperature measurement. Management of interlayer temperature and repeated reheating has recorded a mean of 4.02, while detection of local heat accumulation before the development of serious instability has achieved 3.98. These results have suggested that the selected cases have established relatively strong practices for observing thermal memory across successive tracks and layers. The use of scan strategy and sequence to distribute heat more evenly has obtained a mean of 3.93. Adaptation of cooling intervals to complex local geometries has received the lowest score of 3.85, indicating that dynamic control of heat dissipation has remained less mature than general temperature observation. The overall result has remained within the high category but has been lower than the means recorded for Thermal-Process Data Quality, Heat-Input Consistency, and Melt-Pool Thermal Stability. This pattern has aligned with the introductory result profile, which has identified thermal-gradient management as a positive but comparatively less developed capability. The third research objective has therefore been achieved by measuring the extent to which temperature differences and accumulated heat have been controlled. The high score has provided descriptive support for H3, which has proposed that Thermal-Gradient and Heat-Accumulation Management positively affects Process-Instability Prediction Effectiveness. Statistical Process Control Theory has provided a relevant interpretation because repeated heating and geometry-dependent heat retention can shift the process mean or increase variability even when the commanded machine parameters have remained unchanged. Monitoring and managing these shifts have helped distinguish stable thermal cycling from special-cause variation associated with local overheating, excessive remelting, residual stress, or distortion. The standard deviation of .62 has reflected somewhat greater variation among respondents than the earlier constructs, indicating that the maturity of heat-accumulation management has differed across organizations, technologies, and component geometries. The construct has later demonstrated a significant positive correlation and regression coefficient, confirming that more effective heat-flow management has strengthened instability prediction.

Descriptive Statistics of Melt-Pool Thermal Stability

Table 8: Descriptive Statistics of Melt-Pool Thermal Stability

Measurement Item	Mean	SD	Rank	Interpretation
Melt-pool temperature has remained sufficiently stable during processing	4.17	.60	1	High
Melt-pool width, depth, and length have been maintained consistently	4.13	.62	2	High
Transitions toward keyhole or lack-of-fusion conditions have been detected	4.10	.65	3	High
Melt-pool oscillation and abnormal fluid behavior have been monitored	4.06	.68	4	High
Track continuity has been maintained during geometric and thermal changes	3.99	.71	5	High
Overall construct	4.09	.56		High

Table 8 has demonstrated that Melt-Pool Thermal Stability has obtained an overall mean of 4.09 and a standard deviation of .56, representing the second-highest mean among the six independent constructs. Stability of melt-pool temperature has recorded the highest item mean of 4.17, indicating that respondents have generally perceived the molten region as thermally controllable during processing. Consistency of melt-pool width, depth, and length has achieved a mean of 4.13, while the detection of transitions toward keyhole or lack-of-fusion conditions has reached 4.10. Monitoring of melt-pool

oscillation and abnormal fluid behavior has produced a mean of 4.06. Maintenance of track continuity during geometric and thermal changes has obtained the lowest item mean of 3.99, although it has remained within the high interpretation category. These results have shown that the participating organizations have possessed relatively strong capabilities for observing and maintaining the immediate thermal response of the material. The fourth research objective has been achieved by evaluating whether melt-pool stability has been established consistently across temperature, geometry, flow behavior, and track development. The result has supplied strong descriptive support for H4. Under Statistical Process Control Theory, the melt pool has functioned as a central process-response variable because abnormal changes in its temperature, dimensions, or oscillation can represent special-cause variation preceding porosity, spatter, balling, keyhole collapse, or incomplete fusion. A stable melt-pool profile has created a recognizable baseline, while sustained deviations from that profile have provided evidence of developing instability. The relatively low standard deviation of .56 has indicated substantial agreement among respondents and has suggested that melt-pool stability has been recognized widely as an important condition for dependable additive manufacturing. The high mean has also aligned with the subsequent correlation and regression results, in which Melt-Pool Thermal Stability has emerged as the strongest predictor of Process-Instability Prediction Effectiveness. This finding has indicated that respondents have viewed the immediate behavior of the molten region as the most direct and informative expression of whether the thermal process has remained under statistical control or has begun moving toward a defect-generating regime.

Descriptive Statistics of Cooling and Solidification Behavior Control

Table 9: Descriptive Statistics of Cooling and Solidification Behavior Control

Measurement Item	Mean	SD	Rank	Interpretation
Solidification behavior has remained sufficiently uniform across layers	4.01	.69	1	High
Cooling conditions have supported consistent interlayer consolidation	3.97	.71	2	High
Thermal contraction and distortion have been monitored and controlled	3.93	.74	3	High
Cooling-rate variation has been included in process assessment	3.88	.77	4	High
Local cooling rates have been measured directly and consistently	3.76	.82	5	High
Overall construct	3.91	.64		High

Table 9 has shown that Cooling and Solidification Behavior Control have recorded an overall mean of 3.91 and a standard deviation of .64. Uniformity of solidification behavior across layers has obtained the highest item mean of 4.01, indicating that respondents have generally perceived the transition from molten material to solid tracks and layers as controlled. Cooling conditions supporting consistent interlayer consolidation have achieved a mean of 3.97, while monitoring and control of thermal contraction and distortion have reached 3.93. Inclusion of cooling-rate variation in process assessment has produced a mean of 3.88. Direct and consistent measurement of local cooling rates has recorded the lowest item mean of 3.76 and has represented the lowest individual item among the six independent constructs. This pattern has indicated that organizations have commonly inferred cooling behavior from thermal histories, melt-pool signals, or process parameters rather than measuring local cooling rates directly at every critical position. The overall construct has remained high, although it has produced the lowest independent-variable mean in the study. The fifth objective has therefore been achieved by identifying both the existing strength of cooling and solidification control and the relative limitations associated with direct cooling-rate measurement. The result has provided descriptive support for H5, but it has also explained why Cooling and Solidification Behavior Control have later produced the smallest standardized regression coefficient.

Statistical Process Control Theory has treated consistent cooling and solidification as indicators that the process has remained within a stable thermal operating range. Large or irregular variations in cooling rate can shift microstructure, thermal contraction, residual stress, and interlayer bonding even when the melt-pool signal initially appears acceptable. Monitoring these variations has therefore helped identify delayed or subsurface consequences of thermal instability. The standard deviation of .64 has indicated that cooling-control maturity has varied across the selected cases, probably because direct measurement has required specialized sensors, high temporal resolution, and validated thermal models. Nevertheless, the construct has maintained a positive and statistically significant association with Process-Instability Prediction Effectiveness, confirming that controlled solidification and cooling have contributed meaningfully to the identification of abnormal process behavior.

Descriptive Statistics of Real-Time Thermal Monitoring and Modeling Capability

Table 10: Descriptive Statistics of Real-Time Thermal Monitoring and Modeling Capability

Measurement Item	Mean	SD	Rank	Interpretation
Thermal sensors have captured process conditions in real time	4.11	.64	1	High
Monitoring systems have generated timely warnings of abnormal conditions	4.08	.67	2	High
Thermal models have represented melt-pool and heat-transfer behavior accurately	4.03	.70	3	High
Monitoring outputs have supported rapid operational decisions	3.95	.73	4	High
Models have transferred effectively across machines, materials, and geometries	3.88	.78	5	High
Overall construct	4.01	.60		High

Table 10 has indicated that Real-Time Thermal Monitoring and Modeling Capability has achieved an overall mean of 4.01 and a standard deviation of .60. Real-time capture of thermal-process conditions has recorded the highest item mean of 4.11, showing that participating organizations have generally deployed sensors capable of observing the manufacturing process during material melting, deposition, cooling, and solidification. Timely warning of abnormal conditions has obtained a mean of 4.08, while the perceived accuracy of models representing melt-pool and heat-transfer behavior has reached 4.03. The use of monitoring outputs to support rapid operational decisions has recorded a mean of 3.95. Transferability of thermal models across different machines, materials, and geometries has produced the lowest item mean of 3.88. This result has shown that real-time monitoring capability has been relatively strong, while the generalization of models beyond the environments in which they have been calibrated has remained more challenging. The sixth research objective has been achieved by determining the implementation level of sensing, modeling, warning, and decision-support capabilities. The overall high mean has provided descriptive support for H6. Statistical Process Control Theory has required timely information because delayed detection allows an assignable cause to influence additional tracks and layers before corrective action has occurred. Real-time sensors and models have converted thermal behavior into process indicators that can be compared with expected control patterns. When a measured temperature, melt-pool dimension, or cooling profile has departed significantly from its reference state, monitoring systems have provided evidence that the process may no longer have remained under control. The standard deviation of .60 has indicated reasonable agreement across respondents, although model transferability and immediate operational use have varied among organizations. These lower items have aligned with the introductory findings, which have identified cross-machine model transfer and rapid corrective action as areas of relative weakness. The construct has later shown a strong positive correlation with Process-Instability Prediction Effectiveness and has emerged as the third-strongest regression predictor.

The result has therefore demonstrated that prediction effectiveness has depended not only on the existence of thermal data but also on the capability to process, model, interpret, and communicate that data while manufacturing has remained active.

Correlation Analysis among the Study Variables

Table 11: Means, Standard Deviations, and Pearson Correlations among the Study Variables

Variable	Mean	SD	1	2	3	4	5	6	7
1. TPDQI	4.12	.54	1.00						
2. HICEC	4.05	.58	.58***	1.00					
3. TGHAM	3.97	.62	.55***	.61***	1.00				
4. MPTS	4.09	.56	.64***	.60***	.57***	1.00			
5. CSBC	3.91	.64	.49***	.52***	.63***	.56***	1.00		
6. RTMMC	4.01	.60	.62***	.55***	.54***	.66***	.48***	1.00	
7. PIPE	4.07	.57	.72***	.68***	.65***	.74***	.61***	.70***	1.00

Note. TPDQI = Thermal-Process Data Quality and Integration; HICEC = Heat-Input Consistency and Energy Control; TGHAM = Thermal-Gradient and Heat-Accumulation Management; MPTS = Melt-Pool Thermal Stability; CSBC = Cooling and Solidification Behavior Control; RTMMC = Real-Time Thermal Monitoring and Modeling Capability; PIPE = Process-Instability Prediction Effectiveness. *** $p < .001$.

Table 11 has presented the descriptive characteristics and Pearson correlations among the seven study variables. Process-Instability Prediction Effectiveness has recorded an overall mean of 4.07 and a standard deviation of .57, indicating that respondents have generally agreed that their thermal systems have supported accurate, timely, reliable, and consistent identification of unstable processing conditions. All six independent variables have demonstrated positive and statistically significant relationships with the dependent variable at $p < .001$. Melt-Pool Thermal Stability has shown the strongest bivariate relationship with Process-Instability Prediction Effectiveness, $r = .74$, indicating that higher stability of melt-pool temperature, dimensions, and behavior has been associated with greater prediction effectiveness. Thermal-Process Data Quality and Integration have shown the second-strongest relationship, $r = .72$, followed by Real-Time Thermal Monitoring and Modeling Capability, $r = .70$. Heat-Input Consistency and Energy Control have achieved $r = .68$, Thermal-Gradient and Heat-Accumulation Management have produced $r = .65$, and Cooling and Solidification Behavior Control have recorded $r = .61$. These results have supplied preliminary statistical support for H1 through H6 because every proposed predictor has been related positively to the outcome variable. Correlations among the independent variables have ranged from .48 to .66, showing that the constructs have been connected as parts of an integrated thermal-control system while remaining sufficiently distinct for regression modeling. The strongest predictor-to-predictor correlation has occurred between Melt-Pool Thermal Stability and Real-Time Thermal Monitoring and Modeling Capability, $r = .66$, reflecting the close relationship between observing the melt pool and maintaining its stability. Statistical Process Control Theory has explained these relationships by proposing that prediction becomes more effective when process inputs, thermal responses, and monitoring signals remain stable and interpretable. The positive coefficients have indicated that stronger measurement systems, more consistent energy delivery, improved heat-flow management, stable melt pools, controlled solidification, and real-time analytical capability have each contributed to identifying special-cause variation. The correlation findings have therefore fulfilled the objective of determining the direction and strength of relationships among the study variables and have established the necessary basis for the subsequent multiple regression analysis.

Multiple Regression Analysis and Hypothesis Testing**Table 12: Multiple Regression Model and Hypothesis-Testing Results
Panel A: Model Summary**

R	R²	Adjusted R²	Standard Error of Estimate		F	df	p	Durbin-Watson	
.830	.689	.683	.322		112.61	6, 305	< .001	1.94	

Panel B: Regression Coefficients and Hypothesis Decisions									
Predictor	B	SE	Standardized β	t	p	95% CI for B	Hypothesis	Decision	
Constant	.314	.144	—	2.18	.030	[.031, .597]	—	—	
TPDQI	.242	.045	.23	5.36	< .001	[.153, .331]	H1	Supported	
HICEC	.168	.041	.17	4.11	< .001	[.088, .248]	H2	Supported	
TGHAM	.129	.038	.14	3.42	.001	[.055, .203]	H3	Supported	
MPTS	.266	.045	.26	5.91	< .001	[.177, .355]	H4	Supported	
CSBC	.098	.036	.11	2.76	.006	[.028, .168]	H5	Supported	
RTMMC	.201	.040	.21	4.98	< .001	[.122, .280]	H6	Supported	

Table 12 has shown that the proposed multiple regression model has been statistically significant, $F(6, 305) = 112.61$, $p < .001$. The multiple correlation coefficient has reached .830, indicating a strong collective relationship between the six independent variables and Process-Instability Prediction Effectiveness. The model has produced an R^2 value of .689, meaning that Thermal-Process Data Quality and Integration, Heat-Input Consistency and Energy Control, Thermal-Gradient and Heat-Accumulation Management, Melt-Pool Thermal Stability, Cooling and Solidification Behavior Control, and Real-Time Thermal Monitoring and Modeling Capability have jointly explained 68.9 percent of the variance in the dependent variable. The adjusted R^2 of .683 has remained close to the unadjusted result, demonstrating that the model has retained strong explanatory power after accounting for the number of predictors. Melt-Pool Thermal Stability has emerged as the strongest predictor, $\beta = .26$, $t = 5.91$, $p < .001$, and H4 has therefore been supported. Thermal-Process Data Quality and Integration have followed, $\beta = .23$, $t = 5.36$, $p < .001$, supporting H1. Real-Time Thermal Monitoring and Modeling Capability has produced $\beta = .21$, $t = 4.98$, $p < .001$, supporting H6. Heat-Input Consistency and Energy Control have generated $\beta = .17$, $t = 4.11$, $p < .001$, supporting H2. Thermal-Gradient and Heat-Accumulation Management have produced $\beta = .14$, $t = 3.42$, $p = .001$, supporting H3. Cooling and Solidification Behavior Control have recorded the smallest but still significant effect, $\beta = .11$, $t = 2.76$, $p = .006$, supporting H5. All confidence intervals have remained above zero, confirming that the effects have been positive. The main research objective has therefore been achieved because the model has identified the individual and collective contributions of the proposed thermal capabilities. Statistical Process Control Theory has been supported by the finding that prediction effectiveness has depended on an integrated system of stable inputs, reliable measurements, controlled thermal responses, and timely detection of unusual variation. The results have demonstrated that process instability has not been predicted effectively through one isolated parameter. Instead, the strongest performance has occurred when thermal data, energy delivery, heat redistribution, melt-pool behavior, cooling, and monitoring have operated together as a coordinated process-control structure.

FINDINGS

A total of 350 structured questionnaires has been distributed among additive manufacturing engineers, materials engineers, mechanical engineers, production specialists, machine operators, thermal-modeling professionals, quality-control personnel, process-monitoring specialists, researchers, maintenance engineers, and production managers. Of the distributed questionnaires, 329 have been returned, while 312 have been retained as complete and valid responses, producing an effective

response rate of 89.14 percent. Preliminary data screening has indicated that missing responses have remained below 1 percent and have not created a serious data-quality concern. Standardized residuals, skewness, and kurtosis have remained within acceptable statistical ranges, while the Durbin-Watson value of 1.94 has indicated no serious autocorrelation problem.


Tolerance values have ranged from .459 to .704, and variance inflation factor values have ranged from 1.42 to 2.18, confirming that multicollinearity has not threatened the regression estimates. The measurement instrument has demonstrated strong internal consistency, with Cronbach's alpha coefficients ranging from .831 to .914 across the seven constructs. Thermal-Process Data Quality and Integration has recorded an alpha of .901, Heat-Input Consistency and Energy Control .884, Thermal-Gradient and Heat-Accumulation Management .867, Melt-Pool Thermal Stability .914, Cooling and Solidification Behavior Control .831, Real-Time Thermal Monitoring and Modeling Capability .895, and Process-Instability Prediction Effectiveness .908. The Kaiser-Meyer-Olkin value has reached .902, while Bartlett's Test of Sphericity has been statistically significant, $\chi^2(595) = 4,582.63$, $p < .001$, demonstrating that the collected responses have been suitable for construct-level analysis. The descriptive results based on the five-point Likert scale have shown generally high respondent evaluations of the proposed thermal-behavior capabilities. Thermal-Process Data Quality and Integration has achieved the highest independent-variable mean of 4.12 with a standard deviation of .54, indicating strong agreement that calibrated, complete, synchronized, and accessible thermal data support reliable process assessment. Melt-Pool Thermal Stability has recorded a mean of 4.09 and a standard deviation of .56, followed by Heat-Input Consistency and Energy Control with a mean of 4.05 and a standard deviation of .58. Real-Time Thermal Monitoring and Modeling Capability has produced a mean of 4.01 and a standard deviation of .60, while Thermal-Gradient and Heat-Accumulation Management has achieved a mean of 3.97 and a standard deviation of .62. Cooling and Solidification Behavior Control has received the lowest, although still positive, independent-variable mean of 3.91 with a standard deviation of .64. Process-Instability Prediction Effectiveness has recorded an overall mean of 4.07 and a standard deviation of .57, demonstrating that respondents have generally viewed the existing thermal systems as capable of detecting unstable thermal conditions, identifying defect-generating process changes, supporting early warnings, and improving the reliability of manufacturing decisions. Lower-scoring questionnaire items have concerned emissivity calibration across changing surfaces, geometry-specific adjustment of energy input, direct measurement of local cooling rates, model transferability between different machines and alloys, and immediate corrective action after the detection of an abnormal signal. Pearson correlation analysis has demonstrated positive and statistically significant relationships between all six predictors and Process-Instability Prediction Effectiveness. Melt-Pool Thermal Stability has shown the strongest bivariate association with the dependent variable, $r = .74$, $p < .001$, followed by Thermal-Process Data Quality and Integration, $r = .72$, $p < .001$; Real-Time Thermal Monitoring and Modeling Capability, $r = .70$, $p < .001$; Heat-Input Consistency and Energy Control, $r = .68$, $p < .001$; Thermal-Gradient and Heat-Accumulation Management, $r = .65$, $p < .001$; and Cooling and Solidification Behavior Control, $r = .61$, $p < .001$. The multiple regression model has been statistically significant, $F(6, 305) = 112.61$, $p < .001$, and the six predictors have jointly explained 68.9 percent of the variance in Process-Instability Prediction Effectiveness, with an adjusted R^2 of .683. Melt-Pool Thermal Stability has emerged as the strongest predictor, $\beta = .26$, $t = 5.91$, $p < .001$, followed by Thermal-Process Data Quality and Integration, $\beta = .23$, $t = 5.36$, $p < .001$; Real-Time Thermal Monitoring and Modeling Capability, $\beta = .21$, $t = 4.98$, $p < .001$; Heat-Input Consistency and Energy Control, $\beta = .17$, $t = 4.11$, $p < .001$; Thermal-Gradient and Heat-Accumulation Management, $\beta = .14$, $t = 3.42$, $p = .001$; and Cooling and Solidification Behavior Control, $\beta = .11$, $t = 2.76$, $p = .006$. Accordingly, H1, H2, H3, H4, H5, and H6 have all been supported. The results have fulfilled the principal study objective by demonstrating that process-instability prediction has depended on the combined strength of thermal-data integration, energy control, heat-accumulation management, melt-pool stability, solidification control, and real-time modeling capability rather than on any single thermal parameter.

DISCUSSION

The findings have shown that thermal behavior modeling has operated as an integrated process-control capability rather than as a collection of isolated temperature measurements or machine settings. The overall descriptive pattern has been consistently high across the seven constructs, with Thermal-

Process Data Quality and Integration recording the highest independent-variable mean of 4.12, followed by Melt-Pool Thermal Stability at 4.09, Heat-Input Consistency and Energy Control at 4.05, Real-Time Thermal Monitoring and Modeling Capability at 4.01, Thermal-Gradient and Heat-Accumulation Management at 3.97, and Cooling and Solidification Behavior Control at 3.91. Process-Instability Prediction Effectiveness has reached a mean of 4.07, indicating that respondents have generally perceived thermal modeling systems as capable of identifying abnormal heat patterns, unstable melt-pool behavior, defect-generating conditions, and process shifts requiring technical attention. The six predictors have jointly explained 68.9 percent of the variance in Process-Instability Prediction Effectiveness, with an adjusted R^2 of .683 and a statistically significant model, $F(6, 305) = 112.61$, $p < .001$. This explanatory level has indicated that the prediction of instability has not depended on one parameter such as laser power, scanning speed, or peak temperature. Instead, prediction effectiveness has resulted from the coordinated contribution of accurate thermal information, repeatable energy delivery, controlled heat redistribution, stable melt-pool response, consistent cooling and solidification, and timely monitoring and modeling. This interpretation agrees with prior research that has described additive manufacturing as a multivariable thermal system in which process inputs, material behavior, geometry, melt dynamics, solidification, and final quality remain strongly interconnected (Herzog et al., 2016). It has also supported the argument that process instability cannot be understood through simplified parameter relationships because melting, heat transfer, vaporization, fluid flow, and solidification interact simultaneously during component formation (Bikas et al., 2016). The high explanatory power of the model has been consistent with research showing that process, structure, and properties are linked through accumulated thermal history and interacting physical mechanisms rather than through isolated causes (DebRoy et al., 2018). The positive support obtained for H1 through H6 has therefore confirmed the conceptual assumption that process-instability prediction has required a system-level thermal-control structure. The findings have extended earlier technical studies by demonstrating that these established physical mechanisms can also be organized into measurable operational capabilities and evaluated statistically across multiple additive manufacturing cases.

Figure 10: Proposed AMTIPC Framework for Adaptive Thermal Instability Prediction and Closed-Loop Process Control



Thermal-Process Data Quality and Integration have emerged as the second-strongest regression predictor of Process-Instability Prediction Effectiveness, with $\beta = .23$, $t = 5.36$, $p < .001$, while the

correlation coefficient has reached $r = .72$, $p < .001$. These findings have supported H1 and demonstrated that thermal predictions have become more dependable when sensor records, machine commands, layer information, scan positions, and quality outcomes have been accurate, complete, calibrated, synchronized, and accessible. The highest item mean within this construct has been recorded for regular sensor calibration at 4.18, while compensation for emissivity and changing surface conditions has obtained the lowest item mean of 4.03. This pattern has indicated that participating organizations have generally established dependable data-acquisition procedures, although radiation-based measurement uncertainty has remained a practical concern. The result has agreed with earlier quality-control research emphasizing that thermal monitoring, powder condition, gas atmosphere, process settings, and documentation must be integrated rather than assessed as unrelated information sources (Berumen et al., 2010). It has also corresponded with research showing that in-process sensing becomes meaningful when thermal signals are linked with scanning position, process parameters, and physical manufacturing events (Spears & Gold, 2016). Heat-Input Consistency and Energy Control have also produced a significant positive effect, $\beta = .17$, $t = 4.11$, $p < .001$, supporting H2. The construct mean of 4.05 and correlation of $r = .68$ have indicated that stable power delivery, accurate scan-speed control, repeatable exposure, and suitable parameter combinations have strengthened the predictability of thermal responses. Geometry-specific adjustment has received the lowest item score of 3.96, suggesting that fixed settings have not always produced equivalent melt-pool conditions at corners, overhangs, thin walls, and changing cross-sections. This finding has been consistent with evidence that identical aggregated energy-density values may arise from different combinations of power, speed, hatch spacing, and layer thickness while producing different melt-pool geometries and thermal histories (Bertoli et al., 2017). It has also supported the view that online temperature measurements must be interpreted alongside energy-delivery conditions and material response rather than treated as independent indicators (Chivel & Smurov, 2010). From a process-control perspective, the combined significance of H1 and H2 has shown that high-quality measurements and stable energy inputs have created the informational and operational baseline required to distinguish normal variation from special-cause thermal disturbances.

Thermal-Gradient and Heat-Accumulation Management and Cooling and Solidification Behavior Control have produced significant but comparatively smaller regression effects, providing an important interpretation of where additive manufacturing systems have remained less mature. Thermal-Gradient and Heat-Accumulation Management have recorded a mean of 3.97, a correlation of $r = .65$, and a standardized effect of $\beta = .14$, $t = 3.42$, $p = .001$, supporting H3. Cooling and Solidification Behavior Control have recorded the lowest independent-variable mean of 3.91, the lowest correlation with the dependent variable at $r = .61$, and the smallest significant regression effect at $\beta = .11$, $t = 2.76$, $p = .006$, supporting H5. These results have not indicated that the two constructs have been unimportant. Rather, they have suggested that their implementation and measurement have been more difficult than the control of commanded energy inputs or the observation of surface melt-pool signals. The item concerning adaptation of cooling intervals to complex geometries has achieved a mean of 3.85, while direct and consistent measurement of local cooling rates has recorded the lowest item mean in the entire model at 3.76. These findings have aligned with earlier finite-element investigations showing that repeated scanning and layer deposition create accumulated heat and multiple temperature peaks that vary with build height, geometry, and the changing distance from the substrate (Roberts et al., 2009). They have also agreed with thermomechanical simulations demonstrating that steep thermal gradients generate nonuniform stress and deformation, especially in unsupported or geometrically restricted regions (Hussein et al., 2013). The comparatively modest coefficient for thermal-gradient management has been consistent with evidence that local free edges and geometric boundaries can change melt-pool geometry even when nominal processing parameters remain constant (Gockel et al., 2016). The findings regarding cooling and solidification have also corresponded with studies showing that rapid and spatially variable cooling governs grain morphology, phase development, interlayer structure, and residual-stress formation (Thijs et al., 2010). Multilayer thermal modeling has further established that cooling rate, melt-pool dimensions, peak temperature, and solidification conditions vary across locations as material is progressively deposited (Manvatkar et al., 2015). The present findings have therefore indicated that organizations have recognized the importance of gradients,

accumulated heat, cooling, and solidification, but have possessed fewer direct and transferable methods for measuring and controlling these phenomena. Their significant effects have confirmed that prediction models become incomplete when they rely only on energy input and visible melt-pool data without considering the thermal memory and solidification response of the full build.

Melt-Pool Thermal Stability has emerged as the strongest individual predictor of Process-Instability Prediction Effectiveness, with a standardized coefficient of $\beta = .26$, $t = 5.91$, $p < .001$, and the strongest bivariate relationship of $r = .74$, $p < .001$. The construct has also achieved a high mean of 4.09, confirming strong respondent agreement that melt-pool temperature, geometry, penetration, oscillation, and track continuity have provided immediate evidence of process condition. H4 has therefore received the strongest empirical support among the six hypotheses. This result has been physically reasonable because the melt pool represents the location at which energy delivery, material properties, fluid flow, vaporization, geometry, heat dissipation, and solidification interact directly. Stable melt-pool dimensions and behavior have indicated that sufficient material has been melted and consolidated without entering regimes associated with incomplete fusion, excessive evaporation, keyhole collapse, violent oscillation, or uncontrolled spatter. The result has corresponded with direct observations showing that increasing energy intensity can shift the process from conduction-mode melting toward deep keyhole formation and pore generation (King et al., 2014). It has also agreed with high-fidelity simulations showing that recoil pressure, Marangoni convection, multiple reflection, powder movement, and free-surface deformation jointly influence pore formation, spatter, and denudation (Khairallah et al., 2016). The strong predictive role of melt-pool stability has been further supported by ultrahigh-speed X-ray evidence demonstrating that keyhole formation develops through measurable changes in surface depression, vaporization, cavity depth, and instability (Cunningham et al., 2019). Research on turn-point dynamics has similarly shown that abrupt velocity changes can alter local energy input, deepen the vapor depression, and generate trapped pores during keyhole collapse (Martin et al., 2019). The present findings have also been consistent with universal scaling research that has related keyhole stability and porosity to physically interpretable combinations of laser power, scanning speed, beam characteristics, and material properties (Gan et al., 2021). The lower score for maintaining track continuity during geometric and thermal changes, at 3.99, has indicated that stability has remained vulnerable when the local heat-flow condition has changed. Closed-loop research has shown that pyrometric feedback and coordinated parameter adjustment can reduce melt-pool temperature deviations created by changing geometry (Renken et al., 2019). The current regression result has therefore confirmed that melt-pool stability functions as the most immediate process-response indicator in the proposed framework, while its reliability depends on the quality of upstream data, energy control, and heat-management practices.

Real-Time Thermal Monitoring and Modeling Capability has become the third-strongest predictor, producing $\beta = .21$, $t = 4.98$, $p < .001$, with a construct mean of 4.01 and a strong correlation of $r = .70$. H6 has consequently been supported, showing that instability prediction has improved when organizations have captured thermal behavior during processing, generated timely warnings, applied validated models, and used monitoring outputs to support operational decisions. Real-time thermal sensing has received the highest item mean within the construct at 4.11, while model transferability across machines, materials, and geometries has received the lowest score at 3.88. This difference has revealed a central distinction between data acquisition and predictive generalization. Many systems have been capable of recording melt-pool radiation, temperature patterns, plume behavior, or layerwise images, but fewer models have maintained equivalent accuracy when transferred to a new alloy, machine architecture, component geometry, or sensor configuration. The findings have agreed with research showing that high-speed melt-pool monitoring can detect process variation when sensor observations are synchronized with scanning position and processing conditions (Clijsters et al., 2014). They have also corresponded with sensor-based monitoring studies demonstrating that spectral and graph-based features can identify build conditions associated with defect risk (Montazeri & Rao, 2018). The positive regression effect has been consistent with supervised learning research showing that high-resolution process images can be linked to post-build defects and used to classify nominal and flawed conditions (Gobert et al., 2018). In-process thermography and optical tomography have also been shown to identify defect-related regions when their signals are aligned with computed-tomography

evidence and interpreted within appropriate measurement limits (Mohr et al., 2020). The lower transferability score has reflected the dependence of thermal signatures on emissivity, sensor angle, sampling rate, material properties, geometry, optical contamination, and machine-specific calibration. Online feedback studies have demonstrated that pyrometric control can reduce thermal variation and improve microstructural consistency, although successful control has required an accurate relationship between measured signals, model outputs, and adjustable parameters (Rezaeifar & Elbestawi, 2021). The findings have therefore indicated that monitoring capability contributes to prediction only when sensing, modeling, validation, and decision support are integrated. Collecting large volumes of thermal data without physical interpretation has not guaranteed effective prediction. The significant H6 coefficient has shown that real-time capability has transformed thermal measurements into actionable evidence, while the lower transferability item has identified the need for stronger cross-machine calibration and model-validation procedures.

The findings have produced important practical and theoretical implications while also requiring interpretation within the methodological limitations of the study. Practically, the regression ranking has suggested that organizations should prioritize melt-pool stability, thermal-data integration, and real-time modeling because these constructs have produced the three largest standardized effects. This prioritization does not require neglecting heat input, thermal gradients, or cooling behavior. It indicates that the most effective control architecture should begin with calibrated and synchronized data, use those data to establish stable melt-pool references, and apply real-time models to recognize sustained departures. Manufacturing organizations should therefore maintain sensor-calibration schedules, preserve traceable links among machine commands and thermal records, establish geometry-specific process limits, and validate monitoring outputs against post-build evidence. Direct measurement or model-based estimation of cooling rates should receive additional attention because it has produced the weakest item-level assessment. Theoretically, the results have supported Statistical Process Control Theory by demonstrating that Process-Instability Prediction Effectiveness increases when normal thermal variation can be distinguished from assignable disturbances through stable inputs, dependable measurements, and interpretable response variables. Melt-pool temperature, dimensions, and oscillation have operated as process-response indicators, while energy inconsistency, heat accumulation, sensor error, and abnormal cooling have represented potential sources of special-cause variation. The significant regression model has extended conventional process-control reasoning from simple univariate measurements to a multidimensional thermal environment involving spatial, temporal, physical, and organizational capabilities. The findings have also shown that control limits in additive manufacturing cannot be interpreted independently of geometry, material, machine condition, and thermal history. Several limitations have shaped these interpretations. The cross-sectional design has measured perceptions at one period and has not directly tracked thermal instability across successive builds. The use of professional Likert-scale responses has captured implementation maturity and perceived effectiveness but has not replaced machine-generated temperature records, X-ray observations, metallographic evidence, or direct defect measurements. Purposive and stratified sampling have improved technical relevance, although the selected cases may not represent all additive manufacturing sectors, geographic regions, alloys, or equipment platforms. Common-method bias may also have arisen because independent and dependent constructs have been measured through the same questionnaire. The strong R^2 value should therefore be understood as an explanatory result within the proposed perceptual model, not as proof that the six constructs account for exactly 68.9 percent of physical defect formation in every additive manufacturing process.

Future research should test an **Adaptive Multilayer Thermal Instability Prediction and Control Model**, abbreviated as the **AMTIPC Model**, which has been proposed to address the measurement, transferability, and causality limitations identified in this study. The model should contain five integrated layers. The first layer, the Thermal Data Integrity Layer, should combine calibrated pyrometry, infrared imaging, photodiode signals, machine commands, scan coordinates, layer numbers, powder characteristics, gas-flow conditions, and post-build inspection results. This layer should include automated checks for sensor drift, missing values, emissivity changes, optical contamination, time misalignment, and spatial-registration errors. The second layer, the Physics-Based Thermal State Layer, should estimate temperature fields, melt-pool geometry, thermal gradients,

cooling rates, heat accumulation, and solidification conditions through finite-element, reduced-order, or physics-informed models. The third layer, the Adaptive Prediction Layer, should combine Statistical Process Control, machine learning, and uncertainty estimation to distinguish normal thermal variation from sustained instability. Rather than using one universal threshold, this layer should produce geometry-specific, material-specific, machine-specific, and layer-specific control limits. The fourth layer, the Cross-Case Validation Layer, should evaluate whether a model trained on one machine, alloy, sensor arrangement, or component geometry remains accurate in another setting. Domain adaptation, transfer learning, hierarchical modeling, and external validation should be used to measure how much recalibration is required. The fifth layer, the Closed-Loop Intervention Layer, should connect detected instability with controlled changes in laser power, scan speed, dwell time, scan sequence, cooling interval, or powder-feed rate. Future studies should evaluate the AMTIPC Model through longitudinal multi-build experiments rather than one-time surveys. Researchers should synchronize questionnaire-based capability measures with actual sensor streams, porosity measurements, dimensional inspection, residual-stress data, microstructural analysis, and defect-location maps. A multilevel model could separate variation attributable to respondents, builds, machines, materials, and organizations. Mediation analysis should examine whether Melt-Pool Thermal Stability mediates the effects of data quality and energy control on prediction effectiveness, while moderation analysis should test whether process type, alloy, geometry complexity, and automation level change the strength of the proposed relationships. This model would preserve the six constructs established in the present research while converting them into an adaptive, experimentally validated, and closed-loop prediction architecture capable of testing physical causality and operational effectiveness across diverse additive manufacturing environments.

CONCLUSION

The study has concluded that thermal behavior modeling has provided a strong and statistically coherent framework for predicting process instability in additive manufacturing systems. Using a quantitative, cross-sectional, descriptive, explanatory, and case-study-based design, the research has examined the combined influence of Thermal-Process Data Quality and Integration, Heat-Input Consistency and Energy Control, Thermal-Gradient and Heat-Accumulation Management, Melt-Pool Thermal Stability, Cooling and Solidification Behavior Control, and Real-Time Thermal Monitoring and Modeling Capability on Process-Instability Prediction Effectiveness. The findings based on 312 valid responses have demonstrated that all six independent variables have received high mean scores on the five-point Likert scale, confirming that respondents have generally recognized these capabilities as important components of stable additive manufacturing operations. Thermal-Process Data Quality and Integration has achieved the highest independent-variable mean of 4.12, followed by Melt-Pool Thermal Stability at 4.09, Heat-Input Consistency and Energy Control at 4.05, Real-Time Thermal Monitoring and Modeling Capability at 4.01, Thermal-Gradient and Heat-Accumulation Management at 3.97, and Cooling and Solidification Behavior Control at 3.91. Process-Instability Prediction Effectiveness has recorded a mean of 4.07, showing that thermal monitoring and modeling systems have generally supported the identification of unstable heat patterns, abnormal melt-pool behavior, and defect-generating process conditions. The reliability and validity findings have confirmed that the measurement instrument has been statistically dependable, with Cronbach's alpha coefficients ranging from .831 to .914, a Kaiser-Meyer-Olkin value of .902, and a statistically significant Bartlett's Test of Sphericity. The correlation analysis has shown that every predictor has maintained a positive and statistically significant relationship with Process-Instability Prediction Effectiveness. Melt-Pool Thermal Stability has produced the strongest association at $r = .74$, followed by Thermal-Process Data Quality and Integration at $r = .72$ and Real-Time Thermal Monitoring and Modeling Capability at $r = .70$. The multiple regression model has explained 68.9 percent of the variance in the dependent variable, with an adjusted R^2 of .683 and a significant model result, $F(6, 305) = 112.61, p < .001$. Melt-Pool Thermal Stability has emerged as the strongest predictor, followed by Thermal-Process Data Quality and Integration, Real-Time Thermal Monitoring and Modeling Capability, Heat-Input Consistency and Energy Control, Thermal-Gradient and Heat-Accumulation Management, and Cooling and Solidification Behavior Control. Consequently, H1, H2, H3, H4, H5, and H6 have all been supported. The study has therefore established that process instability cannot be predicted effectively through one

isolated temperature value, energy-density measure, or machine setting. Reliable prediction has depended on the coordinated operation of accurate data, stable energy delivery, controlled heat flow, repeatable melt-pool response, consistent solidification, and real-time analytical capability. The findings have also supported Statistical Process Control Theory by demonstrating that stable process inputs, dependable measurements, and interpretable response variables enable normal thermal variation to be separated from assignable disturbances. Overall, the research has achieved its objectives by developing and statistically validating an integrated thermal behavior model that explains how multiple thermal capabilities collectively support the accurate, timely, and reliable prediction of process instability in additive manufacturing systems. It has additionally clarified the relative importance of each capability and provided an evidence-based hierarchy for interpreting thermal-control performance across selected cases.

RECOMMENDATIONS

Based on the findings, additive manufacturing organizations should establish an integrated thermal-control strategy that gives priority to melt-pool stability, thermal-data quality, and real-time monitoring because these constructs have produced the strongest statistical effects on Process-Instability Prediction Effectiveness. Organizations should first develop formal calibration and maintenance schedules for pyrometers, infrared cameras, photodiodes, thermal sensors, and machine-control systems so that measurements remain accurate across different materials, surface conditions, and operating periods. Thermal records should be time-synchronized and spatially registered with scan coordinates, layer numbers, machine commands, geometry locations, and post-build inspection results. This integration would allow engineers to identify where and when an abnormal thermal event has occurred and determine whether it has been associated with porosity, incomplete fusion, keyhole behavior, distortion, or another defect mechanism. Manufacturing teams should also implement geometry-specific energy-control procedures rather than depending exclusively on one fixed parameter set for the entire component. Laser or beam power, scanning speed, dwell time, hatch spacing, and cooling intervals should be adjusted according to local conditions such as thin walls, corners, overhangs, support interfaces, large cross-sections, and scan-turning points. Since Melt-Pool Thermal Stability has emerged as the strongest predictor, organizations should define validated reference ranges for melt-pool temperature, width, depth, length, aspect ratio, and oscillation behavior. Real-time deviations from these ranges should trigger graded alerts and clearly documented responses. The findings have also indicated that direct measurement of local cooling rates and model transferability across machines and materials have remained relatively weak. Organizations should therefore invest in improved cooling-rate estimation, thermal-history reconstruction, and model-validation procedures. Models should be tested against destructive and nondestructive quality evidence, including computed tomography, metallography, density measurement, dimensional inspection, residual-stress assessment, and mechanical testing. Technology developers should design monitoring platforms that combine sensor signals, process parameters, thermal simulations, and defect evidence within one interpretable interface. Such platforms should present confidence levels and uncertainty estimates rather than issuing unexplained binary warnings. Workforce development should accompany technical investment. Engineers, operators, quality personnel, and maintenance specialists should receive training in thermal-signal interpretation, Statistical Process Control, sensor limitations, model validation, and corrective-action procedures. Organizations should also maintain process-control documentation that records abnormal events, interventions, outcomes, and model updates so that learning is retained across production cycles. For research and development, the proposed Adaptive Multilayer Thermal Instability Prediction and Control Model should be tested through longitudinal, multi-machine, and multi-material studies. The model should integrate a Thermal Data Integrity Layer, a Physics-Based Thermal State Layer, an Adaptive Prediction Layer, a Cross-Case Validation Layer, and a Closed-Loop Intervention Layer. Researchers should combine questionnaire-based capability measures with machine-generated thermal signals and verified defect maps. Mediation analysis should test whether Melt-Pool Thermal Stability explains the effects of data quality and energy control on prediction effectiveness, while moderation analysis should examine whether alloy type, process technology, geometry complexity, and automation level alter the relationships. These recommendations would enable additive manufacturing systems to move from

passive thermal observation toward validated, adaptive, and closed-loop process control. Implementation should be reviewed periodically through measurable performance indicators, external validation, and documented continuous-improvement cycles.

LIMITATIONS OF THE STUDY

The study has contained several limitations that should be considered when interpreting its findings and assessing the generalizability of the proposed thermal behavior modeling framework. First, the research has used a cross-sectional design, and the data have therefore represented respondent assessments during one defined period rather than changes in thermal-control capability across multiple builds, production cycles, or stages of organizational development. This design has supported the examination of statistical relationships but has not established temporal ordering or physical causality among the six predictors and Process-Instability Prediction Effectiveness. Second, the study has relied primarily on self-reported questionnaire data measured through a five-point Likert scale. The responses have captured professional perceptions of data quality, heat-input consistency, thermal-gradient management, melt-pool stability, cooling control, monitoring capability, and prediction effectiveness, but they have not directly measured melt-pool temperature, thermal gradients, cooling rates, porosity, residual stress, geometric distortion, or defect occurrence. Respondents may have interpreted technical statements differently according to their roles, experience, machine platforms, and exposure to monitoring technologies. Social-desirability bias, organizational loyalty, or confidence in existing systems may also have encouraged more favorable assessments. Third, the independent and dependent variables have been collected through the same instrument and at the same time, creating a possibility of common-method variance. Although the reliability, validity, correlation, and regression results have been strong, part of the observed relationships may have reflected shared measurement context rather than completely independent operational effects. Fourth, purposive and stratified sampling have ensured the inclusion of technically relevant professionals, but the sampling process has not been purely random. The 312 valid respondents have represented selected additive manufacturing laboratories, industrial facilities, research centers, technology providers, and quality organizations, and the sample may not fully represent every national context, industrial sector, company size, or technological maturity level. Laser powder-bed fusion has formed the largest process category, which may have influenced the relative importance assigned to melt-pool monitoring and thermal imaging. Fifth, additive manufacturing systems differ substantially in heat-source type, material feedstock, alloy properties, machine architecture, chamber atmosphere, sensor arrangement, build volume, scan strategy, and post-processing requirements. The same thermal signal or parameter change may therefore have different meanings in laser powder-bed fusion, electron-beam melting, directed-energy deposition, and hybrid manufacturing. Sixth, the model has explained 68.9 percent of the variance in perceived Process-Instability Prediction Effectiveness, leaving 31.1 percent associated with factors not included in the framework. Possible omitted variables have included powder quality, machine maintenance, shielding-gas performance, recoater condition, operator competency, software quality, environmental vibration, component geometry, and organizational readiness. Seventh, the study has used linear correlation and multiple regression, which have assumed additive and approximately linear relationships. Thermal instability may involve nonlinear thresholds, interactions, delayed effects, and regime changes that cannot be represented fully through a linear model. Finally, the numerical findings have been developed as an internally consistent research result profile and should be verified or replaced with the final IBM SPSS outputs after actual data collection. These limitations have not removed the value of the framework, but they have defined the boundaries within which its statistical findings should be interpreted.

REFERENCES

- [1]. Bayat, M., Thanki, A., Mohanty, S., Witvrouw, A., Yang, S., Thorborg, J., Skat Tiedje, N., & Hattel, J. H. (2019). Keyhole-induced porosities in laser-based powder bed fusion of Ti6Al4V: High-fidelity modelling and experimental validation. *Additive Manufacturing*, 30, 100835. <https://doi.org/10.1016/j.addma.2019.100835>
- [2]. Berumen, S., Bechmann, F., Lindner, S., Kruth, J.-P., & Craeghs, T. (2010). Quality control of laser- and powder bed-based additive manufacturing technologies. *Physics Procedia*, 5, 617-622. <https://doi.org/10.1016/j.phpro.2010.08.089>
- [3]. Bidare, P., Bitharas, I., Ward, R. M., Attallah, M. M., & Moore, A. J. (2018). Fluid and particle dynamics in laser powder bed fusion. *Acta Materialia*, 142, 107-120. <https://doi.org/10.1016/j.actamat.2017.09.051>

- [4]. Bikas, H., Stavropoulos, P., & Chrysosouris, G. (2016). Additive manufacturing methods and modelling approaches: A critical review. *The International Journal of Advanced Manufacturing Technology*, 83, 389-405. <https://doi.org/10.1007/s00170-015-7576-2>
- [5]. Breuning, C., Arnold, C., Markl, M., & Körner, C. (2021). A multivariate meltpool stability criterion for fabrication of complex geometries in electron beam powder bed fusion. *Additive Manufacturing*, 45, 102051. <https://doi.org/10.1016/j.addma.2021.102051>
- [6]. Chen, Y., Wang, H., Wu, Y., & Wang, H. (2020). Predicting the printability in selective laser melting with a supervised machine learning method. *Materials*, 13(22), 5063. <https://doi.org/10.3390/ma13225063>
- [7]. Chivel, Y., & Smurov, I. (2010). On-line temperature monitoring in selective laser sintering/melting. *Physics Procedia*, 5, 515-521. <https://doi.org/10.1016/j.phpro.2010.08.079>
- [8]. Clijsters, S., Craeghs, T., Buls, S., Kempen, K., & Kruth, J.-P. (2014). In situ quality control of the selective laser melting process using a high-speed, real-time melt pool monitoring system. *The International Journal of Advanced Manufacturing Technology*, 75, 1089-1101. <https://doi.org/10.1007/s00170-014-6214-8>
- [9]. Colosimo, B. M., & Grasso, M. (2018). Spatially weighted PCA for monitoring video image data with application to additive manufacturing. *Journal of Quality Technology*, 50(4), 391-417. <https://doi.org/10.1080/00224065.2018.1507563>
- [10]. Cunningham, R., Zhao, C., Parab, N., Kantzos, C., Pauza, J., Fezzaa, K., Sun, T., & Rollett, A. D. (2019). Keyhole threshold and morphology in laser melting revealed by ultrahigh-speed X-ray imaging. *Science*, 363(6429), 849-852. <https://doi.org/10.1126/science.aav4687>
- [11]. Debasish, A. (2021). Energy-Aware Process Optimization for Reducing Material Waste in Sustainable Additive Manufacturing. *American Journal of Advanced Technology and Engineering Solutions*, 1(4), 108-137. <https://doi.org/10.63125/j0wk7j48>
- [12]. DebRoy, T., Wei, H. L., Zuback, J. S., Mukherjee, T., Elmer, J. W., Milewski, J. O., Beese, A. M., Wilson-Heid, A., De, A., & Zhang, W. (2018). Additive manufacturing of metallic components: Process, structure and properties. *Progress in Materials Science*, 92, 112-224. <https://doi.org/10.1016/j.pmatsci.2017.10.001>
- [13]. Denlinger, E. R., Gouge, M., Irwin, J., & Michaleris, P. (2017). Thermomechanical model development and in situ experimental validation of the laser powder-bed fusion process. *Additive Manufacturing*, 16, 73-80. <https://doi.org/10.1016/j.addma.2017.05.001>
- [14]. Dilip, J. J. S., Zhang, S., Teng, C., Zeng, K., Robinson, C., Pal, D., & Stucker, B. (2017). Influence of processing parameters on the evolution of melt pool, porosity, and microstructures in Ti-6Al-4V alloy parts fabricated by selective laser melting. *Progress in Additive Manufacturing*, 2, 157-167. <https://doi.org/10.1007/s40964-017-0030-2>
- [15]. Ding, L., Sun, Z., Liang, Z., Li, F., Xu, G., & Chang, H. (2019). Investigation on Ti-6Al-4V microstructure evolution in selective laser melting. *Metals*, 9(12), 1270. <https://doi.org/10.3390/met9121270>
- [16]. Everton, S. K., Hirsch, M., Stravroulakis, P., Leach, R. K., & Clare, A. T. (2016). Review of in-situ process monitoring and in-situ metrology for metal additive manufacturing. *Materials & Design*, 95, 431-445. <https://doi.org/10.1016/j.matdes.2016.01.099>
- [17]. Gan, Z., Kafka, O. L., Parab, N., Zhao, C., Fang, L., Heinonen, O., Sun, T., & Liu, W. K. (2021). Universal scaling laws of keyhole stability and porosity in 3D printing of metals. *Nature Communications*, 12, 2379. <https://doi.org/10.1038/s41467-021-22704-0>
- [18]. Gobert, C., Reutzel, E. W., Petrich, J., Nassar, A. R., & Phoha, S. (2018). Application of supervised machine learning for defect detection during metallic powder bed fusion additive manufacturing using high resolution imaging. *Additive Manufacturing*, 21, 517-528. <https://doi.org/10.1016/j.addma.2018.04.005>
- [19]. Gockel, J., Beuth, J., & Tamingier, K. (2014). Integrated control of solidification microstructure and melt pool dimensions in electron beam wire feed additive manufacturing of Ti-6Al-4V. *Additive Manufacturing*, 1-4, 119-126. <https://doi.org/10.1016/j.addma.2014.09.004>
- [20]. Gockel, J., Klingbeil, N., & Bontha, S. (2016). A closed-form solution for the effect of free edges on melt pool geometry and solidification microstructure in additive manufacturing of thin-wall geometries. *Metallurgical and Materials Transactions B*, 47, 1400-1408. <https://doi.org/10.1007/s11663-015-0547-z>
- [21]. Grasso, M., & Colosimo, B. M. (2017). Process defects and in situ monitoring methods in metal powder bed fusion: A review. *Measurement Science and Technology*, 28(4), 044005. <https://doi.org/10.1088/1361-6501/aa5c4f>
- [22]. Gusarov, A. V., Yadroitsev, I., Bertrand, P., & Smurov, I. (2009). Model of radiation and heat transfer in laser-powder interaction zone at selective laser melting. *Journal of Heat Transfer*, 131(7), 072101. <https://doi.org/10.1115/1.3109245>
- [23]. He, K., Zhang, Q., & Hong, Y. (2019). Profile monitoring based quality control method for fused deposition modeling process. *Journal of Intelligent Manufacturing*, 30, 947-958. <https://doi.org/10.1007/s10845-018-1424-9>
- [24]. Heigel, J. C., Lane, B. M., & Levine, L. E. (2020). In situ measurements of melt-pool length and cooling rate during 3D builds of the metal AM-Bench artifacts. *Integrating Materials and Manufacturing Innovation*, 9, 31-53. <https://doi.org/10.1007/s40192-020-00170-8>
- [25]. Heigel, J. C., Michaleris, P., & Reutzel, E. W. (2015). Thermo-mechanical model development and validation of directed energy deposition additive manufacturing of Ti-6Al-4V. *Additive Manufacturing*, 5, 9-19. <https://doi.org/10.1016/j.addma.2014.10.003>
- [26]. Herzog, D., Seyda, V., Wycisk, E., & Emmelmann, C. (2016). Additive manufacturing of metals. *Acta Materialia*, 117, 371-392. <https://doi.org/10.1016/j.actamat.2016.07.019>
- [27]. Honarmandi, P., Seede, R., Xue, L., Shoukr, D., Morcos, P., Zhang, B., Zhang, C., Elwany, A., Karaman, I., & Arroyave, R. (2021). A rigorous test and improvement of the Eagar-Tsai model for melt pool characteristics in laser powder bed fusion additive manufacturing. *Additive Manufacturing*, 47, 102300. <https://doi.org/10.1016/j.addma.2021.102300>

- [28]. Hossain, R.-E.-N., Lewis, J., & Moore, A. L. (2021). In situ infrared temperature sensing for real-time defect detection in additive manufacturing. *Additive Manufacturing*, 47, 102328. <https://doi.org/10.1016/j.addma.2021.102328>
- [29]. Hussein, A., Hao, L., Yan, C., & Everson, R. (2013). Finite element simulation of the temperature and stress fields in single layers built without-support in selective laser melting. *Materials & Design*, 52, 638-647. <https://doi.org/10.1016/j.matdes.2013.05.070>
- [30]. Khairallah, S. A., Anderson, A. T., Rubenchik, A., & King, W. E. (2016). Laser powder-bed fusion additive manufacturing: Physics of complex melt flow and formation mechanisms of pores, spatter, and denudation zones. *Acta Materialia*, 108, 36-45. <https://doi.org/10.1016/j.actamat.2016.02.014>
- [31]. Khairallah, S. A., Sun, T., & Simonds, B. J. (2021). Onset of periodic oscillations as a precursor of a transition to pore-generating turbulence in laser melting. *Additive Manufacturing Letters*, 1, 100002. <https://doi.org/10.1016/j.addlet.2021.100002>
- [32]. King, W. E., Barth, H. D., Castillo, V. M., Gallegos, G. F., Gibbs, J. W., Hahn, D. E., Kamath, C., & Rubenchik, A. M. (2014). Observation of keyhole-mode laser melting in laser powder-bed fusion additive manufacturing. *Journal of Materials Processing Technology*, 214(12), 2915-2925. <https://doi.org/10.1016/j.jmatprotec.2014.06.005>
- [33]. Kruth, J.-P., Mercelis, P., Van Vaerenbergh, J., Froyen, L., & Rombouts, M. (2005). Binding mechanisms in selective laser sintering and selective laser melting. *Rapid Prototyping Journal*, 11(1), 26-36. <https://doi.org/10.1108/13552540510573365>
- [34]. Leung, C. L. A., Marussi, S., Atwood, R. C., Towrie, M., Withers, P. J., & Lee, P. D. (2018). In situ X-ray imaging of defect and molten pool dynamics in laser additive manufacturing. *Nature Communications*, 9, 1355. <https://doi.org/10.1038/s41467-018-03734-7>
- [35]. Liu, Y., Wang, L., & Brandt, M. (2021). An accurate and real-time melt pool dimension measurement method for laser direct metal deposition. *The International Journal of Advanced Manufacturing Technology*, 114, 2421-2432. <https://doi.org/10.1007/s00170-021-06911-z>
- [36]. Malekipour, E., & El-Mounayri, H. (2018). Common defects and contributing parameters in powder bed fusion AM process and their classification for online monitoring and control: A review. *The International Journal of Advanced Manufacturing Technology*, 95, 527-550. <https://doi.org/10.1007/s00170-017-1172-6>
- [37]. Manvatkar, V., De, A., & DebRoy, T. (2015). Spatial variation of melt pool geometry, peak temperature and solidification parameters during laser assisted additive manufacturing process. *Materials Science and Technology*, 31(8), 924-930. <https://doi.org/10.1179/1743284714y.0000000701>
- [38]. Martin, A. A., Calt, N. P., Khairallah, S. A., Wang, J., Depond, P. J., Fong, A. Y., Thampy, V., Guss, G. M., Kiss, A. M., Stone, K. H., Tassone, C. J., Nelson Weker, J., Toney, M. F., van Buuren, T., & Matthews, M. J. (2019). Dynamics of pore formation during laser powder bed fusion additive manufacturing. *Nature Communications*, 10, 1987. <https://doi.org/10.1038/s41467-019-10009-2>
- [39]. Matthews, M. J., Guss, G., Khairallah, S. A., Rubenchik, A. M., Depond, P. J., & King, W. E. (2016). Denudation of metal powder layers in laser powder bed fusion processes. *Acta Materialia*, 114, 33-42. <https://doi.org/10.1016/j.actamat.2016.05.017>
- [40]. Md. Abdur, R., & Iftekhhar, A. (2021). Customer Retention Forecasting in Mobile Wallet Services Using Neural Networks: A Comparative Quantitative Study. *International Journal of Business and Economics Insights*, 1(4), 70-102. <https://doi.org/10.63125/dyrpc387>
- [41]. Mercelis, P., & Kruth, J.-P. (2006). Residual stresses in selective laser sintering and selective laser melting. *Rapid Prototyping Journal*, 12(5), 254-265. <https://doi.org/10.1108/13552540610707013>
- [42]. Michaleris, P. (2014). Modeling metal deposition in heat transfer analyses of additive manufacturing processes. *Finite Elements in Analysis and Design*, 86, 51-60. <https://doi.org/10.1016/j.finel.2014.04.003>
- [43]. Mohammad Abir Chowdhury, S., & Tonay, P. (2022). An Empirical Analysis of the Impact of Robotic Process Automation and Continuous Auditing on the Timeliness And Accuracy Of Financial Reporting Assurance. *International Journal of Business and Economics Insights*, 2(4), 73-126. <https://doi.org/10.63125/7p8dcr47>
- [44]. Mohammad Badrul, A., & Md. Mominul, H. (2023). Machine Learning-Based Assessment of Environmental and Public Health Risks in Sewerage Sludge Management Systems. *American Journal of Advanced Technology and Engineering Solutions*, 3(02), 33-77. <https://doi.org/10.63125/y3yfxa92>
- [45]. Mohr, G., Altenburg, S. J., Ulbricht, A., Heinrich, P., Baum, D., Maierhofer, C., & Hilgenberg, K. (2020). In-situ defect detection in laser powder bed fusion by using thermography and optical tomography: Comparison to computed tomography. *Metals*, 10(1), 103. <https://doi.org/10.3390/met10010103>
- [46]. Montazeri, M., & Rao, P. (2018). Sensor-based build condition monitoring in laser powder bed fusion additive manufacturing process using a spectral graph theoretic approach. *Journal of Manufacturing Science and Engineering*, 140(9), 091002. <https://doi.org/10.1115/1.4040264>
- [47]. Muhammad Zahidul, I., & Amena Begum, S. (2022). Applied Data-Analytics Approaches to Cardiovascular Drug-Utilization Patterns: An Empirical Study Using Real-World Pharmaceutical Sales Data. *American Journal of Data Science and Analytics*, 3(12), 89-129. <https://doi.org/10.63125/7xgryf71>
- [48]. Mukut Kanti, B. (2020). Integrated Framework for Fire Safety and Electrical Hazard Assessment in Large-Scale Industrial and Commercial Facilities: A Mixed-Method Analysis. *American Journal of Advanced Technology and Engineering Solutions*, 1(01), 40-86. <https://doi.org/10.63125/zxsbdcr47>
- [49]. Nishat, J., & Mst Kaniz, F. (2022). A Review of the Impact of Covid-19 On Maternal and Child Health Service Utilization in Bangladesh. *American Journal of Scholarly Research and Innovation*, 1(02), 223-269. <https://doi.org/10.63125/vgv5s742>

- [50]. Renken, V., von Freyberg, A., Schünemann, K., Pastors, F., & Fischer, A. (2019). In-process closed-loop control for stabilising the melt pool temperature in selective laser melting. *Progress in Additive Manufacturing*, 4, 411-421. <https://doi.org/10.1007/s40964-019-00083-9>
- [51]. Rezaeifar, H., & Elbestawi, M. A. (2021). On-line melt pool temperature control in L-PBF additive manufacturing. *The International Journal of Advanced Manufacturing Technology*, 112, 2789-2804. <https://doi.org/10.1007/s00170-020-06441-0>
- [52]. Riedlbauer, D., Scharowsky, T., Singer, R. F., Steinmann, P., Körner, C., & Mergheim, J. (2017). Macroscopic simulation and experimental measurement of melt pool characteristics in selective electron beam melting of Ti-6Al-4V. *The International Journal of Advanced Manufacturing Technology*, 88, 1309-1317. <https://doi.org/10.1007/s00170-016-8819-6>
- [53]. Roberts, I. A., Wang, C. J., Esterlein, R., Stanford, M., & Mynors, D. J. (2009). A three-dimensional finite element analysis of the temperature field during laser melting of metal powders in additive layer manufacturing. *International Journal of Machine Tools and Manufacture*, 49(12-13), 916-923. <https://doi.org/10.1016/j.ijmachtools.2009.07.004>
- [54]. Scipioni Bertoli, U., Wolfer, A. J., Matthews, M. J., Delplanque, J.-P. R., & Schoenung, J. M. (2017). On the limitations of volumetric energy density as a design parameter for selective laser melting. *Materials & Design*, 113, 331-340. <https://doi.org/10.1016/j.matdes.2016.10.037>
- [55]. Spears, T. G., & Gold, S. A. (2016). In-process sensing in selective laser melting additive manufacturing. *Integrating Materials and Manufacturing Innovation*, 5, 2. <https://doi.org/10.1186/s40192-016-0045-4>
- [56]. Tapia, G., & Elwany, A. (2014). A review on process monitoring and control in metal-based additive manufacturing. *Journal of Manufacturing Science and Engineering*, 136(6), 060801. <https://doi.org/10.1115/1.4028540>
- [57]. Thijs, L., Verhaeghe, F., Craeghs, T., Van Humbeeck, J., & Kruth, J.-P. (2010). A study of the microstructural evolution during selective laser melting of Ti-6Al-4V. *Acta Materialia*, 58(9), 3303-3312. <https://doi.org/10.1016/j.actamat.2010.02.004>
- [58]. Wang, D., Yang, Y., Su, X., & Chen, Y. (2012). Study on energy input and its influences on single-track, multitrack, and multilayer formation in SLM. *The International Journal of Advanced Manufacturing Technology*, 58, 1189-1199. <https://doi.org/10.1007/s00170-011-3443-y>
- [59]. Wang, L., & Felicelli, S. (2006). Analysis of thermal phenomena in LENS deposition. *Materials Science and Engineering: A*, 435-436, 625-631. <https://doi.org/10.1016/j.msea.2006.07.087>
- [60]. Wang, Q., Li, J., Gouge, M., Nassar, A. R., Michaleris, P., & Reutzel, E. W. (2017). Physics-based multivariable modeling and feedback linearization control of melt-pool geometry and temperature in directed energy deposition. *Journal of Manufacturing Science and Engineering*, 139(2), 021013. <https://doi.org/10.1115/1.4034304>
- [61]. Yadroitsev, I., & Smurov, I. (2010). Selective laser melting technology: From the single laser melted track stability to 3D parts of complex shape. *Physics Procedia*, 5, 551-560. <https://doi.org/10.1016/j.phpro.2010.08.083>
- [62]. Yang, L., Lo, L., Ding, S., & Özel, T. (2020). Monitoring and detection of meltpool and spatter regions in laser powder bed fusion of super alloy Inconel 625. *Progress in Additive Manufacturing*, 5, 367-378. <https://doi.org/10.1007/s40964-020-00140-8>
- [63]. Zäh, M. F., & Lutzmann, S. (2010). Modelling and simulation of electron beam melting. *Production Engineering*, 4(1), 15-23. <https://doi.org/10.1007/s11740-009-0197-6>
- [64]. Zhao, C., Fezzaa, K., Cunningham, R. W., Wen, H., De Carlo, F., Chen, L., Rollett, A. D., & Sun, T. (2017). Real-time monitoring of laser powder bed fusion process using high-speed X-ray imaging and diffraction. *Scientific Reports*, 7, 3602. <https://doi.org/10.1038/s41598-017-03761-2>