International Journal of Scientific Interdisciplinary Research

Volume: 14; **Issue:** 9
Pages: 01– 41

Machine Learning Enhanced Intrusion Detection and Anomaly Classification for MIS-Driven Enterprise Network Security

Kynatun Mahin[1]; Saba Ashfaq[2];

[1]. Graduate Student, Management Information Systems; Lamar University; Texas, United States;
Email: kynat.mahin@gmail.com

[2]. Graduate Student, M.S. in Information Technology, Washington University of Science and Technology, Alexandria, Virginia, United States;
Email: sabarashfaq01@gmail.com

Doi: 10.63125/xk6kpc72
Received: *11 June 2024;* ***Revised:*** *21 July 2024;* ***Accepted:*** *13 August 2024;* ***Published:*** *02 September 2024*

Abstract

This study addresses the persistent challenge of protecting MIS-driven enterprise networks against increasingly complex, previously unseen, and adaptive cyber threats when conventional signature-based controls, fragmented security data, and static monitoring practices provide limited visibility and response capability. The purpose was to examine how Machine Learning-Based Intrusion Detection Capability (MLIDC), Intelligent Anomaly Classification Capability (IACC), MIS-Security Data Integration (MSDI), and Adaptive Threat Monitoring and Response (ATMR) influence Enterprise Network Security Performance (ENSP) across enterprise environments containing interconnected digital, network, and cloud-enabled resources. A quantitative, cross-sectional, explanatory, case-based survey design was adopted using purposive sampling of cybersecurity analysts, network administrators, IT/MIS'S managers, security engineers, system administrators, and IT risk or compliance professionals. Of 320 questionnaires distributed, 298 were returned and 286 valid responses were retained, yielding an 89.4% valid response rate. Data were analyzed using descriptive statistics, Cronbach's alpha, KMO and Bartlett tests, Pearson correlation, multiple regression, ANOVA, multicollinearity diagnostics, and residual testing. ENSP recorded the highest mean ($M = 4.21$, $SD = 0.51$), followed by IACC ($M = 4.18$, $SD = 0.54$), ATMR ($M = 4.16$, $SD = 0.56$), MLIDC ($M = 4.13$, $SD = 0.58$), and MSDI ($M = 4.09$, $SD = 0.60$). All predictors were positively associated with ENSP: IACC ($r = .78$), ATMR ($r = .75$), MSDI ($r = .71$), and MLIDC ($r = .69$), all $p < .001$. The regression model explained 71.4% of ENSP variance ($R^2 = .714$, adjusted $R^2 = .710$, $F(4,281) = 175.40$, $p < .001$), with IACC the strongest predictor ($\beta = .34$), followed by ATMR ($\beta = .28$), MSDI ($\beta = .23$), and MLIDC ($\beta = .20$). The findings imply that enterprise cybersecurity improves when intelligent detection is integrated with accurate anomaly classification, coordinated security information, and adaptive threat response, supporting security operations, MIS visibility, faster incident handling, and resilient enterprise network protection.

Keywords

Machine Learning-Based Intrusion Detection; Intelligent Anomaly Classification; Enterprise Network Security; MIS-Security Data Integration; Adaptive Threat Monitoring and Response

INTRODUCTION

Cybersecurity can be defined as the coordinated protection of information systems, communication networks, digital assets, and network-enabled organizational processes against unauthorized access, disruption, manipulation, disclosure, and other forms of malicious activity. Within this broader domain, an intrusion detection system (IDS) refers to a security mechanism that observes host or network activities and distinguishes legitimate behavior from activities associated with attacks or policy violations. Machine learning refers to computational techniques through which models learn patterns and decision boundaries from data rather than depending exclusively on manually encoded signatures or static rules. Anomaly detection is more specifically concerned with identifying observations or behavioral patterns that deviate meaningfully from a representation of normal activity, while anomaly classification extends this function by assigning suspicious observations to identifiable attack or behavioral categories. In An overview of anomaly detection techniques (pp. 3448-3470), anomaly detection is presented as a response to the limitations of purely signature-oriented security mechanisms when previously unseen behavioral deviations must be recognized (Patcha & Park, 2007). The related article Anomaly-based network intrusion detection: Techniques, systems and challenges (pp. 18-28) describes anomaly-oriented intrusion detection as a mechanism for modeling legitimate behavior and detecting significant departures from that behavioral profile (García-Teodoro et al., 2009). This distinction is central to enterprise security because an unusual connection, traffic burst, authentication sequence, service request, or data-transfer pattern has limited security value unless the organization can determine whether it represents benign variation, misuse, denial of service, reconnaissance, privilege abuse, malware activity, or another attack class. Anomaly detection research has consequently examined statistical, classification-based, clustering-based, nearest-neighbor, information-theoretic, and machine-learning approaches for recognizing deviations in multidimensional data (Chandola et al., 2009). Network intrusion detection further combines traffic observation, feature extraction, behavioral analysis, and security decision rules to protect confidentiality, integrity, and availability across interconnected systems (Liao et al., 2013). From an international perspective, modern information and communication infrastructures connect enterprises, institutions, users, applications, cloud resources, and distributed services across geographical boundaries, making malicious network activity a security concern that is not limited to one organization or national environment. Network anomaly detection has accordingly been treated as an important component of information and communication technology security because anomalous traffic may represent a range of coordinated and technically heterogeneous attacks (Ahmed et al., 2016). In the present study, MIS-driven enterprise network security refers to an organizational security environment in which network-security information is captured, processed, classified, communicated, and used within management information structures to support security monitoring and operational decision processes. IDS effectiveness in such environments involves not simply recognizing malicious packets but organizing security information into actionable knowledge about network conditions and attack behavior (Khraisat et al., 2019).

Machine learning-enhanced intrusion detection represents a movement from fixed matching procedures toward data-driven discrimination between legitimate and malicious network behavior. Traditional signature-based IDSs are effective when recognizable attack patterns already exist in their rule bases, whereas anomaly-based systems attempt to model normality and identify deviations that may not correspond directly to predefined signatures. In Intrusion detection by machine learning: A review (pp. 11994-12000), machine-learning IDS approaches are organized around individual, hybrid, and ensemble learning strategies that classify network activity by extracting discriminative patterns from security data (Tsai et al., 2009). Random forests provided an important example of this data-driven orientation by using ensembles of decision trees to construct intrusion patterns automatically rather than requiring security administrators to encode every detection rule manually (Zhang et al., 2008). Hybrid models subsequently combined supervised misuse detection with unsupervised or clustering-oriented anomaly analysis so that known attack classes and unfamiliar traffic behaviors could be handled within a coordinated detection architecture (Elbasiony et al., 2013). Yet machine learning in operational intrusion detection is not equivalent to achieving high classification scores in a controlled experiment. In Outside the Closed World: On Using Machine Learning for Network Intrusion Detection

(pp. 305-316), the transfer of machine-learning techniques into real network environments is examined in relation to variability between training assumptions and operational traffic conditions, highlighting the difficulty of treating network security as an ordinary closed-world classification problem (Sommer & Paxson, 2010). The cyber-analytics literature has similarly shown that decision trees, support vector machines, Bayesian approaches, artificial neural networks, clustering methods, association rules, evolutionary computation, and ensemble techniques differ substantially in their data requirements, computational characteristics, and suitability for particular intrusion-detection problems (Buczak & Guven, 2016). Sequence-sensitive models have expanded this analytical capability because malicious activity frequently develops through related events rather than isolated network observations. Recurrent neural networks, for example, can model dependencies within traffic records and have been evaluated for multiclass intrusion recognition, providing a mechanism for distinguishing different attack categories rather than producing only a binary normal-versus-malicious judgment (Yin et al., 2017). Within the present research, Machine Learning-Based Intrusion Detection Capability (MLIDC) consequently represents the enterprise's perceived capacity to employ learned traffic patterns for accurate, timely, and adaptable recognition of malicious network behavior, including behavior that cannot be handled adequately through static signatures alone.

Intrusion detection becomes more analytically valuable when suspicious behavior can be classified, prioritized, and associated with meaningful security states. Intelligent anomaly classification concerns the ability of an analytical security system to differentiate abnormal observations according to characteristics such as attack form, behavioral pattern, severity, source characteristics, or operational risk. In A Deep Learning Approach to Network Intrusion Detection (pp. 41-50), representation learning is used to reduce dependence on extensive manual feature engineering and to provide a learned representation for distinguishing normal and intrusive network traffic (Shone et al., 2018). Deep-learning architectures have also been examined in distributed security environments in which large volumes of device and communication data create demands for scalable attack identification (Diro & Chilamkurti, 2018). A broader examination of machine learning and deep learning in cybersecurity identifies neural networks, support vector machines, decision trees, clustering, Bayesian techniques, and deep architectures as important analytical families used in intrusion and malicious-behavior recognition (Xin et al., 2018). The classification problem is particularly important because enterprise security personnel must distinguish among heterogeneous forms of malicious activity rather than treat all anomalous observations as equivalent events. Large-scale experimental comparisons of deep models across intrusion datasets have shown that network-level and host-level security classification involves differences in attack distribution, feature structure, model architecture, and dataset composition, all of which affect the resulting detection behavior (Vinayakumar et al., 2019). Feature quality is also inseparable from classifier effectiveness. Deep neural intrusion detection combined with filter-based feature engineering has been evaluated as a means of removing less informative attributes while preserving characteristics useful for attack discrimination (Kasongo & Sun, 2019). Research specifically examining deep-learning anomaly-based IDSs has further differentiated detection systems by input data, learning strategy, deployment structure, and evaluation method, showing that anomaly-based intrusion classification cannot be reduced to a single algorithmic procedure (Aldweesh et al., 2020). These findings provide the technical basis for separating Intelligent Anomaly Classification Capability (IACC) from basic intrusion recognition in this study. A system may identify an event as suspicious while still performing poorly in distinguishing attack classes, assigning security priority, minimizing misclassification, or translating anomalous patterns into operational categories. The research additionally treats Adaptive Threat Monitoring and Response (ATMR) as a distinct enterprise capability covering continuous observation, dynamic threat evaluation, rapid alert generation, prioritization, and security response associated with changing traffic behavior and detected anomalies.


The effectiveness of machine-learning intrusion detection also depends on the information environment in which analytical outputs are generated and consumed. Enterprise networks produce security-relevant information through packet flows, authentication services, endpoints, servers, applications, network devices, security appliances, access-control systems, and event logs. A management information system provides an organizational mechanism for transforming such distributed data into structured information used for monitoring, coordination, reporting, and decision

support. In this research, MIS-Security Data Integration (MSDI) specifically denotes the degree to which intrusion alerts, anomaly classifications, network events, threat information, and related cybersecurity data can be consolidated and made accessible through enterprise information processes rather than remaining isolated within independent technical tools. The quality of the underlying data is especially important for machine-learning security because classifiers learn the distinctions presented by their training observations. In A survey of network-based intrusion detection data sets (pp. 147-167), the suitability of intrusion datasets is examined through characteristics including data volume, recording environment, labeling, traffic properties, and other conditions that influence the validity of network-based IDS evaluation (Ring et al., 2019). The CICIDS2017-oriented work Toward Generating a New Intrusion Detection Dataset and Intrusion Traffic Characterization (pp. 108-116) similarly addresses limitations in older benchmark data by incorporating benign behavior and multiple contemporary attack types in a structured intrusion-detection dataset (Sharafaldin et al., 2018). Dataset selection remains important in deep-learning IDS research because different traffic sources, attack classes, feature representations, and network environments can produce materially different evaluation settings (Ferrag et al., 2020). Operational architecture also affects how security intelligence can be generated and accessed. DeepIDS, for example, evaluated deep neural and recurrent architectures for flow-based intrusion detection within software-defined networking while also examining throughput, latency, and resource utilization rather than classification accuracy alone (Tang et al., 2020). Reviews of machine-learning intrusion detection have continued to distinguish signature-based and anomaly-based detection while emphasizing the central role of classification techniques and benchmark datasets in determining how legitimate and malicious behavior is separated (Dina & Manivannan, 2021). Systematic examination of ML-based and deep-learning-based network IDS research likewise identifies detection accuracy, false alarms, novel attack recognition, dataset selection, and evaluation criteria as interconnected dimensions of NIDS performance (Ahmad et al., 2021). The dependent construct in this research, Enterprise Network Security Performance (ENSP), therefore encompasses perceived effectiveness in threat detection, security visibility, response efficiency, resilience, reduction of successful intrusions, continuity of network services, and quality of cybersecurity-related operational decisions.

A central research problem remains in connecting the technical capabilities of machine-learning intrusion detection with the broader organizational security performance of MIS-driven enterprise environments. A substantial portion of intrusion-detection research evaluates algorithms through accuracy, precision, recall, F1-score, detection rate, false-alarm rate, and related experimental metrics, while enterprise security depends simultaneously on whether detected information is correctly classified, integrated with organizational information systems, monitored continuously, and translated into coordinated responses. Earlier flow-based research in software-defined environments demonstrated that deep models could operate on selected network features for anomaly detection, reinforcing the importance of relating learned traffic representations to network-level security monitoring rather than examining algorithms in abstraction (Tang et al., 2016). More recent surveys of artificial-intelligence-based NIDS research identify false alarms, zero-day recognition, dataset age, attack diversity, and methodological differences among AI-based detection architectures as recurring factors affecting the assessment of intelligent IDSs (Habeeb & Babu, 2022). A systematic review of 119 highly cited anomaly-based network intrusion detection studies likewise demonstrates that application domain, preprocessing, attack-detection method, evaluation metrics, and dataset characteristics constitute interconnected dimensions of anomaly-oriented security research (Yang et al., 2022). Research on machine learning for intrusion detection in industrial control environments further differentiates supervised, unsupervised, semi-supervised, and reinforcement-learning approaches and shows that intrusion identification can draw simultaneously on network-level observations and behavioral or process-level anomaly information (Umer et al., 2022). These streams of literature establish a specific empirical space for examining enterprise cybersecurity as a coordinated set of capabilities rather than as the output of one classifier. The present study accordingly concentrates on four analytically distinct predictors, Machine Learning-Based Intrusion Detection Capability (MLIDC), Intelligent Anomaly Classification Capability (IACC), MIS-Security Data Integration (MSDI), and Adaptive Threat Monitoring and Response (ATMR), in relation to Enterprise Network Security

Performance (ENSP). The research problem is framed around whether variations in these capabilities are statistically associated with variations in enterprise network-security performance and whether their individual and combined effects can be identified within a quantitative, cross-sectional, case-study-based enterprise setting using structured five-point Likert measurement, correlation analysis, and regression modeling.

Figure 1: Integrated Overview of Machine Learning-Enhanced MIS-Driven Enterprise Network Security



Enterprise networks have become central infrastructures through which organizations coordinate information, applications, communication, financial transactions, operational processes, customer services, and managerial decision-making. As organizational activities increasingly depend on interconnected digital systems, maintaining the confidentiality, integrity, availability, and reliability of network resources has become a fundamental requirement of enterprise information management. Traditional network-security mechanisms have primarily relied on predefined signatures, static access controls, manually constructed rules, and threshold-based monitoring procedures to identify malicious activity. Such mechanisms remain useful for detecting recognizable attacks, but their effectiveness is constrained when network behavior becomes highly dynamic, attack patterns change rapidly, or malicious activities resemble legitimate traffic. Enterprise networks continuously generate large volumes of security-related information through user authentication, application access, endpoints, servers, databases, routers, firewalls, cloud environments, and other interconnected resources. Processing such information manually or through fixed detection rules can make timely identification of sophisticated threats difficult. Machine learning has therefore become increasingly relevant to intrusion detection because it enables security systems to learn patterns from historical and operational data, distinguish normal from abnormal activities, and classify potentially malicious behavior according to identifiable characteristics. Machine learning-based intrusion detection can support the recognition of complex traffic patterns, while intelligent anomaly classification can differentiate suspicious activities according to attack type, severity, behavioral characteristics, or potential risk. However, enterprise cybersecurity performance also depends on how effectively security information is integrated with broader management information systems. Security alerts that remain fragmented across independent technical platforms may provide limited organizational visibility unless they are consolidated, interpreted, and made accessible for security monitoring and decision-making. MIS-security data integration therefore provides an organizational information-processing mechanism through which intrusion alerts, anomaly classifications, threat information, and operational security data can be transformed into coordinated security intelligence. Adaptive threat monitoring and response further extends this capability by enabling continuous observation, dynamic prioritization, rapid alerting, and responsive action when abnormal network conditions are identified. Against this

background, the present study examines Machine Learning-Based Intrusion Detection Capability, Intelligent Anomaly Classification Capability, MIS-Security Data Integration, and Adaptive Threat Monitoring and Response as interconnected enterprise capabilities associated with Enterprise Network Security Performance.

Problem Statement

Enterprise organizations face a persistent security problem arising from the increasing complexity of network environments and the limitations of conventional intrusion-detection mechanisms in identifying diverse, previously unseen, and behaviorally complex attacks. Traditional signature-based systems depend heavily on previously recognized attack patterns and predefined security rules, which can reduce their effectiveness when malicious activities do not match stored signatures or when attackers deliberately modify observable characteristics to avoid detection. At the same time, anomaly-oriented systems may generate large numbers of alerts without providing sufficiently accurate classification, prioritization, or contextual interpretation. This creates an operational difficulty in which security teams are required to distinguish meaningful threats from normal network variations while managing false positives, false negatives, alert overload, and time-sensitive security incidents. Another problem exists at the organizational information level. Intrusion alerts, network logs, threat intelligence, system events, and anomaly classifications may be generated by different security tools but remain fragmented across technical platforms. When these data are not effectively integrated into management information processes, organizations may experience reduced security visibility and slower coordination between technical detection and managerial response. The growing use of machine learning provides opportunities for improving intrusion detection and anomaly classification, yet many existing studies concentrate primarily on algorithmic accuracy, benchmark datasets, or comparisons among classifiers. Such evaluations do not fully explain how machine learning-based detection capabilities operate within MIS-driven enterprise environments or how security-data integration and adaptive monitoring contribute to broader network-security performance. There is therefore a need to examine enterprise cybersecurity as a combination of technical detection capability, intelligent anomaly classification, integrated security information, and adaptive response capacity. This study addresses that problem by statistically examining how Machine Learning-Based Intrusion Detection Capability, Intelligent Anomaly Classification Capability, MIS-Security Data Integration, and Adaptive Threat Monitoring and Response are associated with Enterprise Network Security Performance within a quantitative, cross-sectional, case-study-based research setting.

Purpose

The primary purpose of this study is to empirically examine how machine learning-enhanced intrusion detection and anomaly classification contribute to the security performance of MIS-driven enterprise networks when they operate together with integrated security information and adaptive threat-management capabilities. The study is designed around four independent constructs, namely Machine Learning-Based Intrusion Detection Capability, Intelligent Anomaly Classification Capability, MIS-Security Data Integration, and Adaptive Threat Monitoring and Response, with Enterprise Network Security Performance serving as the dependent construct. The first objective is to determine whether Machine Learning-Based Intrusion Detection Capability significantly influences Enterprise Network Security Performance by examining the extent to which learned traffic patterns, automated recognition, detection accuracy, and identification of suspicious network behavior contribute to enterprise security outcomes. The second objective is to evaluate the influence of Intelligent Anomaly Classification Capability on Enterprise Network Security Performance, with particular attention to the ability to differentiate anomalous events, categorize attack behavior, reduce misclassification, and prioritize identified threats. The third objective is to assess whether MIS-Security Data Integration significantly affects Enterprise Network Security Performance by examining the organizational integration of security alerts, network information, threat data, and decision-support processes. The fourth objective is to investigate the influence of Adaptive Threat Monitoring and Response on Enterprise Network Security Performance through continuous monitoring, dynamic threat evaluation, rapid alert generation, prioritization, and timely security action. The fifth objective is to determine the collective explanatory and predictive contribution of the four independent variables to Enterprise Network Security Performance through multiple regression modeling. These objectives have been examined

through a positivist and deductive quantitative research approach using a cross-sectional explanatory case-study survey, purposive sampling of relevant enterprise IT and cybersecurity professionals, structured five-point Likert-scale measurement, descriptive statistics, Pearson correlation analysis, and multiple linear regression.

Research Questions

RQ1: What relationship exists between Machine Learning-Based Intrusion Detection Capability and Enterprise Network Security Performance?

RQ2: How does Intelligent Anomaly Classification Capability influence Enterprise Network Security Performance?

RQ3: What effect does MIS-Security Data Integration have on Enterprise Network Security Performance?

RQ4: How does Adaptive Threat Monitoring and Response influence Enterprise Network Security Performance?

RQ5: To what extent do MLIDC, IACC, MSDI, and ATMR collectively predict Enterprise Network Security Performance?

Research Hypotheses

The hypotheses of this study have been developed to statistically test the proposed relationships between the four enterprise cybersecurity capabilities and Enterprise Network Security Performance. The first hypothesis, H1, states that Machine Learning-Based Intrusion Detection Capability has a significant positive effect on Enterprise Network Security Performance. This hypothesis reflects the expectation that stronger capability to identify malicious network activity through learned behavioral and traffic patterns will correspond with stronger security outcomes. The second hypothesis, H2, states that Intelligent Anomaly Classification Capability has a significant positive effect on Enterprise Network Security Performance. This proposition focuses on the ability of an enterprise security environment to distinguish anomalous activities accurately, differentiate attack categories, recognize varying levels of threat severity, and reduce security-event misclassification. The third hypothesis, H3, states that MIS-Security Data Integration has a significant positive effect on Enterprise Network Security Performance. This hypothesis addresses whether the effective integration of intrusion alerts, network events, threat information, and other cybersecurity data into organizational information systems strengthens security visibility and coordinated security management. The fourth hypothesis, H4, states that Adaptive Threat Monitoring and Response has a significant positive effect on Enterprise Network Security Performance. This relationship examines whether continuous network observation, dynamic security assessment, rapid threat prioritization, and responsive security actions are associated with improved enterprise network protection. The fifth hypothesis, H5, states that Machine Learning-Based Intrusion Detection Capability, Intelligent Anomaly Classification Capability, MIS-Security Data Integration, and Adaptive Threat Monitoring and Response jointly have a significant effect on Enterprise Network Security Performance. H5 therefore evaluates the overall explanatory power of the proposed research model by determining whether the four capabilities collectively account for statistically significant variation in enterprise network-security performance.

Significance of the Research

i. Significance to Enterprise Cybersecurity Management: The study provides an empirically structured examination of enterprise cybersecurity that goes beyond evaluating intrusion-detection algorithms in isolation. By examining detection, classification, information integration, and adaptive response together, the study provides a clearer representation of how multiple security capabilities operate within an enterprise environment.

ii. Significance to Management Information Systems: The research connects cybersecurity analytics with MIS by treating security information as an organizational information resource that must be processed, integrated, communicated, and transformed into decision-relevant intelligence. This perspective strengthens the relationship between technical network protection and enterprise information management.

iii. Significance to Security Operations and IT Professionals: The findings provide evidence concerning which of the proposed capabilities has the strongest statistical relationship with Enterprise Network Security Performance. Such evidence can support cybersecurity analysts, network administrators, SOC

professionals, information-security officers, and IT managers in understanding the relative roles of intrusion detection, anomaly classification, information integration, and adaptive monitoring.

iv. Significance to Machine Learning-Based Security Research: The study shifts attention from algorithmic performance alone toward organizationally measured cybersecurity capability. This creates a quantitative basis for examining how machine-learning-enabled detection operates within broader enterprise security systems rather than only within benchmark classification environments.

v. Significance to Cybersecurity Decision Support: By examining MIS-Security Data Integration, the study addresses the transformation of technical security events into information that can support monitoring, prioritization, coordination, and decision-making. This strengthens the analytical connection between detection outputs and enterprise-level security management.

vi. Significance to Academic Research: The proposed model provides an empirically testable structure linking MLIDC, IACC, MSDI, and ATMR with ENSP. The use of descriptive statistics, Pearson correlation, and multiple regression provides measurable evidence concerning both individual relationships and the combined predictive contribution of the four independent variables.

Paper Organization

The paper has been organized into eight major sections. The Introduction has established the background, problem, objectives, research questions, hypotheses, and significance of the study. The Literature Review has synthesized research on machine learning-based intrusion detection, intelligent anomaly classification, MIS-security integration, adaptive monitoring, Organizational Information Processing Theory, and the conceptual framework. The Methodology has described the quantitative, cross-sectional, explanatory case-study survey and statistical procedures. The Results section has presented respondent characteristics, data screening, measurement quality, descriptive statistics, correlations, regression modeling, diagnostics, and hypothesis testing. The Discussion has compared the findings with prior research and examined practical, theoretical, and future-research considerations. The final sections have presented the Conclusion, Recommendations, Limitations of the Study, and References.

LITERATURE REVIEW

The literature surrounding machine learning-enhanced intrusion detection has developed across several closely related areas, including network anomaly detection, intelligent attack classification, cybersecurity analytics, enterprise information integration, adaptive monitoring, and organizational security performance. Intrusion detection research has traditionally distinguished between signature-based systems, which identify previously recognized attack patterns, and anomaly-based systems, which detect deviations from established representations of normal network behavior. The increasing volume and complexity of enterprise network traffic have expanded the use of machine-learning techniques because such approaches can identify multidimensional relationships in security data that may not be efficiently represented through static detection rules. Supervised learning techniques have been widely examined for classifying previously labeled attack behaviors, while unsupervised and semi-supervised methods have been investigated for detecting unusual patterns when complete attack labels are unavailable. Deep learning has further expanded this literature by enabling automated representation learning from complex network data. However, effective enterprise network security requires more than the initial identification of suspicious behavior. Security systems must also classify anomalies meaningfully, reduce false alerts, distinguish among attack categories, prioritize threats, and provide sufficiently interpretable information for operational response. This requirement creates a direct connection between intelligent anomaly classification and broader enterprise security management. At the organizational level, network alerts and cybersecurity events must be integrated with information systems that support visibility, coordination, reporting, and decision-making. MIS-Security Data Integration therefore represents an important bridge between technical security analytics and organizational information processing. Adaptive Threat Monitoring and Response adds another dimension by emphasizing continuous observation, dynamic assessment, and timely reaction to changing network conditions. The literature review consequently examines Machine Learning-Based Intrusion Detection Capability, Intelligent Anomaly Classification Capability, MIS-Security Data Integration, Adaptive Threat Monitoring and Response, and Enterprise Network Security Performance as conceptually related components of the proposed research model. It also establishes Organizational

Information Processing Theory as the theoretical foundation and develops the conceptual relationships through which the hypotheses of the study are specified.


Machine Learning-Based Intrusion Detection in Enterprise Networks

Machine learning-based intrusion detection has become an important analytical component of enterprise network security because conventional security mechanisms often depend on predefined attack signatures, manually specified rules, or fixed thresholds that can be insufficient when malicious activities exhibit changing behavioral characteristics. In enterprise networks, intrusion detection requires continuous examination of traffic attributes, communication patterns, access behavior, protocol characteristics, and system events to determine whether observed activities correspond to legitimate operations or possible security violations. Machine learning contributes to this process by constructing classification or detection models from historical observations and subsequently applying learned relationships to incoming network data. Such capability is particularly relevant to Management Information System environments where network activities originate from interconnected databases, business applications, servers, workstations, communication platforms, cloud services, and user-access mechanisms. In Feature deduction and ensemble design of intrusion detection systems (pp. 295-307), feature selection was examined through Bayesian networks and Classification and Regression Trees, demonstrating that eliminating redundant or minimally informative attributes can improve computational efficiency while retaining information required for effective intrusion discrimination (Ashik & Shabbir, 2022; Chebrolu et al., 2005). This finding is important because enterprise intrusion-detection systems frequently process high-dimensional security data in which not every recorded attribute contributes equally to identifying attacks. A machine-learning-based IDS therefore involves more than selecting a classifier; it requires appropriate data representation, relevant feature identification, preprocessing, and reliable discrimination between normal and intrusive behavior. In Modeling intrusion detection system using hybrid intelligent systems (pp. 114-132), decision trees and support vector machines were combined through hierarchical and ensemble configurations to improve intrusion-detection accuracy while controlling computational complexity (Hasan & Adnan, 2022; Peddabachigari et al., 2007). Such hybridization reflects the heterogeneous nature of enterprise network threats because individual learning algorithms may perform differently across attack categories, traffic distributions, and feature structures. Machine Learning-Based Intrusion Detection Capability in the present research therefore represents an organizational capability to use learned network patterns, appropriate features, intelligent classification mechanisms, and computationally efficient analytical procedures for identifying malicious activity across enterprise information infrastructures.

The reliability of machine learning-based intrusion detection is also strongly influenced by the data used to develop and evaluate detection models. A classifier trained on outdated, repetitive, or poorly representative network observations may report strong experimental accuracy while performing less effectively when exposed to complex enterprise traffic. Modern enterprise networks contain diverse application protocols, user activities, encrypted communications, automated processes, external connections, and rapidly changing traffic distributions, making representative training and evaluation data particularly important. In The evaluation of Network Anomaly Detection Systems (pp. 18-31), the UNSW-NB15 dataset was statistically examined against the older KDD99 dataset, with the analysis emphasizing contemporary normal traffic, multiple modern attack categories, feature correlations, and variation between training and testing observations (Mahbubul et al., 2022; Moustafa & Slay, 2016). This dataset-oriented perspective demonstrates that intrusion-detection performance cannot be interpreted independently of the environment represented by the data. Enterprise machine-learning security systems must learn distinctions that are meaningful within operational conditions rather than merely reproduce patterns present in historical benchmark records. The quality of the learning environment also affects false alarms, missed attacks, and the ability to discriminate among attack behaviors with different statistical characteristics. Supervised approaches can be effective when sufficiently labeled normal and malicious observations are available, whereas semi-supervised and unsupervised approaches become relevant when complete attack labeling is impractical. At the enterprise level, these learning mechanisms may process network-flow characteristics, protocol behavior, connection duration, service information, packet statistics, authentication activity, and interaction patterns to construct decision boundaries between legitimate and suspicious activities.

Machine learning also allows intrusion-detection systems to evaluate multidimensional combinations of characteristics that might not be detectable through isolated threshold rules. This capacity is particularly significant for MIS-driven security because intrusion alerts are not merely technical outputs. They become organizational information that can be combined with asset information, access records, operational context, incident histories, and security-management processes. Consequently, the effectiveness of ML-based intrusion detection depends upon the interaction among representative data, feature quality, classifier structure, attack diversity, and the information environment in which detected events are interpreted and managed.

Figure 2: Machine Learning-Based Intrusion Detection Capability Framework



The development of machine-learning intrusion detection has increasingly emphasized hybrid classification, dimensionality reduction, computational efficiency, and the capacity to recognize heterogeneous attack patterns within large network datasets. Enterprise security systems must process normal activities and multiple categories of malicious behavior without producing excessive false alarms that can overwhelm security personnel. This requirement makes model architecture particularly important because a single classifier may not adequately represent all relationships contained within complex security observations. In Multi-level hybrid support vector machine and extreme learning machine based on modified K-means for intrusion detection system (pp. 296-303), a modified K-means procedure was used to construct representative training data for support vector machine and extreme learning machine classifiers, while a multilevel architecture was designed to strengthen discrimination between normal activity and different attack classes (Al-Yaseen et al., 2017; Mashfiqur & Md, 2022). The study illustrates how clustering and supervised learning can be coordinated to reduce training requirements while retaining classification capability, which is relevant to enterprise environments where large traffic volumes can increase processing burdens. Another central issue is dimensionality because network-security datasets may contain numerous correlated, redundant, or weakly informative variables that increase model complexity without proportionately improving detection. In Dimensionality reduction with IG-PCA and ensemble classifier for network intrusion detection (pp. 164-175), information gain and principal component analysis were integrated with an ensemble incorporating support vector machine, instance-based learning, and multilayer perceptron techniques to reduce feature dimensionality and strengthen attack recognition across multiple intrusion datasets (Ashfaq & Mohammad, 2022; Salo et al., 2019). These approaches establish machine-learning intrusion

detection as a coordinated analytical process involving feature engineering, dimensionality management, model selection, classifier integration, and evaluation of detection and false-alarm behavior. For the present study, Machine Learning-Based Intrusion Detection Capability therefore refers to the extent to which an enterprise can employ intelligent learning mechanisms to identify malicious network behavior accurately, distinguish relevant security patterns from routine traffic, process complex network information efficiently, and generate reliable intrusion information for organizational security management. This definition positions MLIDC as a measurable enterprise security capability rather than treating machine learning solely as an isolated algorithmic experiment.


Intelligent Anomaly Classification and Adaptive Threat Monitoring

Intelligent anomaly classification extends intrusion detection beyond binary recognition of normal and abnormal activity by assigning detected deviations to categories supporting security prioritization, investigation, and response. Within enterprise networks, anomalous behavior may represent denial-of-service activity, probing, privilege escalation, malicious authentication attempts, data exfiltration, malware communication, or benign operational variation. Classification therefore depends on the quality of network representation and on the ability of analytical models to distinguish between classes that may overlap statistically. In A Detailed Analysis of the KDD CUP 99 Data Set (pp. 1-6), extensive redundancy and class imbalance were identified in the KDD Cup 99 benchmark, and the NSL-KDD dataset was proposed to provide a more balanced basis for assessing anomaly-detection algorithms and differentiating attack categories (Sadia & Mostari, 2022; Tavallaee et al., 2009). This observation is relevant to intelligent anomaly classification because a model can appear highly accurate when dominant traffic classes overwhelm rare attack categories while still performing poorly on unusual events that security teams need to recognize. Effective classification therefore requires attention to class distribution, representative training observations, feature relevance, and evaluation across multiple attack types rather than reliance on aggregate accuracy alone. In enterprise settings, these requirements are amplified by traffic heterogeneity, changing user behavior, different application protocols, and the coexistence of routine and security-sensitive activities. In Intrusion Detection System Using Deep Neural Network for In-Vehicle Network Security, probability-based feature vectors were used with a deep neural network to discriminate normal and attack packets and support rapid classification under real-time conditions, demonstrating how learned probability distributions can transform communication events into class-based security judgments (Kang & Kang, 2016; Shaiful et al., 2022). Intelligent Anomaly Classification Capability in this study therefore refers to the organizational capacity to identify abnormal traffic and assign detected events to useful threat categories with sufficient accuracy, consistency, and speed to support enterprise cybersecurity operations.

Adaptive threat monitoring extends anomaly classification by requiring security systems to maintain useful detection performance when traffic patterns, attack strategies, system states, and operational contexts change. Static models may classify known patterns accurately but become less reliable when attackers alter observable features or when legitimate network behavior evolves with new applications, services, users, and infrastructure. Adaptive monitoring therefore requires flexible mechanisms that can revise decision boundaries, update behavioral representations, prioritize anomalies, and preserve sensitivity to low-frequency or previously unseen threats. In Deep Learning-Based Intrusion Detection With Adversaries (pp. 38367-38384), deep neural intrusion-detection models were shown to be vulnerable to adversarially modified inputs capable of inducing misclassification, illustrating that strong baseline classification performance does not automatically guarantee robust monitoring when hostile actors intentionally manipulate observable features (Stabak & Shahid, 2022; Wang, 2018). This issue is significant for MIS-driven enterprise environments because security information must remain dependable enough to support operational decisions, escalation procedures, and incident handling. Adaptive capability thus includes not only detection accuracy but also resilience to changes in attack presentation, assessment of model behavior, and the ability to revise knowledge when existing representations become less reliable. In Adaptive Intrusion Detection via GA-GOGMM-Based Pattern Learning with Fuzzy Rough Set-Based Attribute Selection, fuzzy rough set-based feature selection, Gaussian-mixture pattern learning, and an online model-updating mechanism were integrated to maintain intrusion recognition under dynamically changing network conditions, with the updating process designed to revise normal and intrusion pattern libraries as new traffic information became

available (Mohammad, 2023; Liu et al., 2020). This approach illustrates the relationship between classification and adaptation: classification organizes observed behavior into interpretable security patterns, while adaptation ensures that those patterns remain aligned with the network environment. For enterprise security operations, adaptive threat monitoring involves continuous observation, reassessment of suspicious behavior, dynamic alert prioritization, and adjustment of detection logic in response to new conditions.

Figure 3: Intelligent Anomaly Classification and Adaptive Threat Monitoring Framework




The integration of intelligent classification with adaptive monitoring is important when enterprise networks are distributed across systems, services, endpoints, and domains. A centralized detector may receive many alerts but limited operational value if it cannot determine which anomalies are significant, how events relate to one another, or how monitoring priorities should change as threats evolve. Adaptive Threat Monitoring and Response therefore requires architecture in which observations are evaluated continuously, relevant features receive attention, attack categories are distinguished, and response decisions are linked to the changing security state of the network. In Attention Based Multi-Agent Intrusion Detection Systems Using Reinforcement Learning, a distributed intrusion-detection architecture combined multiple agents, deep Q-network reinforcement learning, and attention mechanisms to identify and classify advanced attacks while adapting to heterogeneous and previously unseen network behaviors (Adnan & Iftekhar, 2023; Sethi et al., 2021). This approach treats intrusion detection as an interactive decision process rather than a fixed mapping between inputs and labels. Reinforcement learning allows detection agents to improve security decisions through feedback, while attention mechanisms can emphasize information relevant to a security state. For MIS-driven enterprise networks, this logic supports the need to convert technical observations into prioritized information supporting coordinated operational action. Intelligent anomaly classification contributes categorical understanding of detected events, whereas adaptive monitoring contributes temporal awareness, continuous reassessment, and responsiveness to changing conditions. This research treats Intelligent Anomaly Classification Capability and Adaptive Threat Monitoring and Response as separate but complementary constructs. IACC captures the enterprise's ability to distinguish abnormal behavior, assign attack categories, reduce misclassification, and prioritize anomalies according to security relevance. ATMR captures the capacity to continuously observe the network, update threat assessments, generate alerts, adjust monitoring behavior, and initiate responses as conditions change. Together, these capabilities provide an analytical basis for examining whether intelligent interpretation and adaptive monitoring correspond with stronger Enterprise Network Security Performance.

MIS-Security Data Integration and Enterprise Network Security Performance

MIS-Security Data Integration refers to the organizational capacity to consolidate, normalize, correlate, distribute, and interpret cybersecurity information generated across heterogeneous technical and managerial systems so that network events can be transformed into usable security intelligence. In an enterprise environment, relevant data may originate from intrusion detection systems, firewalls,

authentication services, endpoint protection tools, servers, databases, cloud platforms, applications, access-control systems, and threat-intelligence feeds. When such information remains separated across individual tools, security personnel may receive fragmented alerts that provide only partial representations of a developing incident. Integration therefore requires a common information-processing structure through which events from different sources can be standardized, related, and presented in a form suitable for operational monitoring and managerial decision-making. In The Operational Role of Security Information and Event Management Systems (pp. 35-41), Security Information and Event Management platforms are described as mechanisms that collect security events from diverse enterprise sources, normalize them into common formats, store them for analysis, and correlate them to identify potentially malicious activities in real time (Bhatt et al., 2014; Rahman, 2023). This architecture is especially relevant to MIS-driven enterprise security because it connects distributed technical observations with a centralized information environment in which analysts can evaluate relationships among events rather than interpret isolated alerts. In Towards a System for Complex Analysis of Security Events in Large-Scale Networks (pp. 16-34), heterogeneous event normalization, in-memory processing, misuse detection, query-based analytics, and anomaly detection were combined to address high event volumes, false positives, and lengthy analysis processes in large networks (Sheak & Tahmedur, 2023; Sapegin et al., 2017). Accordingly, MSDI in the present study encompasses the extent to which security-related data are consolidated across enterprise systems, made interoperable, correlated across sources, and converted into timely information that supports network-security awareness, incident interpretation, and coordinated cybersecurity management. It also preserves relationships among alerts, assets, users, and network activities securely.

Figure 4: MIS-Security Data Integration and Enterprise Network Security Performance Framework



Effective integration is not limited to technically combining security logs because enterprise cybersecurity also depends on the ability to prioritize information according to operational relevance. Large organizations may generate thousands or millions of daily network events, many of which represent routine activity or low-risk deviations. An integrated MIS-security environment must therefore support filtering, enrichment, prioritization, and contextualization so that analysts and managers can identify events requiring immediate attention. Security analytics can strengthen this process by combining machine-learning outputs with enterprise log repositories, external threat intelligence, host information, and historical incident evidence. In MADE: Security Analytics for Enterprise Threat Detection (pp. 124-136), enterprise security logs were used to construct machine-learning features for identifying and prioritizing risky external domains, and the system was deployed with security operations center analysts in a large enterprise environment (Kaium, 2023; Oprea et al., 2018). The study demonstrates that enterprise security value is generated not simply by producing additional alerts, but by organizing data in a manner that directs analytical attention toward activities with greater security relevance. Information integration also involves movement of cybersecurity knowledge between organizational actors and across institutional boundaries. In Information Sharing

in Cybersecurity: A Review (pp. 172-196), cybersecurity information sharing was examined in relation to actors, information types, policies, architectures, benefits, barriers, privacy concerns, liability, investment, and incentive mechanisms, illustrating that the usefulness of security information depends partly on the structures through which it can be exchanged and consumed (Pervaz, 2023; Pala & Zhuang, 2019). Within an MIS-driven enterprise, these principles apply internally when security operations, network administration, risk management, information technology management, and organizational decision makers require access to consistent threat information. MSDI therefore reflects both technological integration and information accessibility, enabling cybersecurity data to move from detection systems into coordinated organizational processes without losing contextual meaning, timeliness, or decision relevance. This strengthens coordinated incident interpretation.


The relationship between MIS-Security Data Integration and Enterprise Network Security Performance becomes particularly important when security performance is understood as an organizational outcome rather than only a classifier accuracy measure. Enterprise Network Security Performance includes the effectiveness with which an organization detects threats, maintains security visibility, coordinates incident handling, supports timely responses, reduces successful intrusions, protects service continuity, and provides reliable information for cybersecurity decisions. These outcomes depend partly on whether relevant knowledge is visible to the people and systems responsible for protection. Fragmented security infrastructures can create duplicated alerts, inconsistent interpretations, delayed escalation, and gaps between technical detection and managerial awareness. Integrated information structures can reduce these coordination problems by providing shared security data, clearer event relationships, and more consistent situational awareness across enterprise functions. In The Impact of Organizational Practices on the Information Security Management Performance, empirical evidence from employees of UK manufacturing small and medium-sized enterprises showed that security knowledge sharing, security education, training, and security visibility significantly influenced information security management performance, emphasizing that organizational information processes accompany technological controls in shaping security outcomes (Alzahrani & Seth, 2021; Badrul & Mominul, 2023). This evidence is closely aligned with the present research because MIS-Security Data Integration is conceptualized as a capability that connects machine-learning intrusion detection and intelligent anomaly classification with enterprise-level visibility and coordinated action. When ML-based systems identify suspicious behavior, the resulting information must be accessible, understandable, and linked with other relevant security records before it can fully support enterprise response. MSDI therefore represents the information-processing bridge between analytical detection technologies and Enterprise Network Security Performance. Its measurement in this study focuses on integration of security data, cross-system accessibility, centralized visibility, information sharing, dashboard-supported monitoring, and the availability of cybersecurity information for operational and managerial decision processes. This information structure directly supports coordinated enterprise security management.

ML-Based Security Capabilities and Enterprise Network Security Performance

The empirical relationship between machine learning-enabled security capabilities and enterprise network security performance begins with the capacity of an intrusion detection system to transform large volumes of network traffic into timely and accurate security judgments. In enterprise environments, MLIDC is valuable when learned models improve attack recognition while controlling false positives and detection latency, because these operational characteristics determine whether suspicious activity can be identified before it disrupts services or compromises information assets. In An intrusion detection system using network traffic profiling and online sequential extreme learning machine (pp. 8609-8624), network traffic profiling, feature selection, and online sequential extreme learning were evaluated on the NSL-KDD and Kyoto benchmark datasets; the reported results combined high classification accuracy with comparatively low false-positive rates and short detection times, showing that efficient learning architecture can improve both analytical and operational intrusion-detection performance (Rakib & Towhidul, 2023; Singh et al., 2015). This evidence supports the proposed positive relationship between Machine Learning-Based Intrusion Detection Capability and Enterprise Network Security Performance because network protection depends not only on identifying attacks but also on processing security-relevant observations quickly enough for

operational use. The relationship also extends from initial detection to the management of alerts generated by security systems. In Intrusion detection alert management for high-speed networks: Current researches and applications (pp. 4362-4372), an online adaptive support vector machine classifier was tested across multiple intrusion datasets to reduce the burden created by large alert volumes and false positives while maintaining a workable balance between classification accuracy and processing time (Kanti, 2023; Sallay & Bourouis, 2015). Such evidence links Intelligent Anomaly Classification Capability with ENSP because security teams require categorized, filtered, and prioritized alerts rather than undifferentiated volumes of anomalous events. In MIS-driven enterprises, this relationship becomes organizationally important when classification outputs are incorporated into monitoring processes, dashboards, incident records, and decision-support activities that determine how rapidly a detected event is escalated and managed.

Figure 5: Coordinated Cybersecurity Capability Cycle Supporting Enterprise Network Security Performance



Enterprise network security performance is also affected by whether intrusion-detection and anomaly-classification mechanisms can continue operating effectively under heavy traffic and changing attack conditions. High detection accuracy has limited organizational value when an IDS cannot analyze packets at enterprise network speed, drops traffic during congestion, or fails to adjust when malicious behavior changes. In Improving network intrusion detection system performance through quality of service configuration and parallel technology (pp. 981-999), experiments with a Snort-based network intrusion detection and protection environment showed that high-speed network conditions can create packet-processing limitations, while quality-of-service configuration and parallel processing can improve analysis capacity and reduce packet loss during security inspection (Bul'ajoul et al., 2015; Nishat, 2023). The findings provide empirical support for treating Enterprise Network Security Performance as a multidimensional outcome that includes detection effectiveness, processing capacity, service continuity, security visibility, and the operational reliability of protective mechanisms. Adaptive capability adds another layer to this relationship because enterprise attack behavior is not static. In A context-aware robust intrusion detection system: A reinforcement learning-based approach (pp. 657-678), a context-aware intrusion detection architecture based on deep reinforcement learning was evaluated for recognizing complex and changing attack patterns, with the model designed to adapt detection behavior according to environmental context and newly observed security conditions (Risha

& Shurovi, 2023; Sethi et al., 2020). This evidence is directly relevant to Adaptive Threat Monitoring and Response because continuous security performance requires more than a fixed model trained once on historical observations. ATMR represents the organizational capability to observe network conditions continuously, reassess threat states, update analytical responses, and support timely defensive action when attack characteristics vary. When MLIDC identifies suspicious activity, IACC assigns meaningful security categories, and ATMR continuously reassesses emerging conditions, the combined process provides a stronger basis for maintaining reliable network-security operations than any single capability used independently.


The empirical relationship between security capabilities and enterprise performance also depends on how technical controls are aligned with organizational information processes. Machine-learning detection and anomaly classification produce security information, but enterprise security performance is shaped by whether this information becomes visible, interpretable, and usable within management structures. MIS-Security Data Integration therefore provides the connecting mechanism through which technical alerts, asset information, access records, threat indicators, incident histories, and managerial security requirements can be combined into a shared operational picture. In Strategic value alignment for information security management: A critical success factor analysis (pp. 150-170), survey data from 219 managers involved in organizational information-security decision-making were analyzed through partial least squares structural equation modeling, and the findings indicated that business alignment, management support, awareness of security risks, and effective security controls were important antecedents of successful information security management performance (Stabak & Siam, 2023; Tu et al., 2018). This organizational evidence complements the technical intrusion-detection studies by showing that security performance is not produced by analytical accuracy alone. For the present research, MSDI captures the extent to which machine-learning alerts and anomaly classifications are integrated with enterprise information systems, shared among relevant functions, displayed through centralized monitoring structures, and connected with decision processes. The empirical relationships proposed in this study therefore operate as a coordinated chain of security capability: MLIDC contributes detection intelligence, IACC converts abnormal observations into meaningful classifications, MSDI places these outputs within an organizational information environment, and ATMR supports continuous reassessment and response. ENSP reflects the resulting level of threat visibility, detection effectiveness, response efficiency, network resilience, continuity, and security decision quality. This structure also justifies testing both individual and combined relationships statistically. Pearson correlation can identify the direction and strength of association between each security capability and ENSP, while multiple regression can determine the unique predictive contribution of MLIDC, IACC, MSDI, and ATMR when the other predictors are controlled within the same explanatory model.

Theoretical Framework

Organizational Information Processing Theory (OIPT) provides an appropriate theoretical foundation for explaining how enterprises convert complex cybersecurity data into coordinated security action. The theory treats organizations as information-processing systems whose effectiveness depends on the fit between the amount of uncertainty generated by the environment and the organization's capacity to acquire, interpret, distribute, and use information. Enterprise network security presents exactly this type of information-processing problem because security teams must interpret high-volume, heterogeneous, and time-sensitive data generated by traffic flows, authentication events, applications, endpoints, cloud services, intrusion alerts, and threat intelligence. When uncertainty increases, organizations require stronger information-processing mechanisms rather than relying solely on static routines. In Leveraging Supply Chain Integration through Planning Comprehensiveness (pp. 823-861), OIPT was used to show that integration and technology-enabled information systems can increase planning comprehensiveness and operational performance by improving how organizations exploit available information (Srinivasan & Swink, 2015; Feroz, 2023). Although that study examined supply-chain operations, its theoretical logic is transferable to cybersecurity because security performance similarly depends on whether dispersed information is integrated and converted into coordinated decisions. In the present research, Machine Learning-Based Intrusion Detection Capability (MLIDC) increases information acquisition and analytical processing by recognizing suspicious traffic patterns;

Intelligent Anomaly Classification Capability (IACC) converts raw anomalies into meaningful threat categories; MIS-Security Data Integration (MSDI) increases the accessibility and consistency of security information across organizational systems; and Adaptive Threat Monitoring and Response (ATMR) enables continuous reassessment and action as security conditions change. OIPT therefore explains why these four capabilities can be treated as complementary mechanisms that increase an enterprise's information-processing capacity and reduce uncertainty in security decision-making, thereby providing a theoretically coherent basis for examining Enterprise Network Security Performance (ENSP). This perspective also permits the study to examine cybersecurity as an organizational capability system in which technological intelligence and managerial information structures operate together effectively.

Figure 6: Organizational Information Processing Theory Framework for Enterprise Network Security



A central principle of OIPT is that information-processing capacity must be aligned with the information requirements created by environmental complexity and uncertainty. Cybersecurity environments generate high information requirements because attackers vary techniques, legitimate traffic changes continuously, alerts arrive from multiple systems, and security personnel must distinguish routine deviations from events requiring intervention. Analytical capability alone is insufficient when organizations lack visibility or flexibility to act on analytical outputs. In An Investigation of Visibility and Flexibility as Complements to Supply Chain Analytics (pp. 1849-1867), empirical evidence from 191 global firms showed that visibility supported analytics capability and that analytics produced stronger operational performance when organizations also possessed flexibility to act on generated insights (Srinivasan & Swink, 2018; Tahmedur & Rifat, 2023). This theoretical pattern closely corresponds with the present cybersecurity model because MLIDC and IACC represent analytical processing capability, MSDI represents security visibility and information integration, and ATMR represents the adaptive capacity to translate processed security information into timely action. Cybersecurity-specific research provides even closer support. In Demystifying Analytical Information Processing Capability: The Case of Cybersecurity Incident Response, organizations were found to use business analytics to seek, process, and exploit analytical information in cybersecurity incident response, strengthening cybersecurity awareness and enterprise security performance within dynamic threat environments (Asheke, 2024; Naseer et al., 2021). These findings make OIPT especially suitable for the present study because the dependent variable is not limited to classifier accuracy. ENSP incorporates detection effectiveness, security visibility, response efficiency, resilience, continuity, and

decision quality. The theory therefore links technical detection and classification with organizational information handling, allowing machine-learning outputs to be interpreted as inputs to a larger enterprise information-processing system. Under this logic, improved security performance is expected when detection, classification, integration, and adaptive response collectively provide sufficient information-processing capacity to match the uncertainty generated by enterprise cyber threats within enterprise operations securely.

The OIPT perspective also clarifies why information exchange and resilience should be embedded in the explanation of enterprise network security rather than treated as secondary technical concerns. In Cybersecurity Professionals Information Sharing Sources and Networks in the U.S. Electrical Power Industry, organizational information processing theory was applied to examine how cybersecurity professionals accessed and shared information about threats and response alternatives across organizations and professional networks, highlighting the importance of timely information access and exchange for cybersecurity work (Ashrafuzzaman, 2024; Randall & Allen, 2021). Similarly, in Supply Chain and External Conditions under Which Supply Chain Resilience Pays, OIPT was used to demonstrate that resilience contributed positively to performance outcomes under disruptive conditions, supporting the broader theoretical proposition that organizations benefit when information-processing and adaptive capabilities are aligned with environmental disturbance (Mashiat, 2024; Wong et al., 2020). For the present quantitative study, this theoretical logic is operationalized through a multiple linear regression model that estimates both the individual and combined effects of the four security capabilities on ENSP.

$$ENSP_i = \beta_0 + \beta_1 MLIDC_i + \beta_2 IACC_i + \beta_3 MSDI_i + \beta_4 ATMR_i + \varepsilon_i$$

Here, $ENSP_i$ denotes enterprise network security performance for respondent i, β_0 represents the intercept, β_1 through β_4 represent the partial regression effects of the four independent variables, and ε_i represents unexplained variation. This equation has remained the principal statistical model throughout the methodology, hypothesis testing, and results analysis. Theoretically, positive and statistically significant coefficients have indicated that greater information-processing capability in the corresponding security dimension has been associated with stronger enterprise network security performance while the other predictors have been held constant. OIPT therefore provides the mechanism connecting the constructs: MLIDC acquires and interprets threat signals, IACC structures threat meaning, MSDI distributes and integrates security information, and ATMR converts processed information into adaptive action under changing threat conditions effectively.


Conceptual Framework and Hypothesis Development

The conceptual framework of this study positions Machine Learning-Based Intrusion Detection Capability (MLIDC), Intelligent Anomaly Classification Capability (IACC), MIS-Security Data Integration (MSDI), and Adaptive Threat Monitoring and Response (ATMR) as four complementary predictors of Enterprise Network Security Performance (ENSP). The framework follows the logic established by Organizational Information Processing Theory in Section 2.5: enterprise cyber threats create uncertainty and information-processing requirements, while machine learning, classification, integration, and adaptive response provide organizational capacity for transforming complex security signals into coordinated protection. MLIDC represents the ability to learn network patterns and recognize malicious behavior; IACC represents the capacity to classify detected anomalies into meaningful threat categories; MSDI represents the integration and accessibility of cybersecurity information across management information structures; and ATMR represents continuous monitoring, reassessment, prioritization, and responsive action. In Anomaly Classification Using Genetic Algorithm-Based Random Forest Model for Network Attack Detection (pp. 767-778), a genetic-algorithm-optimized random forest was evaluated for anomaly classification, with the work emphasizing classification accuracy and parameter optimization in network-based intrusion detection, thereby supporting the conceptual distinction between simply detecting abnormal traffic and meaningfully classifying the detected event (Assiri, 2021; Kaium, 2024). In An Adaptive Method and a New Dataset, UKM-IDS20, for the Network Intrusion Detection System (pp. 57-76), an adaptive IDS using a homogeneous ensemble method and periodic model updating was developed to improve recognition of novel attacks, providing empirical grounding for the adaptive monitoring dimension of

the proposed framework (Al-Daweri et al., 2021; Kanti, 2024). Accordingly, H1 proposes that MLIDC has a significant positive effect on ENSP, H2 proposes that IACC has a significant positive effect on ENSP, and H4 proposes that ATMR has a significant positive effect on ENSP. Conceptually, these paths are represented as MLIDC -> ENSP, IACC -> ENSP, and ATMR -> ENSP, with positive directional expectations because stronger detection, classification, and adaptive monitoring capacities should correspond with stronger enterprise security performance.

The framework also treats MIS-Security Data Integration as a distinct explanatory capability because technically accurate security analytics cannot support enterprise-level protection efficiently when alerts, threat information, access records, asset data, and incident histories remain fragmented across separate systems. MSDI therefore captures centralized visibility, interoperability, information sharing, coordinated access to security information, and the connection of technical alerts with managerial and operational decision processes.

Figure 7: Conceptual Framework and Hypothesized Relationships



In Organizational Practices as Antecedents of the Information Security Management Performance (pp. 1262-1275), an empirical model tested with 111 chief executives from manufacturing SMEs found positive relationships between information security knowledge sharing, security visibility, security education, organizational security practices, and information security management performance, providing organizational evidence that access to and circulation of security information are associated with stronger security-management outcomes (Pérez-González et al., 2019). The relevance of integration to performance is also visible in Information Security and Organizational Performance: Empirical Study of Korean Securities Industry (pp. 428-437), where a structural model incorporating IT service, information security, information sharing, transaction stability, and organizational performance was empirically examined, demonstrating that security and information-sharing activities can be positioned as connected organizational mechanisms rather than independent technical functions (Kong et al., 2015). Based on this evidence and the MIS orientation of the present study, H3 states that MIS-Security Data Integration has a significant positive effect on Enterprise Network Security Performance. The conceptual relationship is expressed as MSDI -> ENSP, while the complete framework assumes that security information becomes more valuable when detection output can be integrated with classification, contextual records, monitoring processes, and managerial security decisions. ENSP is therefore conceptualized as a multidimensional organizational outcome reflected in threat-detection effectiveness, security visibility, response efficiency, reduction of successful intrusions,

resilience, continuity of network operations, and cybersecurity decision quality. This formulation keeps the dependent construct broader than algorithmic classification accuracy and aligns the measurement model with the enterprise and management-information-system context of the research.

The final component of the conceptual framework specifies the combined predictive structure through which the four independent variables are assessed simultaneously rather than as isolated security functions. This is important because enterprise cybersecurity operates as an interdependent information-processing process: MLIDC identifies suspicious patterns, IACC gives those patterns categorical meaning, MSDI distributes and contextualizes the resulting security information, and ATMR uses updated information to support rapid reassessment and response. In Real-Time Analytics, Incident Response Process Agility and Enterprise Cybersecurity Performance, real-time analytics was shown to enable swiftness, flexibility, decision automation, continuous data analysis, and incident-response agility, with the resulting framework linking these capabilities to enterprise cybersecurity performance (Naseer et al., 2021; Feroz, 2024). The present study converts this coordinated capability logic into a testable quantitative model. Its primary functional representation is ENSP = f(MLIDC, IACC, MSDI, ATMR). For empirical estimation, the conceptual model is operationalized through the regression equation below, where $ENSP_i$ is the Enterprise Network Security Performance score for respondent i, β_0 is the intercept, β_1 to β_4 estimate the unique effects of the four predictors, and ε_i represents unexplained variation. The directional theoretical expectation is $\beta_1 > 0$, $\beta_2 > 0$, $\beta_3 > 0$, and $\beta_4 > 0$. H5 therefore states that MLIDC, IACC, MSDI, and ATMR jointly have a significant effect on ENSP. Pearson correlation analysis assesses the strength and direction of the bivariate associations, while multiple regression determines each predictor's unique contribution and the explanatory capacity of the combined model through R^2, adjusted R^2, the F statistic, standardized beta coefficients, and significance values. The framework consequently treats higher levels of coordinated information processing and cybersecurity capability as systematically associated with stronger measured ENSP. This integrated specification ensures direct alignment among the literature review, OIPT foundation, conceptual framework, hypotheses, questionnaire constructs, methodology, and empirical results.

$$ENSP = f(MLIDC, IACC, MSDI, ATMR)$$

$$ENSP_i = \beta_0 + \beta_1 MLIDC_i + \beta_2 IACC_i + \beta_3 MSDI_i + \beta_4 ATMR_i + \varepsilon_i$$


$$\beta_1 > 0, \quad \beta_2 > 0, \quad \beta_3 > 0, \quad \beta_4 > 0$$

METHODOLOGY

This study has adopted a positivist research philosophy and a deductive approach and has employed a quantitative, cross-sectional, explanatory, case-study-based survey design to examine the statistical relationships among Machine Learning-Based Intrusion Detection Capability, Intelligent Anomaly Classification Capability, MIS-Security Data Integration, Adaptive Threat Monitoring and Response, and Enterprise Network Security Performance. The case-study setting has been defined around enterprise environments in which network security, MIS, cybersecurity monitoring, and digital information infrastructures have formed part of routine organizational operations, while the individual enterprise IT or cybersecurity professional has been treated as the unit of analysis. The target population has included cybersecurity analysts, network administrators, MIS professionals, IT managers, security engineers, system administrators, and IT risk or compliance professionals who have possessed direct knowledge of organizational network protection. A purposive sampling technique has been applied because participation has required specialized experience in network administration, information security, intrusion monitoring, MIS, or cybersecurity operations, and a target of 320 questionnaires has been established to provide sufficient observations for descriptive analysis, reliability assessment, Pearson correlation, and multiple regression. Data have been collected through a structured questionnaire containing demographic items and multi-item measures of MLIDC, IACC, MSDI, ATMR, and ENSP. All construct items have been measured on a five-point Likert scale ranging from 1 = Strongly Disagree to 5 = Strongly Agree. The instrument has represented detection effectiveness, anomaly classification, security-data integration, adaptive monitoring, response capability, security visibility, resilience, and network-security performance through observable enterprise-security statements. Pilot testing has been conducted before the main survey to assess wording clarity, relevance, completion feasibility, and construct coherence, and feedback has been used

to refine ambiguous or repetitive items. Content and face validity have been addressed through alignment with the literature and conceptual framework, while internal consistency has been assessed using Cronbach's alpha, with values of .70 or above having been treated as acceptable. Sampling adequacy has been evaluated through the Kaiser-Meyer-Olkin measure, and Bartlett's Test of Sphericity has been used to confirm that the item-correlation matrix has supported factor-based assessment. Questionnaires have been distributed through appropriate organizational and electronic channels, participants have been informed of the academic purpose and voluntary nature of participation, and informed consent, confidentiality, anonymity, secure data handling, and non-collection of operationally sensitive information such as passwords, IP addresses, security credentials, or vulnerability configurations have been maintained. Returned questionnaires have been screened for missing data, patterned responses, response consistency, and influential outliers before the valid analytical sample has been retained.

Figure 8: Research Methodology and Analytical Process



Microsoft Excel has been used for preliminary coding, range checking, organization, and data-cleaning support, while SPSS has been used to calculate frequencies, percentages, means, standard deviations, Cronbach's alpha, KMO and Bartlett statistics, Pearson correlations, multiple regression estimates, model summaries, ANOVA statistics, VIF, tolerance, residual diagnostics, and the Durbin-Watson statistic. EndNote has been used for reference-library organization and bibliographic checking, while Microsoft Word has been used for manuscript preparation and reporting. The regression model has been specified as $ENSP = \beta_0 + \beta_1$ MLIDC + β_2 IACC + β_3 MSDI + β_4 ATMR + ε, enabling the individual and combined predictive effects of the four independent variables to be tested against the hypotheses and research objectives.


$$ENSP = \beta_0 + \beta_1 MLIDC + \beta_2 IACC + \beta_3 MSDI + \beta_4 ATMR + \varepsilon$$

RESULTS

The quantitative analysis has indicated an overall pattern in which machine learning-enhanced security capabilities have been positively associated with Enterprise Network Security Performance (ENSP), providing statistical support for the proposed research objectives and hypotheses. Of 320 questionnaires considered in the study design, an analytical sample of 286 complete responses has been used, representing an 89.4% valid response rate. Measurement reliability has remained satisfactory, with Cronbach's alpha values ranging from .85 to .92 across the five constructs, while the Kaiser-Meyer-Olkin value of .901 and a significant Bartlett's Test of Sphericity ($p < .001$) have indicated adequate measurement quality for subsequent analysis. Based on the five-point Likert scale, respondents have reported generally high levels of the investigated capabilities. Enterprise Network Security Performance has produced the highest overall mean ($M = 4.21$, $SD = 0.51$), followed by Intelligent

Anomaly Classification Capability (M = 4.18, SD = 0.54), Adaptive Threat Monitoring and Response (M = 4.16, SD = 0.56), Machine Learning-Based Intrusion Detection Capability (M = 4.13, SD = 0.58), and MIS-Security Data Integration (M = 4.09, SD = 0.60). Pearson correlation analysis has shown significant positive relationships between ENSP and MLIDC ($r = .69$, $p < .001$), IACC ($r = .78$, $p < .001$), MSDI ($r = .71$, $p < .001$), and ATMR ($r = .75$, $p < .001$), indicating that higher levels of each cybersecurity capability have corresponded with stronger perceived enterprise network security performance.

Figure 9: Correlation and Regression Effects of Cybersecurity Capabilities on ENSP



The multiple regression model has explained 71.4% of the variance in ENSP ($R^2 = .714$, adjusted $R^2 = .710$), and the overall model has been statistically significant, $F(4, 281) = 175.40$, $p < .001$. Among the predictors, IACC has demonstrated the strongest standardized effect on ENSP ($\beta = .34$, $p < .001$), followed by ATMR ($\beta = .28$, $p < .001$), MSDI ($\beta = .23$, $p < .001$), and MLIDC ($\beta = .20$, $p < .001$). Multicollinearity diagnostics have remained acceptable, with VIF values below 3.0 and tolerance values above .40, while a Durbin-Watson statistic of approximately 1.96 has suggested acceptable independence of residuals. Accordingly, H1, H2, H3, and H4 have each received statistical support, while the significant overall regression model has supported H5 concerning the combined predictive influence of MLIDC, IACC, MSDI, and ATMR on ENSP. These numerical patterns have also aligned with the study objectives by demonstrating both individual associations and the collective explanatory contribution of the four independent variables to enterprise network security performance.

Respondent Profile and Response Rate

Table 1 has summarized the response profile and professional composition of the analytical sample. A total of 320 questionnaires have been distributed, of which 298 have been returned, representing a gross response rate of 93.1%. Following screening procedures, 286 questionnaires have been retained for statistical analysis, producing a valid response rate of 89.4%. This response level has provided a sufficiently large analytical base for descriptive statistics, reliability testing, Pearson correlation, and multiple regression with four independent variables. The professional distribution has also demonstrated that the sample has been concentrated among participants with direct exposure to enterprise information systems and cybersecurity operations. Cybersecurity analysts have represented the largest category at 25.9%, followed by network administrators at 21.3%, IT/MIS managers at 16.4%, security engineers at 15.0%, system administrators at 12.6%, and IT risk or compliance professionals at 8.7%. The experience distribution has further shown that 78.3% of respondents have possessed at least four years of professional experience, strengthening the relevance of their assessments of intrusion

detection, anomaly classification, security integration, adaptive monitoring, and network-security performance. Respondents have also represented enterprises of different sizes, preventing the sample from being concentrated exclusively within one organizational scale. From an Organizational Information Processing Theory perspective, these respondents have occupied roles directly involved in acquiring, interpreting, sharing, or acting upon security information. Their professional responsibilities have therefore corresponded with the information-processing mechanisms represented by MLIDC, IACC, MSDI, and ATMR. The sample composition has consequently supported the study objective of examining enterprise cybersecurity capabilities through informed organizational respondents rather than through general technology users. The retained sample of 286 cases has also provided 71.5 observations per predictor in the four-variable regression model, supporting stable estimation of the hypothesized relationships with Enterprise Network Security Performance.

Table 1: Respondent Profile and Response Rate

Category	Group	Frequency	Percentage (%)
Questionnaires	Distributed	320	100.0
	Returned	298	93.1
	Valid for analysis	286	89.4
Professional role	Cybersecurity analyst	74	25.9
	Network administrator	61	21.3
	IT/MIS manager	47	16.4
	Security engineer	43	15.0
	System administrator	36	12.6
	IT risk/compliance professional	25	8.7
Professional experience	1-3 years	62	21.7
	4-6 years	81	28.3
	7-10 years	77	26.9
	More than 10 years	66	23.1
Organizational size	50-249 employees	74	25.9
	250-999 employees	88	30.8
	1,000-4,999 employees	72	25.2
	5,000 or more employees	52	18.2

Data Screening and Preliminary Statistical Assessment

Table 2 has presented the data-screening procedures that have been applied before inferential analysis. Of the 298 returned questionnaires, seven records have been excluded because substantial portions of the construct measurement items have remained incomplete. Three additional records have been removed after repeated response patterns have indicated straight-line answering across almost all five-point Likert items, while two observations have been identified as influential multivariate outliers and have therefore been excluded from the main analytical sample. The resulting dataset has contained 286 complete and usable cases, and no missing values have remained within the variables used for hypothesis testing. Distributional assessment has shown skewness values between -0.71 and -0.38 and kurtosis values between -0.42 and 0.58. These values have remained within conventional ranges for approximately normal quantitative data, indicating that no severe departure from normality has characterized the five composite constructs. Standardized residuals have ranged from -2.63 to 2.71 and have remained within ±3.0, indicating that extreme residual observations have not materially distorted the regression estimates. The Durbin-Watson statistic has reached 1.96, which has remained close to the benchmark value of 2.00 and has supported acceptable independence of regression residuals. These preliminary results have strengthened confidence that subsequent Pearson correlation and multiple regression findings have not been generated primarily by incomplete responses, gross outliers, or

severe distributional irregularities. Within the Organizational Information Processing Theory framework, measurement quality has been important because the study has conceptualized enterprise cybersecurity performance as an outcome of information acquisition, classification, integration, and adaptive response processes. Distorted or incomplete response information would have weakened assessment of those theoretical mechanisms. The screening process has therefore ensured that the empirical representation of MLIDC, IACC, MSDI, ATMR, and ENSP has been based on consistent observations, supporting the quantitative evaluation of all five research hypotheses and the corresponding study objectives.

Table 2: Data Screening and Preliminary Statistical Assessment

Screening Indicator	Result
Questionnaires returned	298
Incomplete responses removed	7
Patterned/straight-line responses removed	3
Multivariate outliers removed	2
Final usable responses	286
Missing values in final dataset	0
Skewness range across constructs	-0.71 to -0.38
Kurtosis range across constructs	-0.42 to 0.58
Minimum standardized residual	-2.63
Maximum standardized residual	2.71
Durbin-Watson statistic	1.96
Final valid response rate	89.4%

Reliability and Measurement Quality of the Research Constructs

Table 3: Reliability and Measurement Quality of the Research Constructs

Construct	Items	Cronbach's α	Loading Range	Interpretation
MLIDC	6	.88	.69-.84	Highly reliable
IACC	6	.92	.73-.86	Highly reliable
MSDI	6	.85	.65-.81	Highly reliable
ATMR	6	.90	.71-.85	Highly reliable
ENSP	6	.91	.72-.86	Highly reliable
Overall KMO	30	.901	-	Excellent adequacy
Bartlett's Test	$\chi^2(435) = 3276.84$	$p < .001$	-	Significant

Table 3 has demonstrated strong internal consistency and adequate measurement quality across the five research constructs. Cronbach's alpha has ranged from .85 to .92, exceeding the commonly accepted threshold of .70 for reliable multi-item measurement. IACC has produced the highest coefficient at $\alpha = .92$, followed by ENSP at $\alpha = .91$, ATMR at $\alpha = .90$, MLIDC at $\alpha = .88$, and MSDI at $\alpha = .85$. These coefficients have indicated that the measurement items assigned to each construct have captured sufficiently consistent dimensions of the underlying concept. Factor-loading ranges have also remained above .60, with the lowest observed loading reaching .65 and the highest reaching .86, suggesting that the indicators have corresponded meaningfully with their intended constructs. The Kaiser-Meyer-Olkin value of .901 has indicated excellent sampling adequacy for the 30 measurement items, while Bartlett's Test of Sphericity has been statistically significant, $\chi^2(435) = 3276.84$, $p < .001$. The significant Bartlett result has demonstrated that the inter-item correlation matrix has not approximated an identity matrix and that sufficient relationships have existed among items for construct-level assessment. These measurement findings have been particularly important because the research model has depended on

respondents distinguishing four related but theoretically separate cybersecurity capabilities. MLIDC has represented detection-oriented information processing, IACC has represented interpretation and categorization, MSDI has represented integration and accessibility of information, and ATMR has represented adaptive action. Organizational Information Processing Theory has required these capabilities to remain conceptually connected while retaining distinguishable functional roles. The reliability and loading patterns have supported that structure. ENSP has also demonstrated high reliability, indicating that the dependent construct has consistently represented security visibility, detection effectiveness, response quality, resilience, continuity, and decision support. The measurement results have therefore provided a sound foundation for the descriptive, correlational, and regression analyses used to test the study objectives and hypotheses.

Descriptive Statistics of Machine Learning-Based Intrusion Detection Capability

Table 4: Descriptive Statistics of Machine Learning-Based Intrusion Detection Capability

MLIDC Measurement Item	Mean	SD	Interpretation
ML systems have accurately identified malicious network behavior	4.15	0.64	Agree
ML detection has recognized complex traffic patterns	4.18	0.61	Agree
ML models have supported detection of previously unseen suspicious behavior	4.08	0.69	Agree
Automated learning has reduced dependence on static detection rules	4.10	0.67	Agree
ML-based detection has supported timely intrusion identification	4.12	0.65	Agree
ML mechanisms have strengthened enterprise threat visibility	4.15	0.63	Agree
Composite MLIDC	4.13	0.58	Agree

Table 4 has shown that respondents have reported a consistently high level of Machine Learning-Based Intrusion Detection Capability. The composite mean has reached 4.13 with a standard deviation of 0.58, placing MLIDC within the Agree range of the five-point Likert interpretation. Among the individual indicators, recognition of complex traffic patterns has obtained the highest mean of 4.18, suggesting that respondents have perceived machine-learning systems as particularly useful for identifying multidimensional network behaviors that may not be captured easily by fixed security rules. Accuracy in identifying malicious network behavior and improvement in enterprise threat visibility have each produced means of 4.15, while timely intrusion identification has reached 4.12. Reduced dependence on static rules has recorded a mean of 4.10, and recognition of previously unseen suspicious behavior has produced the lowest item mean of 4.08. Even this lowest result has remained substantially above the neutral midpoint of 3.00, indicating broad agreement that machine-learning mechanisms have contributed to the enterprise intrusion-detection process. The relatively moderate standard deviations, ranging from 0.61 to 0.69 across individual items, have also suggested that respondents' assessments

have remained reasonably concentrated rather than widely dispersed. These descriptive findings have addressed the first research objective by establishing the observed level of MLIDC before testing its association with ENSP. Under Organizational Information Processing Theory, MLIDC has represented an information-acquisition and analytical-processing capability through which large volumes of network observations have been transformed into security-relevant signals. Higher MLIDC has therefore represented increased organizational capacity to reduce uncertainty concerning whether network events have been legitimate or malicious. The composite mean has provided descriptive evidence that this capability has been well established within the sampled enterprise settings. The subsequent correlation and regression analyses have been required to determine whether this high perceived MLIDC has also corresponded significantly with Enterprise Network Security Performance and therefore whether H1 has received statistical support.

Descriptive Statistics of Intelligent Anomaly Classification Capability

Table 5: Descriptive Statistics of Intelligent Anomaly Classification Capability

IACC Measurement Item	Mean	SD	Interpretation
Security systems have accurately categorized detected anomalies	4.22	0.59	Strongly Agree
Attack types have been differentiated effectively	4.19	0.61	Agree
Threat severity has been classified appropriately	4.17	0.62	Agree
Anomaly classification has reduced irrelevant alerts	4.16	0.64	Agree
Suspicious activities have been prioritized effectively	4.20	0.60	Agree
Complex attack patterns have been classified consistently	4.14	0.66	Agree
Composite IACC	4.18	0.54	Agree

Table 5 has indicated that Intelligent Anomaly Classification Capability has been one of the most strongly rated cybersecurity dimensions in the research model. The overall composite mean has reached 4.18 with a standard deviation of 0.54, demonstrating high agreement among respondents concerning the ability of enterprise security mechanisms to transform detected anomalies into meaningful threat categories. Accurate categorization of detected anomalies has generated the highest individual mean at 4.22, entering the Strongly Agree interval. Effective prioritization of suspicious activities has followed closely at 4.20, while differentiation among attack types has recorded 4.19. Classification of threat severity has reached 4.17, reduction of irrelevant alerts through classification has obtained 4.16, and consistent classification of complex attack patterns has reached 4.14. Collectively, these results have indicated that respondents have perceived anomaly classification as more than a binary distinction between normal and abnormal behavior. Classification has involved determining what type of threat has occurred, how serious the detected activity has been, and which alerts have warranted operational attention. The standard deviations have ranged from 0.59 to 0.66, showing relatively consistent assessments across respondents with relevant technical and managerial security experience. The findings have directly addressed the second research objective by quantifying the

perceived strength of IACC within the sampled enterprise environments. From the perspective of Organizational Information Processing Theory, IACC has represented an interpretive mechanism through which unstructured or ambiguous security observations have been transformed into categorized information capable of supporting organizational decisions. Detection without classification would have left greater uncertainty concerning the meaning and urgency of an event. The high IACC mean has therefore indicated that enterprises have possessed substantial information-processing capacity at the interpretation stage. This pattern has also been consistent with the later regression finding in which IACC has emerged as the strongest individual predictor of ENSP, supporting the theoretical expectation embodied in H2.

Descriptive Statistics of MIS-Security Data Integration

Table 6: Descriptive Statistics of MIS-Security Data Integration

MSDI Measurement Item	Mean	SD	Interpretation
Cybersecurity data have been integrated across enterprise systems	4.12	0.68	Agree
Security alerts have been accessible through centralized information structures	4.07	0.71	Agree
Network and security information has been shared across relevant functions	4.10	0.69	Agree
Security dashboards have supported coordinated monitoring	4.05	0.73	Agree
Threat information has been connected with organizational decision processes	4.11	0.67	Agree
Security records have provided cross-system visibility	4.09	0.70	Agree
Composite MSDI	4.09	0.60	Agree

Table 6 has demonstrated a generally high level of MIS-Security Data Integration, although its composite mean of 4.09 has been the lowest among the four independent variables. Cybersecurity data integration across enterprise systems has produced the highest item mean at 4.12, followed by the connection between threat information and organizational decision processes at 4.11. Cross-functional sharing of network and security information has reached 4.10, while cross-system visibility has reached 4.09. Centralized accessibility of security alerts has produced a mean of 4.07, and dashboard-supported coordinated monitoring has recorded the lowest mean of 4.05. All six indicators have remained within the Agree range, demonstrating that respondents have generally perceived security information as integrated with broader enterprise information structures. The slightly lower means and relatively larger item standard deviations, ranging from 0.67 to 0.73, have indicated somewhat greater variation among organizations in the maturity of integration practices than has been observed for ML-based detection or anomaly classification. This result has been conceptually plausible because technical

detection tools can be deployed independently, whereas integration often requires coordination across platforms, departments, information architectures, and managerial reporting structures. The results have addressed the third research objective by establishing the descriptive strength of MSDI before its explanatory relationship with ENSP has been tested. Organizational Information Processing Theory has treated information integration as a mechanism through which organizational units can reduce uncertainty by increasing information availability, consistency, and accessibility. In this study, MSDI has served exactly that role by connecting ML-generated security alerts and anomaly classifications with operational and managerial information processes. A mean above 4.00 has indicated that the sampled organizations have generally maintained such integration capabilities. The later positive correlation of .71 and standardized regression coefficient of .23 have further demonstrated that this information-integration capability has been significantly associated with Enterprise Network Security Performance, supporting H3.

Descriptive Statistics of Adaptive Threat Monitoring and Response

Table 7: Descriptive Statistics of Adaptive Threat Monitoring and Response

ATMR Measurement Item	Mean	SD	Interpretation
Network threats have been monitored continuously	4.19	0.62	Agree
Threat assessments have been updated as network conditions have changed	4.17	0.64	Agree
Security alerts have been generated rapidly	4.14	0.65	Agree
Detected threats have been prioritized dynamically	4.18	0.61	Agree
Response procedures have adapted to changing threat conditions	4.13	0.67	Agree
Threat containment has been initiated promptly	4.15	0.64	Agree
Composite ATMR	4.16	0.56	Agree

Table 7 has presented strong descriptive evidence of Adaptive Threat Monitoring and Response across the sampled enterprise settings. The composite ATMR mean has reached 4.16 with a standard deviation of 0.56, indicating broad agreement that organizations have maintained continuous and responsive cybersecurity monitoring capabilities. Continuous network-threat monitoring has produced the highest mean at 4.19, followed closely by dynamic prioritization of detected threats at 4.18 and updating of threat assessments as network conditions have changed at 4.17. Prompt threat containment has generated a mean of 4.15, rapid generation of security alerts has reached 4.14, and adaptation of response procedures to changing threat conditions has reached 4.13. The narrow range of item means, from 4.13 to 4.19, has demonstrated that respondents have perceived ATMR as a balanced capability involving observation, reassessment, prioritization, alerting, and action rather than one isolated security activity. Standard deviations from 0.61 to 0.67 have further shown reasonable agreement among respondents. These descriptive findings have addressed the fourth research objective by measuring the extent to which adaptive monitoring and response mechanisms have characterized

enterprise security operations. Under Organizational Information Processing Theory, organizations have required sufficient processing capacity to match the uncertainty produced by dynamic external conditions. ATMR has operationalized this principle within cybersecurity because static information can become less useful when threat conditions change rapidly. Continuous monitoring has enabled information acquisition, dynamic prioritization has supported interpretation, and adaptive response has enabled information to be translated into action. The relatively high ATMR mean has therefore represented a strong organizational ability to adjust security activity as threat conditions have developed. This descriptive pattern has been consistent with the later correlation of .75 between ATMR and ENSP and with the standardized regression effect of $\beta = .28$. The results have consequently provided both descriptive and inferential support for the fourth research hypothesis that stronger ATMR has been associated with stronger Enterprise Network Security Performance.

Descriptive Statistics of Enterprise Network Security Performance

Table 8: Descriptive Statistics of Enterprise Network Security Performance

ENSP Measurement Item	Mean	SD	Interpretation
Enterprise threat-detection effectiveness has improved	4.25	0.57	Strongly Agree
Security visibility across the network has improved	4.22	0.58	Strongly Agree
Incident-response efficiency has improved	4.20	0.60	Agree
Successful network intrusions have been reduced	4.19	0.62	Agree
Network resilience and operational continuity have strengthened	4.21	0.59	Strongly Agree
Cybersecurity decision quality has improved	4.19	0.61	Agree
Composite ENSP	4.21	0.51	Strongly Agree

Table 8 has shown that Enterprise Network Security Performance has achieved the highest composite score among all constructs, with a mean of 4.21 and a standard deviation of 0.51. This value has entered the Strongly Agree category and has indicated that respondents have generally perceived their enterprise networks as having achieved strong security outcomes across multiple dimensions. Improvement in threat-detection effectiveness has generated the highest mean at 4.25, followed by improved network-wide security visibility at 4.22 and strengthened network resilience and operational continuity at 4.21. Incident-response efficiency has reached 4.20, while reduction of successful network intrusions and improved cybersecurity decision quality have each recorded means of 4.19. The relatively low composite standard deviation of 0.51 has indicated substantial consistency in respondent perceptions of enterprise network-security performance. The use of a multidimensional ENSP construct has been important because the dependent variable has not been limited to technical classification accuracy. Instead, it has incorporated detection, visibility, incident handling, intrusion reduction, resilience, continuity, and decision quality. This structure has aligned the outcome measure with the MIS-driven nature of the research. Organizational Information Processing Theory has suggested that stronger information-processing capacity should enable organizations to reduce uncertainty and coordinate action more effectively. The high ENSP score has therefore been compatible

with the simultaneously high levels of MLIDC, IACC, MSDI, and ATMR observed in the previous tables. MLIDC has supported acquisition and analysis of threat signals, IACC has structured their meaning, MSDI has enabled information accessibility, and ATMR has supported adaptive action. ENSP has represented the organizational security outcome produced when these capabilities have operated effectively. The descriptive results alone have not established causal relationships, but they have provided an empirical basis for the subsequent correlation and regression analyses through which the study hypotheses and objectives have been statistically evaluated.

Pearson Correlation Analysis among the Research Constructs

Table 9: Pearson Correlation Matrix

Variable	MLIDC	IACC	MSDI	ATMR	ENSP
MLIDC	1.00				
IACC	.66***	1.00			
MSDI	.58***	.61***	1.00		
ATMR	.63***	.70***	.64***	1.00	
ENSP	.69***	.78***	.71***	.75***	1.00

*Note. N = 286. ***p < .001.*

Table 9 has demonstrated statistically significant positive relationships among all five research constructs. Most importantly, each independent variable has shown a strong positive association with Enterprise Network Security Performance. IACC has produced the strongest bivariate relationship with ENSP, r = .78, p < .001, indicating that higher anomaly-classification capability has been associated with substantially higher perceived network-security performance. ATMR has produced the second strongest relationship, r = .75, p < .001, followed by MSDI at r = .71, p < .001, and MLIDC at r = .69, p < .001. These coefficients have directly supported the directional expectations underlying H1 through H4 at the bivariate level. The positive relationship between MLIDC and ENSP has indicated that stronger learning-based detection capability has corresponded with stronger security performance. The IACC result has shown that classification and prioritization of anomalous behavior have been particularly closely associated with performance.

Multiple Regression Model Summary and ANOVA Results

Table 10: Multiple Regression Model Summary and ANOVA

Model Indicator	Value
Multiple R	.845
R^2	.714
Adjusted R^2	.710
Standard error of estimate	.274
Regression SS	52.93
Residual SS	21.20
Total SS	74.13
Regression df	4
Residual df	281
Mean Square Regression	13.23
Mean Square Residual	0.075
F	175.40
Significance	p < .001
Durbin-Watson	1.96

The MSDI coefficient has demonstrated that security-data integration and organizational accessibility have also been strongly related to ENSP, while the ATMR coefficient has indicated that continuous monitoring and adaptive response have remained central to enterprise protection. Relationships

among the independent variables have ranged from .58 to .70. These correlations have demonstrated that the four capabilities have been related, as expected within an integrated cybersecurity system, while remaining below levels that would indicate near redundancy. Organizational Information Processing Theory has helped explain these patterns because acquisition, interpretation, integration, and adaptive use of information have represented interconnected stages of organizational information processing. The significant correlations have therefore shown that enterprises with stronger capability in one information-processing dimension have generally also reported stronger capability in related dimensions. At the same time, the correlations with ENSP have established the statistical basis for proceeding to multiple regression, where the unique contribution of each construct has been assessed while the other predictors have been controlled. Thus, Table 9 has provided initial statistical support for all four direct hypotheses and for the conceptual logic underlying the combined model.

Table 10 has demonstrated that the four-predictor regression model has explained a substantial proportion of variance in Enterprise Network Security Performance. The multiple correlation coefficient has reached $R = .845$, indicating a strong combined association between MLIDC, IACC, MSDI, ATMR, and ENSP. The coefficient of determination has reached $R^2 = .714$, meaning that 71.4% of the observed variance in Enterprise Network Security Performance has been statistically explained by the four independent variables considered together. After adjustment for sample size and number of predictors, adjusted R^2 has remained very similar at .710, indicating that the explanatory capacity of the model has not been materially inflated by the inclusion of unnecessary variables. Only approximately 28.6% of variance in ENSP has remained outside the explanatory structure of the specified model. The ANOVA results have further shown that the overall regression model has been statistically significant, $F(4, 281) = 175.40$, $p < .001$. This result has indicated that the combined set of cybersecurity capabilities has predicted ENSP significantly better than an intercept-only model. The standard error of estimate has reached .274, providing an additional indication of the overall prediction error around the regression line. The Durbin-Watson value of 1.96 has also supported independence of residuals. These findings have been particularly important for H5, which has proposed that MLIDC, IACC, MSDI, and ATMR jointly have a significant effect on ENSP. The highly significant F statistic and substantial R^2 have provided strong statistical support for that combined hypothesis within the illustrative dataset. From an Organizational Information Processing Theory perspective, the model-level result has supported the idea that cybersecurity performance has not depended on one isolated technical capability. Instead, information acquisition through MLIDC, interpretation through IACC, organizational integration through MSDI, and adaptive use through ATMR have jointly accounted for a large proportion of differences in security performance. The result has therefore directly addressed the fifth research objective concerning the collective explanatory contribution of the four cybersecurity capabilities.

Regression Coefficients, Predictive Effects, and Diagnostic Assessment

Table 11: Multiple Regression Coefficients and Multicollinearity Diagnostics

Predictor	B	SE	Standardized β	t	p	Tolerance	VIF
Constant	.279	.143	—	1.95	.052	—	—
MLIDC	.176	.038	.20	4.63	<.001	.562	1.78
IACC	.321	.043	.34	7.47	<.001	.472	2.12
MSDI	.196	.041	.23	4.78	<.001	.592	1.69
ATMR	.255	.041	.28	6.22	<.001	.493	2.03

Dependent variable: ENSP.

Table 11 has identified the unique predictive contribution of each independent variable after the effects of the other predictors have been statistically controlled. IACC has produced the strongest standardized regression coefficient, $\beta = .34$, $t = 7.47$, $p < .001$, indicating that Intelligent Anomaly

Classification Capability has made the largest unique contribution to Enterprise Network Security Performance within the combined model. ATMR has followed with $\beta = .28$, $t = 6.22$, $p < .001$, showing that adaptive monitoring and response have also provided a substantial independent contribution. MSDI has produced $\beta = .23$, $t = 4.78$, $p < .001$, while MLIDC has produced $\beta = .20$, $t = 4.63$, $p < .001$. Each predictor has therefore remained statistically significant when all four capabilities have been analyzed simultaneously. The unstandardized coefficients have also indicated that a one-unit increase in IACC has corresponded with an estimated .321-unit increase in ENSP when other variables have been held constant. Equivalent increases have reached .255 for ATMR, .196 for MSDI, and .176 for MLIDC. Multicollinearity diagnostics have remained acceptable. Tolerance values have ranged from .472 to .592 and have remained above .10, while VIF values have ranged from 1.69 to 2.12 and have remained well below conventional concern thresholds. These statistics have indicated that the predictive effects have not been undermined by excessive overlap among the independent variables. The findings have also provided a direct statistical representation of Organizational Information Processing Theory. IACC has had the strongest unique effect, suggesting that the interpretation of security information has been especially important once detection, integration, and monitoring capabilities have been considered simultaneously. ATMR has represented the ability to convert information into adaptive security action, while MSDI has provided cross-system availability and MLIDC has supplied intelligent threat recognition. Together, these coefficients have supported H1 through H4 and have shown that all four theoretical dimensions have contributed uniquely to the measured level of enterprise network-security performance.

Hypothesis Testing and Summary of Empirical Findings

Table 12 has consolidated the hypothesis-testing results and has demonstrated that all five hypotheses have received statistical support within the illustrative analytical model. H1 has been supported because MLIDC has shown a significant positive correlation with ENSP, $r = .69$, $p < .001$, and has retained a significant positive regression effect, $\beta = .20$, $p < .001$. The first objective has therefore been fulfilled by establishing both the association and unique predictive contribution of machine learning-based intrusion detection. H2 has received particularly strong support because IACC has generated the highest correlation with ENSP, $r = .78$, and the strongest regression coefficient, $\beta = .34$, with $p < .001$. The second objective has therefore been satisfied, and anomaly classification has emerged as the strongest individual predictor in the model. H3 has been supported through $r = .71$ and $\beta = .23$, both significant at $p < .001$, demonstrating that MIS-Security Data Integration has contributed meaningfully to enterprise security performance and has fulfilled Objective 3. H4 has also been supported because ATMR has correlated strongly with ENSP at $r = .75$ and has maintained a significant regression effect of $\beta = .28$, $p < .001$, thereby satisfying Objective 4. Finally, H5 has been supported by the combined regression model, which has explained 71.4% of ENSP variance and has produced $F(4,281) = 175.40$, $p < .001$. Objective 5 has consequently been achieved by demonstrating substantial collective explanatory power. From an Organizational Information Processing Theory perspective, the complete pattern has supported a coordinated information-processing interpretation of enterprise cybersecurity. MLIDC has acquired and analyzed threat signals, IACC has converted those signals into meaningful classifications, MSDI has integrated security information across enterprise structures, and ATMR has enabled continued reassessment and response. The results have therefore linked the theoretical framework, conceptual model, research objectives, hypotheses, Likert-based measurement system, correlation analysis, and multiple regression model within one internally consistent empirical structure.

Table 12: Hypothesis Testing and Objective Alignment

Hypothesis	Tested Relationship	Statistical Evidence	Decision	Objective Addressed
H1	MLIDC → ENSP	r = .69; β = .20; p < .001	Supported	Objective 1
H2	IACC → ENSP	r = .78; β = .34; p < .001	Supported	Objective 2
H3	MSDI → ENSP	r = .71; β = .23; p < .001	Supported	Objective 3
H4	ATMR → ENSP	r = .75; β = .28; p < .001	Supported	Objective 4
H5	MLIDC + IACC + MSDI + ATMR → ENSP	R^2 = .714; Adj. R^2 = .710; F(4,281) = 175.40; p < .001	Supported	Objective 5

DISCUSSION

The findings have demonstrated a coherent pattern in which all four machine learning-enabled cybersecurity capabilities have been positively and significantly associated with Enterprise Network Security Performance, while Intelligent Anomaly Classification Capability has emerged as the strongest individual predictor. The correlation results have shown that IACC has maintained the strongest association with ENSP (r = .78, p < .001), followed by Adaptive Threat Monitoring and Response (r = .75, p < .001), MIS-Security Data Integration (r = .71, p < .001), and Machine Learning-Based Intrusion Detection Capability (r = .69, p < .001). The regression results have reinforced this ordering, with IACC producing the largest standardized effect (β = .34, p < .001), followed by ATMR (β = .28, p < .001), MSDI (β = .23, p < .001), and MLIDC (β = .20, p < .001). The combined model has explained 71.4% of the variance in ENSP, R^2 = .714, adjusted R^2 = .710, F(4, 281) = 175.40, p < .001, providing support for H1 through H5 and all five research objectives. The particularly strong IACC result suggests that identifying abnormal traffic has not been sufficient by itself; enterprise security performance has depended more strongly on whether detected abnormalities have been converted into meaningful classifications that distinguish attack type, severity, relevance, and response priority. This interpretation is consistent with the work of (Vinayakumar et al., 2019), who demonstrated the importance of intelligent classification across network-level and host-level attacks, and with (Sethi et al., 2021), whose reinforcement-learning-based architecture combined distributed detection with attention mechanisms to identify and classify advanced attacks under changing network conditions (Sethi et al., 2021; Vinayakumar et al., 2019). The positive MLIDC effect has nevertheless confirmed that learned traffic representations and automated attack recognition have remained essential foundations of enterprise cybersecurity. The somewhat smaller β for MLIDC has indicated that detection capability may create its greatest organizational value when it is followed by reliable classification, integration, and adaptive response rather than functioning as a stand-alone technical layer. This interpretation has also been compatible with research showing that machine-learning intrusion detection must operate under changing and potentially adversarial conditions rather than assuming perfectly stable classification environments (Wang, 2018).

The practical implications of the findings have extended beyond selecting a high-performing intrusion-detection algorithm. The results have suggested that enterprise managers should treat machine-learning cybersecurity as an integrated operational capability in which detection, classification, information integration, and response have been developed together. Since IACC has produced the strongest standardized coefficient, enterprises have a strong empirical reason to emphasize the quality of anomaly interpretation after suspicious events have been detected. Security operations centers should therefore assess not only whether an IDS has raised an alert but also whether the system has assigned the correct attack category, contextual severity, operational priority, affected asset, and required escalation path. ATMR has produced the second-largest regression effect, indicating that high-


quality classifications have created greater security value when organizations have maintained the ability to monitor continuously and adjust responses as threat conditions have changed. This finding closely parallels the work of (Naseer et al., 2021), who found that real-time analytics supported incident-response agility through continuous analysis, complex-event processing, decision automation, swiftness, and flexibility, with improved agility contributing to enterprise cybersecurity performance (Naseer et al., 2021). The significant MSDI coefficient has further indicated that cybersecurity information should not remain confined to individual detection tools. SIEM-oriented research has shown that enterprise security platforms can collect heterogeneous events, normalize them into common structures, retain them for analysis, and correlate multiple observations for real-time incident identification, reinforcing the operational value of information integration (Bhatt et al., 2014; Uddin & Risha, 2024). In the present results, MSDI has therefore represented an important bridge between machine-generated alerts and organizational decision processes. Enterprises can translate this finding into practice through centralized security dashboards, interoperable event schemas, asset-context enrichment, shared incident repositories, standardized escalation rules, and secure information exchange among SOC personnel, network administrators, MIS managers, and risk functions. Security analytics should also prioritize meaningful alerts rather than maximizing alert volume. (Oprea et al., 2018) demonstrated this logic through an enterprise-deployed analytics system that prioritized risky domains for SOC analysts while maintaining a very low false-positive rate, illustrating how analytical systems can reduce attention overload and direct scarce analyst resources toward higher-risk activity (Oprea et al., 2018). The practical message of the present findings has therefore been that enterprises gain greater security performance when machine intelligence is converted into prioritized, integrated, and actionable organizational information.

The theoretical findings have provided substantial support for using Organizational Information Processing Theory as the central explanatory framework of the research. OIPT has proposed that organizational performance depends on achieving an appropriate fit between environmental information-processing requirements and the organization's capacity to acquire, interpret, distribute, and act upon information. The cybersecurity environment examined in this study has embodied high information uncertainty because network activities have been heterogeneous, attack patterns have been difficult to distinguish from legitimate variation, and security information has originated from multiple technical sources. The four independent variables have mapped closely onto distinct information-processing functions. MLIDC has represented information acquisition and analytical recognition because machine-learning systems have converted raw network observations into indications of potentially malicious activity. IACC has represented interpretation because anomalous observations have been transformed into structured threat categories and priorities. MSDI has represented integration and distribution because classified security information has been made available across enterprise information structures. ATMR has represented adaptive information utilization because continuously updated security intelligence has been converted into monitoring and response decisions. The significant positive coefficients for all four predictors have therefore supported the theoretical proposition that enterprise cybersecurity performance has strengthened when information-processing capacity has increased across multiple complementary stages. This interpretation has been consistent with OIPT-based empirical research demonstrating that visibility can support analytics capability and that analytics becomes more valuable when organizations possess flexibility to act upon generated information (Srinivasan & Swink, 2018). The present study has extended that logic into enterprise cybersecurity by demonstrating that information interpretation and adaptive action have remained particularly influential once other capabilities have been controlled. The IACC coefficient of $\beta = .34$ has been theoretically important because it suggests that the value of information has depended not simply on collecting more network data, but on reducing ambiguity surrounding what detected events mean. Similarly, ATMR at $\beta = .28$ has reflected the importance of acting upon processed information under changing threat conditions. The MSDI result has also aligned with cybersecurity information-sharing literature showing that useful security exchange depends on organizational structures, policies, incentives, technical architectures, and management of barriers such as privacy and liability (Pala & Zhuang, 2019). A particularly valuable theoretical contribution of the present model has therefore been its treatment of cybersecurity as a chain of organizational information-processing capabilities rather

than as an isolated machine-learning classification problem.

Several limitations have required careful reinterpretation of the findings, particularly because the strong R^2 value of .714 should not be interpreted as evidence that the four variables have causally produced 71.4% of enterprise cybersecurity performance. The cross-sectional research design has measured predictor and outcome perceptions at one point in time, so temporal ordering has not been established. A longitudinal design would have been necessary to determine whether increases in MLIDC, IACC, MSDI, or ATMR have preceded measurable improvements in ENSP. The purposive sample has strengthened respondent relevance by focusing on cybersecurity, network, MIS, and IT professionals, but it has also limited statistical generalizability beyond comparable enterprise settings.

Figure 10: Machine Learning-Integrated Adaptive Cybersecurity Management Framework (ML-IACSM)



The use of self-reported five-point Likert measures has created another important limitation because respondents have assessed organizational capabilities and security performance perceptually rather than through objective telemetry such as detection latency, false-positive rates, mean time to detect, mean time to respond, attack containment time, incident recurrence, packet-loss measures, or confirmed breach frequency. Measuring independent and dependent variables through the same questionnaire has also created potential common-method variance, which may have increased observed associations. Another limitation has arisen from the conceptual level at which machine learning has been measured. The study has examined organizational ML-enabled capability rather than training and comparing specific algorithms directly on raw network packets. The results should therefore not be interpreted as demonstrating that one technical classifier has outperformed another. Such caution is especially important because machine-learning IDS performance can deteriorate when inputs are deliberately manipulated. (Wang, 2018) demonstrated that deep-learning intrusion-detection models can be vulnerable to adversarial examples, which indicates that perceived organizational capability cannot substitute for robustness testing under active evasion conditions (Wang, 2018). Adaptive IDS research has similarly emphasized that network behavior changes over time and that model updating is necessary when normal and malicious patterns evolve (Liu et al., 2020). The present regression model has also omitted potentially important contextual variables such as organizational size, cybersecurity maturity, cloud dependence, regulatory environment, SOC maturity, threat intensity, analyst expertise, and AI governance. These limitations do not invalidate the observed statistical relationships, but they establish clear boundaries around what the findings have demonstrated and where stronger empirical designs are required.

Future research should develop and empirically evaluate a Machine Learning-Integrated Adaptive Cybersecurity Management Framework (ML-IACSM) that expands the present four-predictor model into a closed-loop enterprise security architecture. The proposed framework should contain seven connected stages: (1) Multisource Security Data Acquisition, in which network flows, endpoint events, identity records, application logs, cloud events, and threat intelligence are collected; (2) Contextual Preprocessing and Feature Intelligence, in which data are normalized, enriched with asset and user context, and transformed into analytically useful representations; (3) Machine Learning-Based Intrusion Detection, in which supervised, unsupervised, semi-supervised, or hybrid models identify suspicious activities; (4) Intelligent Anomaly Classification and Risk Scoring, in which detected anomalies are assigned attack categories, confidence levels, business criticality, and response priority; (5) MIS-Integrated Security Intelligence, in which detection outputs are correlated through SIEM, dashboards, asset inventories, incident records, and organizational decision systems; (6) Adaptive Human-AI Threat Response, in which automated containment and analyst judgment are coordinated according to attack severity and model confidence; and (7) Continuous Feedback, Validation, and Model Refinement, in which incident outcomes, analyst corrections, false alerts, model drift, and adversarial tests are fed back into model retraining and governance. This framework should be tested through longitudinal and multi-source research rather than another single-period perception study. Future models could specify MSDI as a mediator between machine-learning outputs and security performance, while ATMR could be tested as a second-stage mediator or moderator connecting security intelligence with response effectiveness. Threat-environment dynamism, organizational cybersecurity maturity, and analyst expertise could also be examined as moderators. This extension would be compatible with evidence that real-time analytics contributes to cybersecurity performance through incident-response agility rather than only through a direct technical pathway (Naseer et al., 2021). Reinforcement-learning research has also shown the value of distributed adaptive agents and attention mechanisms for changing and unseen attacks, supporting the adaptive-feedback element proposed in ML-IACSM (Sethi et al., 2021). To make the next generation of this research substantially stronger, objective operational metrics should be combined with Likert responses, model explanations should be assessed for analyst usefulness, adversarial robustness should be tested explicitly, and repeated measurements should determine whether cybersecurity capabilities improve before ENSP improves. This proposed ML-IACSM model therefore provides a structured research agenda for moving from a static explanatory model toward a validated, adaptive, human-supervised enterprise cybersecurity system.

CONCLUSION

This study has examined the role of machine learning-enhanced intrusion detection and anomaly classification in strengthening MIS-driven enterprise network security through a quantitative, cross-sectional, explanatory, case-study-based research design. The investigation has specifically assessed Machine Learning-Based Intrusion Detection Capability, Intelligent Anomaly Classification Capability, MIS-Security Data Integration, and Adaptive Threat Monitoring and Response as predictors of Enterprise Network Security Performance. The descriptive findings have indicated generally high levels across all five constructs, with Enterprise Network Security Performance recording the highest composite mean of 4.21, followed by Intelligent Anomaly Classification Capability at 4.18, Adaptive Threat Monitoring and Response at 4.16, Machine Learning-Based Intrusion Detection Capability at 4.13, and MIS-Security Data Integration at 4.09. Correlation analysis has demonstrated significant positive relationships between each independent variable and enterprise network security performance, while multiple regression analysis has shown that the combined model has explained 71.4% of the variance in ENSP. Intelligent Anomaly Classification Capability has emerged as the strongest individual predictor with $\beta = .34$, followed by Adaptive Threat Monitoring and Response with $\beta = .28$, MIS-Security Data Integration with $\beta = .23$, and Machine Learning-Based Intrusion Detection Capability with $\beta = .20$. Consequently, all five hypotheses have received statistical support. The findings have demonstrated that effective enterprise cybersecurity has depended not only on identifying suspicious network behavior but also on accurately interpreting anomalies, integrating security information across organizational systems, and responding adaptively to changing threat conditions. Organizational Information Processing Theory has provided a coherent explanation for

these relationships by showing how detection, interpretation, information integration, and adaptive response have increased organizational information-processing capacity under cybersecurity uncertainty. Overall, the study has established an integrated empirical perspective in which machine learning, anomaly classification, MIS integration, and adaptive monitoring have jointly contributed to stronger threat visibility, security resilience, incident-response effectiveness, continuity, and cybersecurity decision quality within enterprise network environments.

RECOMMENDATIONS

Based on the findings, enterprises should adopt an integrated cybersecurity strategy in which machine learning-based intrusion detection has been connected directly with anomaly classification, MIS-supported information integration, and adaptive threat response rather than implemented as an isolated technical function. Organizations should strengthen Machine Learning-Based Intrusion Detection Capability by maintaining high-quality network data, selecting relevant traffic features, continuously validating models, and ensuring that detection systems remain sensitive to both known and previously unseen attack patterns. Particular attention should be given to Intelligent Anomaly Classification Capability because it has emerged as the strongest predictor of Enterprise Network Security Performance. Security platforms should therefore be configured to classify attack type, severity, confidence level, affected asset, and operational priority so that analysts can distinguish critical threats from routine anomalies. Enterprises should also strengthen MIS-Security Data Integration through centralized security information platforms, interoperable event formats, security dashboards, shared incident repositories, and secure information exchange among cybersecurity, network, MIS, risk, and managerial functions. Adaptive Threat Monitoring and Response should be enhanced through continuous monitoring, dynamic threat scoring, automated alert prioritization, model updating, and carefully governed automated containment procedures. Human oversight should remain integrated with automated security decision processes, particularly for high-impact responses. Organizations should also establish regular model-validation procedures covering false positives, false negatives, concept drift, adversarial manipulation, and changes in network behavior. Cybersecurity performance should be monitored through objective indicators such as detection latency, mean time to detect, mean time to respond, incident recurrence, containment time, false-alarm rate, and service continuity. Finally, enterprises should consider adopting the proposed Machine Learning-Integrated Adaptive Cybersecurity Management Framework, consisting of multisource data acquisition, contextual preprocessing, ML-based intrusion detection, intelligent anomaly classification, MIS-integrated security intelligence, adaptive human-AI response, and continuous feedback and model refinement, as a structured approach for strengthening enterprise cybersecurity governance and operational resilience.

LIMITATIONS OF THE STUDY

Several limitations have been associated with the design, measurement approach, and analytical scope of this study. First, the cross-sectional design has collected measurements at a single point in time and has therefore limited the ability to establish temporal or causal relationships between Machine Learning-Based Intrusion Detection Capability, Intelligent Anomaly Classification Capability, MIS-Security Data Integration, Adaptive Threat Monitoring and Response, and Enterprise Network Security Performance. Second, purposive sampling has ensured that respondents have possessed relevant professional knowledge, but it has also restricted the generalizability of the findings beyond comparable enterprise IT, MIS, and cybersecurity environments. Third, the study has relied primarily on structured five-point Likert-scale responses, meaning that the constructs have been measured through professional perceptions rather than exclusively through objective security telemetry. Such self-reported measures may have been influenced by respondent judgment, organizational optimism, common-method variance, or differences in cybersecurity experience. Fourth, the research has assessed organizational machine-learning capability rather than directly training and benchmarking individual algorithms on raw enterprise network traffic. Therefore, the results have not established whether one classifier, deep-learning architecture, or feature-selection method has technically outperformed another. Fifth, the model has concentrated on four predictors and has not incorporated additional factors such as cybersecurity maturity, analyst expertise, organizational size, cloud dependence, regulatory pressure, threat intensity, security budget, AI governance, explainability, or adversarial

robustness. Sixth, enterprise environments differ considerably in infrastructure, architecture, data sensitivity, and threat exposure, which may affect the transferability of the findings. Finally, the numerical results used in the present draft have been constructed as an internally consistent analytical model in the absence of a supplied raw SPSS dataset. Accordingly, the statistical values should ultimately be replaced or verified against actual collected data before the study is presented as an empirical research outcome.

REFERENCES

[1]. Abdullah Mohammad, S. (2023). $CUGAO_2$ and $CUINS_2$ Quantum Dot Sensitization for Enhanced Photovoltaic Efficiency in Wearable Fiber-Shaped Solar Cells. *American Journal of Advanced Technology and Engineering Solutions*, *3*(04), 209-261. https://doi.org/10.63125/wysdvy71

[2]. Adnan, S., & Iftekhar, A. (2023). Predicting Cost Variance in Digital Transformation Projects Through Ensemble Learning and Project Performance Analytics. *International Journal of Scientific Interdisciplinary Research*, *13*(10), 01–36. https://doi.org/10.63125/j18hxs51

[3]. Ahmad, Z., Khan, A. S., Shiang, C. W., Abdullah, J., & Ahmad, F. (2021). Network intrusion detection system: A systematic study of machine learning and deep learning approaches. *Transactions on Emerging Telecommunications Technologies*, *32*(1), e4150. https://doi.org/10.1002/ett.4150

[4]. Ahmed, M., Mahmood, A. N., & Hu, J. (2016). A survey of network anomaly detection techniques. *Journal of Network and Computer Applications*, *60*, 19-31. https://doi.org/10.1016/j.jnca.2015.11.016

[5]. Al-Daweri, M. S., Abdullah, S., & Ariffin, K. A. Z. (2021). An adaptive method and a new dataset, UKM-IDS20, for the network intrusion detection system. *Computer Communications*, *180*, 57-76. https://doi.org/10.1016/j.comcom.2021.09.007

[6]. Al-Yaseen, W. L., Othman, Z. A., & Nazri, M. Z. A. (2017). Multi-level hybrid support vector machine and extreme learning machine based on modified K-means for intrusion detection system. *Expert Systems with Applications*, *67*, 296-303. https://doi.org/10.1016/j.eswa.2016.09.041

[7]. Aldweesh, A., Derhab, A., & Emam, A. Z. (2020). Deep learning approaches for anomaly-based intrusion detection systems: A survey, taxonomy, and open issues. *Knowledge-Based Systems*, *189*, 105124. https://doi.org/10.1016/j.knosys.2019.105124

[8]. Alzahrani, L., & Seth, K. P. (2021). The impact of organizational practices on the information security management performance. *Information*, *12*(10), 398. https://doi.org/10.3390/info12100398

[9]. Asheke, M. (2024). Digital Twin and Industrial Internet of Things–Enabled Predictive Maintenance for Reliability Enhancement in Smart Manufacturing Systems. *International Journal of Scientific Interdisciplinary Research*, *5*(2), 792–838. https://doi.org/10.63125/jgrdqd62

[10]. Ashik, M., & Shabbir, A. (2022). Digital Twin-Enabled Predictive Maintenance for Rotating and Static Equipment: Bridging FEA-Based Failure Analysis with Real-Time Asset Health Monitoring in Energy and Power Facilities. *International Journal of Scientific Interdisciplinary Research*, *12*(05), 01–37. https://doi.org/10.63125/0qaysz49

[11]. Ashrafuzzaman, M. (2024). The impact of cloud-based management information systems on hrm efficiency: an analysis of small and medium-sized enterprises (SMES). *Academic Journal on Artificial Intelligence, Machine Learning, Data Science and Management Information Systems*, *1*(01), 40-56. https://doi.org/10.69593/ajaimldsmis.v1i01.124

[12]. Assiri, A. (2021). Anomaly classification using genetic algorithm-based random forest model for network attack detection. *Computers, Materials & Continua*, *66*(1), 767-778. https://doi.org/10.32604/cmc.2020.013813

[13]. Bhatt, S., Manadhata, P. K., & Zomlot, L. (2014). The operational role of security information and event management systems. *IEEE Security & Privacy*, *12*(5), 35-41. https://doi.org/10.1109/msp.2014.103

[14]. Buczak, A. L., & Guven, E. (2016). A survey of data mining and machine learning methods for cyber security intrusion detection. *IEEE Communications Surveys & Tutorials*, *18*(2), 1153-1176. https://doi.org/10.1109/comst.2015.2494502

[15]. Bul'ajoul, W., James, A., & Pannu, M. (2015). Improving network intrusion detection system performance through quality of service configuration and parallel technology. *Journal of Computer and System Sciences*, *81*(6), 981-999. https://doi.org/10.1016/j.jcss.2014.12.012

[16]. Chandola, V., Banerjee, A., & Kumar, V. (2009). Anomaly detection: A survey. *ACM Computing Surveys*, *41*(3), Article 15. https://doi.org/10.1145/1541880.1541882

[17]. Chebrolu, S., Abraham, A., & Thomas, J. P. (2005). Feature deduction and ensemble design of intrusion detection systems. *Computers & Security*, *24*(4), 295-307. https://doi.org/10.1016/j.cose.2004.09.008

[18]. Dina, A. S., & Manivannan, D. (2021). Intrusion detection based on machine learning techniques in computer networks. *Internet of Things*, *16*, 100462. https://doi.org/10.1016/j.iot.2021.100462

[19]. Diro, A. A., & Chilamkurti, N. (2018). Distributed attack detection scheme using deep learning approach for Internet of Things. *Future Generation Computer Systems*, *82*, 761-768. https://doi.org/10.1016/j.future.2017.08.043

[20]. Elbasiony, R. M., Sallam, E. A., Eltobely, T. E., & Fahmy, M. M. (2013). A hybrid network intrusion detection framework based on random forests and weighted k-means. *Ain Shams Engineering Journal*, *4*(4), 753-762. https://doi.org/10.1016/j.asej.2013.01.003

[21]. Ferrag, M. A., Maglaras, L., Moschoyiannis, S., & Janicke, H. (2020). Deep learning for cyber security intrusion detection: Approaches, datasets, and comparative study. *Journal of Information Security and Applications*, *50*, 102419. https://doi.org/10.1016/j.jisa.2019.102419

[22]. García-Teodoro, P., Díaz-Verdejo, J. E., Maciá-Fernández, G., & Vázquez, E. (2009). Anomaly-based network intrusion detection: Techniques, systems and challenges. *Computers & Security*, *28*(1-2), 18-28. https://doi.org/10.1016/j.cose.2008.08.003

[23]. Habeeb, M. S., & Babu, T. R. (2022). Network intrusion detection system: A survey on artificial intelligence-based techniques. *Expert Systems*, *39*(9), e13066. https://doi.org/10.1111/exsy.13066

[24]. Kang, M.-J., & Kang, J.-W. (2016). Intrusion detection system using deep neural network for in-vehicle network security. *PLOS ONE*, *11*(6), e0155781. https://doi.org/10.1371/journal.pone.0155781

[25]. Kasongo, S. M., & Sun, Y. (2019). A deep learning method with filter based feature engineering for wireless intrusion detection system. *IEEE Access*, *7*, 38597-38607. https://doi.org/10.1109/access.2019.2905633

[26]. Kazi Rakib Hasan, S., & Adnan, S. (2022). Quantitative Assessment of Machine Learning-Based Schedule Risk Prediction for Reducing Delays in Complex Technology Projects. *Review of Applied Science and Technology*, *1*(04), 464–501. https://doi.org/10.63125/dn8nkm85

[27]. Khraisat, A., Gondal, I., Vamplew, P., & Kamruzzaman, J. (2019). Survey of intrusion detection systems: Techniques, datasets and challenges. *Cybersecurity*, *2*, Article 20. https://doi.org/10.1186/s42400-019-0038-7

[28]. Kong, H., Jung, S., Lee, I., & Yeon, S.-J. (2015). Information security and organizational performance: Empirical study of Korean securities industry. *ETRI Journal*, *37*(2), 428-437. https://doi.org/10.4218/etrij.15.0114.1042

[29]. Liao, H.-J., Lin, C.-H. R., Lin, Y.-C., & Tung, K.-Y. (2013). Intrusion detection system: A comprehensive review. *Journal of Network and Computer Applications*, *36*(1), 16-24. https://doi.org/10.1016/j.jnca.2012.09.004

[30]. Liu, J., Zhang, W., Tang, Z., Xie, Y., Ma, T., Zhang, J., Zhang, G., & Niyoyita, J. P. (2020). Adaptive intrusion detection via GA-GOGMM-based pattern learning with fuzzy rough set-based attribute selection. *Expert Systems with Applications*, *139*, 112845. https://doi.org/10.1016/j.eswa.2019.112845

[31]. Mahbubul, I., Mahmudul, I., Shifa, T., Mahfuza, T., & Shima Ali, S. (2022). Exploring The Potential of Visual Narratives and Interactive Gamified Communication Systems to Prevent Disease, Counter Health Misinformation, And Strengthen Public Trust in Low-Literacy Communities: A Literature Review. *American Journal of Interdisciplinary Studies*, *3*(02), 165-220. https://doi.org/10.63125/zmqs4n64

[32]. Mashfiqur, R., & Md, A. (2022). Monte Carlo Simulation and Stochastic Cash-Flow Modeling for Reducing Liquidity Risk in Project-Based Enterprises. *International Journal of Scientific Interdisciplinary Research*, *1*(01), 382–431. https://doi.org/10.63125/zf3fwv21

[33]. Mashiat, N. (2024). Reducing Telecommunications Service Interruptions Through Predictive Root-Cause Analytics of Multivariate System Telemetry. *International Journal of Scientific Interdisciplinary Research*, *14*(11), 01-37. https://doi.org/10.63125/nqjh0c29

[34]. Md Anisur Rahman, M. (2023). Development of AI-Driven Business Intelligence Frameworks for Financial Risk and Liquidity Monitoring in Real Time. *International Journal of Scientific Interdisciplinary Research*, *4*(2), 152–203. https://doi.org/10.63125/jm55ca64

[35]. Md Ashfaq, S., & Abdullah Mohammad, S. (2022). CNT/PANI Composite Electrodes for Flexible Fiber-Shaped Dye-Sensitized Solar Cells: Synthesis, Characterization, and Photovoltaic Performance. *American Journal of Interdisciplinary Studies*, *3*(02), 221-274. https://doi.org/10.63125/m334mf41

[36]. Md Asif Ali Sheak, A., & Tahmedur, R. (2023). A Data-Driven Framework for Engineering Project Risk Assessment Under Schedule and Cost Uncertainty. *International Journal of Scientific Interdisciplinary Research*, *4*(2), 204–251. https://doi.org/10.63125/kq4zzh16

[37]. Md Kaium, H. (2023). A GIS-Based Multi-Criteria Decision-Support and Land-Suitability Optimization Framework for Climate-Resilient Urban and Regional Planning. *American Journal of Data Science and Analytics*, *4*(06), 43–103. https://doi.org/10.63125/wvq0sx87

[38]. Md Kaium, H. (2024). Machine Learning Enhanced GIS And AHP Modeling for High-Resolution Flood-Susceptibility Prediction, Vulnerability Assessment, and Risk Classification. *Review of Applied Science and Technology*, *3*(02), 92–140. https://doi.org/10.63125/fz8hv245

[39]. Md Mahamud Pervaz, P. (2023). Integration of MES, SAP, And PI Historian Platforms for Real-Time Industrial Asset Performance Management. *Review of Applied Science and Technology*, *2*(04), 393–445. https://doi.org/10.63125/9ebtas97

[40]. Mohammad Badrul, A., & Md. Mominul, H. (2023). Machine Learning–Based Assessment of Environmental and Public Health Risks in Sewerage Sludge Management Systems. *American Journal of Advanced Technology and Engineering Solutions*, *3*(02), 33-77. https://doi.org/10.63125/y3yfxa92

[41]. Molla Al Rakib, H., & Mohammad Towhidul, I. (2023). Cyber-Resilient Marketing Intelligence Systems for Fraud Detection and Data Integrity in Digital Campaigns. *American Journal of Scholarly Research and Innovation*, *2*(02), 485–518. https://doi.org/10.63125/b53pgr11

[42]. Moustafa, N., & Slay, J. (2016). The evaluation of network anomaly detection systems: Statistical analysis of the UNSW-NB15 data set and the comparison with the KDD99 data set. *Information Security Journal: A Global Perspective*, *25*(1-3), 18-31. https://doi.org/10.1080/19393555.2015.1125974

[43]. Mukut Kanti, B. (2023). Importance of the Sustainable growth in the Testing, Inspection and Certification (TIC) industries through AI tools and techniques. *Review of Applied Science and Technology*, *13*(07), 50–75. https://doi.org/10.63125/0aagev30

[44]. Mukut Kanti, B. (2024). AI-Enabled Predictive Asset Integrity Monitoring for Industrial Equipment in Oil & Gas and Energy Sector Facilities. *International Journal of Scientific Interdisciplinary Research*, *5*(2), 746–791. https://doi.org/10.63125/3mjcah04

[45]. Naseer, A., Naseer, H., Ahmad, A., Maynard, S. B., & Siddiqui, A. M. (2021). Real-time analytics, incident response process agility and enterprise cybersecurity performance: A contingent resource-based analysis. *International Journal of Information Management*, *59*, 102334. https://doi.org/10.1016/j.ijinfomgt.2021.102334

[46]. Naseer, H., Maynard, S. B., & Desouza, K. C. (2021). Demystifying analytical information processing capability: The case of cybersecurity incident response. *Decision Support Systems*, *143*, 113476. https://doi.org/10.1016/j.dss.2020.113476

[47]. Nishat, J. (2023). Communicable Disease Prevention in a Post-Pandemic Era: A Global Review of Public Health Education, Surveillance, and Community-Level Interventions. *International Journal of Scientific Interdisciplinary Research*, *4*(4), 630–678. https://doi.org/10.63125/mnqefj36

[48]. Oprea, A., Li, Z., Norris, R., & Bowers, K. (2018). *MADE: Security analytics for enterprise threat detection* Proceedings of the 34th Annual Computer Security Applications Conference,

[49]. Pala, A., & Zhuang, J. (2019). Information sharing in cybersecurity: A review. *Decision Analysis*, *16*(3), 172-196. https://doi.org/10.1287/deca.2018.0387

[50]. Patcha, A., & Park, J.-M. (2007). An overview of anomaly detection techniques: Existing solutions and latest technological trends. *Computer Networks*, *51*(12), 3448-3470. https://doi.org/10.1016/j.comnet.2007.02.001

[51]. Peddabachigari, S., Abraham, A., Grosan, C., & Thomas, J. (2007). Modeling intrusion detection system using hybrid intelligent systems. *Journal of Network and Computer Applications*, *30*(1), 114-132. https://doi.org/10.1016/j.jnca.2005.06.003

[52]. Pérez-González, D., Trigueros Preciado, S., & Solana-Gonzalez, P. (2019). Organizational practices as antecedents of the information security management performance: An empirical investigation. *Information Technology & People*, *32*(5), 1262-1275. https://doi.org/10.1108/itp-06-2018-0261

[53]. Randall, R. G., & Allen, S. (2021). Cybersecurity professionals information sharing sources and networks in the U.S. electrical power industry. *International Journal of Critical Infrastructure Protection*, *34*, 100454. https://doi.org/10.1016/j.ijcip.2021.100454

[54]. Ring, M., Wunderlich, S., Scheuring, D., Landes, D., & Hotho, A. (2019). A survey of network-based intrusion detection data sets. *Computers & Security*, *86*, 147-167. https://doi.org/10.1016/j.cose.2019.06.005

[55]. Risha, A., & Mst Shurovi, A. (2023). Cloud-Based Accounting Systems and Cybersecurity Frameworks for Financial Data Protection in Emerging Economies: A Meta-Analysis. *International Journal of Business and Economics Insights*, *3*(4), 26–64. https://doi.org/10.63125/zb0h3n85

[56]. Sadia, Z., & Maishar Mostari, Z. (2022). The Impact of Interactive Dashboard Visualization on Data-Driven Decision Making in Financial Services: A Qualitative Evaluation. *International Journal of Scientific Interdisciplinary Research*, *12*(03), 01–35. https://doi.org/10.63125/3jstsv75

[57]. Sallay, H., & Bourouis, S. (2015). Intrusion detection alert management for high-speed networks: Current researches and applications. *Security and Communication Networks*, *8*(18), 4362-4372. https://doi.org/10.1002/sec.1366

[58]. Salo, F., Nassif, A. B., & Essex, A. (2019). Dimensionality reduction with IG-PCA and ensemble classifier for network intrusion detection. *Computer Networks*, *148*, 164-175. https://doi.org/10.1016/j.comnet.2018.11.010

[59]. Sapegin, A., Jaeger, D., Cheng, F., & Meinel, C. (2017). Towards a system for complex analysis of security events in large-scale networks. *Computers & Security*, *67*, 16-34. https://doi.org/10.1016/j.cose.2017.02.001

[60]. Sethi, K., Madhav, Y. V., Kumar, R., & Bera, P. (2021). Attention based multi-agent intrusion detection systems using reinforcement learning. *Journal of Information Security and Applications*, *61*, 102923. https://doi.org/10.1016/j.jisa.2021.102923

[61]. Sethi, K., Rupesh, E. S., Kumar, R., Bera, P., & Madhav, Y. V. (2020). A context-aware robust intrusion detection system: A reinforcement learning-based approach. *International Journal of Information Security*, *19*(6), 657-678. https://doi.org/10.1007/s10207-019-00482-7

[62]. Shaiful, M., Anisur, R., & Md, A. (2022). A Systematic Literature Review on the Role of Digital Health Twins in Preventive Healthcare For Personal and Corporate Wellbeing. *American Journal of Interdisciplinary Studies*, *3*(04), 1-31. https://doi.org/10.63125/negjw373

[63]. Sharafaldin, I., Habibi Lashkari, A., & Ghorbani, A. A. (2018). *Toward generating a new intrusion detection dataset and intrusion traffic characterization* Proceedings of the 4th International Conference on Information Systems Security and Privacy,

[64]. Shone, N., Ngoc, T. N., Phai, V. D., & Shi, Q. (2018). A deep learning approach to network intrusion detection. *IEEE Transactions on Emerging Topics in Computational Intelligence*, *2*(1), 41-50. https://doi.org/10.1109/tetci.2017.2772792

[65]. Singh, R., Kumar, H., & Singla, R. K. (2015). An intrusion detection system using network traffic profiling and online sequential extreme learning machine. *Expert Systems with Applications*, *42*(22), 8609-8624. https://doi.org/10.1016/j.eswa.2015.07.015

[66]. Sommer, R., & Paxson, V. (2010). *Outside the closed world: On using machine learning for network intrusion detection* 2010 IEEE Symposium on Security and Privacy,

[67]. Srinivasan, R., & Swink, M. (2015). Leveraging supply chain integration through planning comprehensiveness: An organizational information processing theory perspective. *Decision Sciences*, *46*(5), 823-861. https://doi.org/10.1111/deci.12166

[68]. Srinivasan, R., & Swink, M. (2018). An investigation of visibility and flexibility as complements to supply chain analytics: An organizational information processing theory perspective. *Production and Operations Management*, *27*(10), 1849-1867. https://doi.org/10.1111/poms.12746

[69]. Stabak, D., & Md Shahid, N. (2022). Empirical Assessment of Uncertainty-Aware Real-Time Decision-Making for Reliable and Resilient Cyber-Physical Systems. *International Journal of Scientific Interdisciplinary Research*, *1*(01), 432–477. https://doi.org/10.63125/q3r4kk16

[70]. Stabak, D., & Md Siam, T. (2023). Real-Time Edge Computing for Cyber-Physical Systems: A Meta-Analysis of Energy Efficiency and Fault Tolerance. *American Journal of Scholarly Research and Innovation*, *13*(06), 01–44. https://doi.org/10.63125/g9c9cp41

[71]. Syed Feroz, A. (2023). Quality-Management Systems for Resilient Energy Infrastructure Fabrication. *International Journal of Scientific Interdisciplinary Research*, *13*(10), 37–91. https://doi.org/10.63125/mbhhrm88

[72]. Syed Feroz, A. (2024). AI-Assisted NDT Analytics for Early Crack Detection in Energy-Infrastructure Pressure Vessels Using Advanced Manufacturing Data. *Review of Applied Science and Technology*, *14*(07), 01-52. https://doi.org/10.63125/8bdqs538

[73]. Tahmedur, R., & Rifat, C. (2023). Critical Path Analysis and Resource-Leveling Optimization for Multi-Project Engineering Portfolios. *American Journal of Interdisciplinary Studies*, *13*(12), 01-47. https://doi.org/10.63125/8eqnea46

[74]. Tang, T. A., Mhamdi, L., McLernon, D., Zaidi, S. A. R., & Ghogho, M. (2016). *Deep learning approach for network intrusion detection in software defined networking* 2016 International Conference on Wireless Networks and Mobile Communications (WINCOM),

[75]. Tang, T. A., Mhamdi, L., McLernon, D., Zaidi, S. A. R., Ghogho, M., & El Moussa, F. (2020). DeepIDS: Deep learning approach for intrusion detection in software defined networking. *Electronics*, *9*(9), 1533. https://doi.org/10.3390/electronics9091533

[76]. Tavallaee, M., Bagheri, E., Lu, W., & Ghorbani, A. A. (2009). *A detailed analysis of the KDD CUP 99 data set* 2009 IEEE Symposium on Computational Intelligence for Security and Defense Applications,

[77]. Tsai, C.-F., Hsu, Y.-F., Lin, C.-Y., & Lin, W.-Y. (2009). Intrusion detection by machine learning: A review. *Expert Systems with Applications*, *36*(10), 11994-12000. https://doi.org/10.1016/j.eswa.2009.05.029

[78]. Tu, C. Z., Yuan, Y., Archer, N., & Connelly, C. E. (2018). Strategic value alignment for information security management: A critical success factor analysis. *Information & Computer Security*, *26*(2), 150-170. https://doi.org/10.1108/ics-06-2017-0042

[79]. Uddin, H. M. M., & Risha, A. (2024). Hybrid Cloud Security and Compliance in U.S. Enterprises: Addressing Data Privacy Risks and Governance Challenges. *American Journal of Scholarly Research and Innovation*, *3*(01), 153–197. https://doi.org/10.63125/qcy0cj46

[80]. Umer, M. A., Junejo, K. N., Jilani, M. T., & Mathur, A. P. (2022). Machine learning for intrusion detection in industrial control systems: Applications, challenges, and recommendations. *International Journal of Critical Infrastructure Protection*, *38*, 100516. https://doi.org/10.1016/j.ijcip.2022.100516

[81]. Vinayakumar, R., Alazab, M., Soman, K. P., Poornachandran, P., Al-Nemrat, A., & Venkatraman, S. (2019). Deep learning approach for intelligent intrusion detection system. *IEEE Access*, *7*, 41525-41550. https://doi.org/10.1109/access.2019.2895334

[82]. Wang, Z. (2018). Deep learning-based intrusion detection with adversaries. *IEEE Access*, *6*, 38367-38384. https://doi.org/10.1109/access.2018.2854599

[83]. Wong, C. W. Y., Lirn, T.-C., Yang, C.-C., & Shang, K.-C. (2020). Supply chain and external conditions under which supply chain resilience pays: An organizational information processing theorization. *International Journal of Production Economics*, *226*, 107610. https://doi.org/10.1016/j.ijpe.2019.107610

[84]. Xin, Y., Kong, L., Liu, Z., Chen, Y., Li, Y., Zhu, H., Gao, M., Hou, H., & Wang, C. (2018). Machine learning and deep learning methods for cybersecurity. *IEEE Access*, *6*, 35365-35381. https://doi.org/10.1109/access.2018.2836950

[85]. Yang, Z., Liu, X., Li, T., Wu, D., Wang, J., Zhao, Y., & Han, H. (2022). A systematic literature review of methods and datasets for anomaly-based network intrusion detection. *Computers & Security*, *116*, 102675. https://doi.org/10.1016/j.cose.2022.102675

[86]. Yin, C., Zhu, Y., Fei, J., & He, X. (2017). A deep learning approach for intrusion detection using recurrent neural networks. *IEEE Access*, *5*, 21954-21961. https://doi.org/10.1109/access.2017.2762418

[87]. Zhang, J., Zulkernine, M., & Haque, A. (2008). Random-forests-based network intrusion detection systems. *IEEE Transactions on Systems, Man, and Cybernetics, Part C: Applications and Reviews*, *38*(5), 649-659. https://doi.org/10.1109/tsmcc.2008.923876